Package 'seecolor'

July 23, 2025

Title View Colors Used in R Objects in the Console

Version 0.2.0

Description Output colors used in literal vectors, palettes and plot objects (ggplot).

Imports dplyr, crayon, purrr, stringr, rstudioapi, magrittr, ggplot2, fansi

License MIT + file LICENSE

URL https://github.com/lovestat/seecolor

BugReports https://github.com/lovestat/seecolor/issues

Encoding UTF-8

RoxygenNote 7.1.1

Suggests covr, knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Author Shangchen Song [aut, cre]

Maintainer Shangchen Song <s.song@ufl.edu>

Repository CRAN

Date/Publication 2023-02-24 16:50:02 UTC

Contents

open_sample 2
pick_color 2
print_color 3
z_pick_color_addin_mosaic 3
z_pick_color_addin_ribbon 4

Index **5**

open_sample *Open the sample test file*

Description

Open the sample test file

Usage

```
open_sample()
```

pick_color *Select object by cursor and show colors in the console*

Description

Simply highlight the text in the Source panel and the colors used in the specific object will be output in the console

Usage

```
pick_color(type = "mosaic", blank.len = 3)
```

Arguments

type	A character. The style of printing. The default is mosaic. It should be one of the mosaic, ribbon, or m, r
blank.len	A integer. The length of color mosaic. The default value is 3.

Examples

```
pick_color(type = "mosaic", blank.len = 3)
pick_color(type = "ribbon", blank.len = 3)
```

print_color *Print the colors*

Description

Print out the colors used by a literal vector, a palette, or a ggplot object

Usage

```
print_color(x, type = "mosaic", blank.len = 3)
```

Arguments

x	A literal vector, a palette, or a ggplot object
type	A character. The style of printing. The default is mosaic. It should be one of the mosaic, ribbon, or m, r
blank.len	A integer. The length of color mosaic. The default value is 3.

Examples

```
print_color(colors(), type = "mosaic", blank.len = 3)
print_color(palette(), type = "ribbon")
```

z_pick_color_addin_mosaic *Pick Color as Mosaic*

Description

Run pick_color(type = 'mosaic') as addin, you may not run this directly by code, since it comes without arguments

Usage

```
z_pick_color_addin_mosaic()
```

`z_pick_color_addin_ribbon` *Pick Color as Ribbons*

Description

Run `pick_color(type = 'ribbon')` as addin, you may not run this directly by code, since it comes without arguments

Usage

```
z_pick_color_addin_ribbon()
```

Index

open_sample, 2

pick_color, 2
print_color, 3

z_pick_color_addin_mosaic, 3
z_pick_color_addin_ribbon, 4