

Package ‘sendgridr’

July 23, 2025

Title Mail Sender Using 'Sendgrid' Service

Version 0.6.1

Description Send email using 'Sendgrid' <<https://sendgrid.com/>>
mail API(v3) <[https://docs.sendgrid.com/api-reference/
how-to-use-the-sendgrid-v3-api/authentication](https://docs.sendgrid.com/api-reference/how-to-use-the-sendgrid-v3-api/authentication)>.

License MIT + file LICENSE

URL <https://github.com/mrchypark/sendgridr>

BugReports <https://github.com/mrchypark/sendgridr/issues>

Imports magrittr, httr, jsonlite, usethis, cli, base64enc, emayili (>= 0.7), keyring

Encoding UTF-8

RoxygenNote 7.2.1

Depends R (>= 3.4)

Suggests covr, testthat

NeedsCompilation no

Author Chanyub Park [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-6474-2570>>)

Maintainer Chanyub Park <mrchypark@gmail.com>

Repository CRAN

Date/Publication 2022-11-06 19:00:02 UTC

Contents

address	2
attachments	3
auth_check	3
auth_set	4
body	4
dynamic_template	5
dynamic_template_data	5

embed_rmd	6
from	7
mail	7
print.sg_mail	8
send	8
subject	9
template_id	10
Index	11

address	<i>set address to sg_mail class</i>
---------	-------------------------------------

Description

to(), cc(), bcc() is for set email address to sg_mail class

Usage

```
to(sg_mail, email, name = "")  
  
cc(sg_mail, email, name = "")  
  
bcc(sg_mail, email, name = "")
```

Arguments

- sg_mail (required)mail object from package
- email (required)email address
- name (optional)name for email address.

Value

sg_mail class with mail address.

Examples

```
mail() %>%  
  to("mrchypark@gmail.com")  
  
mail() %>%  
  cc("mrchypark@gmail.com")  
  
mail() %>%  
  bcc("mrchypark@gmail.com")
```

attachments	<i>attachments</i>
-------------	--------------------

Description

attachments

Usage

```
attachments(sg_mail, path, name, content_id)
```

Arguments

sg_mail	(required)mail object from package
path	(required)file path to attach
name	file name. default is path's file name
content_id	content id. default is Null.

Value

sg_mail class with attachments.

Examples

```
path <- system.file("extdata", "test.Rmd", package = "sendgridr")
mail() %>%
  attachments(path)
```

auth_check	<i>Check API key for auth.</i>
------------	--------------------------------

Description

Check API key for auth.

Usage

```
auth_check()
```

Value

TRUE/FALSE check work fine return TRUE.

auth_set	<i>Set API key for auth.</i>
----------	------------------------------

Description

Set API key for auth.

Usage

```
auth_set(apikey)
```

Arguments

apikey	sendgrid api key. If key has value, just use as api key. If without param, function call interactive prompt input.
--------	--

Value

None

body	<i>body</i>
------	-------------

Description

body

Usage

```
body(sg_mail, body, type = "text/html")
```

Arguments

sg_mail	(required)mail object from package
body	(required)mail content html support.
type	content type. text/html is default.

Value

sg_mail class with body content.

Examples

```
mail() %>%  
  body("mrchypark@gmail.com")
```

dynamic_template	<i>Add dynamic template</i>
------------------	-----------------------------

Description

Create dynamic templates at <https://mc.sendgrid.com/dynamic-templates>.

Usage

```
dynamic_template(sg_mail, template_id, template_data, force = FALSE)
```

Arguments

sg_mail	(required) mail object from package
template_id	(required) template_id start "d-" and 32-length only digit and lower case alphabet like "d-4ad23ad40a0e47d0a0232b85f24ca5c2"
template_data	A key-value list for template data. (See https://docs.sendgrid.com/ui/sending-email/how-to-send-an-email-with-dynamic-templates)
force	pass template_id validation. default is FALSE.

Value

sg_mail class with dynamic template

Examples

```
mail() %>%
  dynamic_template("d-4ad23ad40a0e47d0a0232b85f24ca5c2", list(first_name = "Amanda", link = "foo"))

mail() %>%
  dynamic_template(template_id = "foo",
    template_data = list(first_name = "Amanda", link = "foo"),
    force = TRUE)
```

dynamic_template_data	<i>Add dynamic template data</i>
-----------------------	----------------------------------

Description

template_id must be included for this data to be applied.

Usage

```
dynamic_template_data(sg_mail, data)
```

Arguments

`sg_mail` (required) mail object from package

`data` A key-value list for template data. (See <https://docs.sendgrid.com/ui/sending-email/how-to-send-an-email-with-dynamic-templates>)

Value

`sg_mail` class with template data for dynamic transactional templates

Examples

```
data_lst <-
  list(
    first_name = "Amanda",
    link = "foo"
  )

mail() %>%
  template_id("d-4ad23ad40a0e47d0a0232b85f24ca5c2")%>%
  dynamic_template_data(data_lst)
```

embed_rmd	<i>Embedding Rmd on body with images.</i>
-----------	---

Description

Embedding Rmd on body with images.

Usage

```
embed_rmd(sg_mail, input, ...)
```

Arguments

`sg_mail` (required) mail object from package

`input` (required) input file path to render for email.

`...` extra params pass to `emayili::render()` function.

Examples

```
path <- system.file("extdata", "test.Rmd", package = "sendgridr")
mail() %>%
  embed_rmd(path)
```

from	<i>from</i>
------	-------------

Description

from

Usage

```
from(sg_mail, email, name = "")
```

Arguments

sg_mail	(required)mail object from package
email	(required)email address
name	name for email address

Value

sg_mail class with from mail address.

Examples

```
mail() %>%  
  from("mrchypark@gmail.com")
```

mail	<i>Set mail class for Sendgrid</i>
------	------------------------------------

Description

New mail class for sendgrid.

Usage

```
mail()
```

Value

sg_mail class.

Examples

```
mail()
```

<code>print.sg_mail</code>	<i>Print for sg_mail class</i>
----------------------------	--------------------------------

Description

Print for sg_mail class

Usage

```
## S3 method for class 'sg_mail'
print(x, ...)
```

Arguments

<code>x</code>	sg_mail class object
<code>...</code>	pass for default print. But not use in sg_mail class.

<code>send</code>	<i>send mail</i>
-------------------	------------------

Description

Send mail with mail content.

Usage

```
send(mail)
```

Arguments

<code>mail</code>	mail object
-------------------	-------------

Value

[list](https://docs.sendgrid.com/api-reference/how-to-use-the-sendgrid-v3-api/authentication) if success, success message. and error, please check <https://docs.sendgrid.com/api-reference/how-to-use-the-sendgrid-v3-api/authentication>.

Examples

```
## Not run:

data_lst <-
  list(
    total = "$239.85",
    name = "Sample Name"
  )
```



```
mail() %>%
  from("example1@mail.com", "example name for display") %>%
  to("example2@mail.com", "example name for display 2") %>%
  dynamic_template_data(data_lst) %>%
  template_id(template_id) %>%
  subject("test mail title") %>%
  body("hello world!") %>%
  ## attachments is optional
  attachments("report.html") %>%
  send()

## End(Not run)
```

subject	<i>subject</i>
---------	----------------

Description

subject

Usage

subject(sg_mail, subject)

Arguments

- sg_mail (required)mail object from package
- subject (required)mail subject

Value

sg_mail class with subject.

Examples

```
mail() %>%
  subject("mrchypark@gmail.com")
```

template_id	<i>template id</i>
-------------	--------------------

Description

Create dynamic templates at <https://mc.sendgrid.com/dynamic-templates>

Usage

```
template_id(sg_mail, template_id, force = FALSE)
```

Arguments

sg_mail	(required) mail object from package
template_id	(required) template_id start "d-" and 32-length only digit and lower case alphabet like "d-4ad23ad40a0e47d0a0232b85f24ca5c2"
force	pass template_id validation. default is FALSE.

Value

sg_mail class with template id.

Examples

```
mail()>%  
  template_id("d-4ad23ad40a0e47d0a0232b85f24ca5c2")  
  
mail() %>%  
  template_id("foo", force = TRUE)
```

Index

address, [2](#)
attachments, [3](#)
auth_check, [3](#)
auth_set, [4](#)

bcc (address), [2](#)
body, [4](#)

cc (address), [2](#)

dynamic_template, [5](#)
dynamic_template_data, [5](#)

embed_rmd, [6](#)

from, [7](#)

list, [8](#)

mail, [7](#)

print.sg_mail, [8](#)

send, [8](#)
subject, [9](#)

template_id, [10](#)
to (address), [2](#)