Package 'shiny.emptystate'

July 23, 2025

Title Empty State Components for 'Shiny'

Version 0.1.0

Description Offers a comprehensive solution for managing 'empty states' in 'Shiny' applications. It provides tools to create both default and customizable components for scenarios where data is absent or doesn't match user-defined filters. The package prioritizes user experience, ensuring clarity and consistency even when data is not available to display.

URL https://appsilon.github.io/shiny.emptystate/, https://github.com/Appsilon/shiny.emptystate

BugReports https://github.com/Appsilon/shiny.emptystate/issues

License LGPL-3

Imports fontawesome, htmltools, R6, shiny, utils

Suggests bsicons, chromote, covr, knitr, lintr, rcmdcheck, rmarkdown, shinytest2, spelling, testthat (>= 3.0.0), withr

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.2.3

NeedsCompilation no

Author Ryszard Szymański [aut, cre], Recle Vibal [aut], Harsh Verma [ctb], Vedha Viyash [ctb]

Maintainer Ryszard Szymański <opensource+ryszard@appsilon.com>

Repository CRAN

Date/Publication 2023-08-17 06:50:06 UTC

Contents

default_empty_state_component 2
EmptyStateManager 2
empty_state_component 4
use_empty_state 5

Index **7**

`default_empty_state_component` *Default empty state component*

Description

Default empty state component, used when user doesn't provide any value while initializing new EmptyStateManager object.

Usage

```
default_empty_state_component()
```

Value

a shiny.tag.

`EmptyStateManager` *EmptyStateManager R6 class*

Description

Creates an EmptyStateManager to then show or hide content.

Details

Creates an object to show an empty state content on selected id specified by `id` parameter. Then `show` or `hide` or use `is_empty_state_show` to check the status.

Value

EmptyStateManager R6 class

Methods

Public methods:

- `EmptyStateManager$new()`
- `EmptyStateManager$is_empty_state_show()`
- `EmptyStateManager$show()`
- `EmptyStateManager$hide()`
- `EmptyStateManager$clone()`

Method `new()`**:** Creates a new empty state manager object.

Usage:

```
EmptyStateManager$new(
  id,
  html_content = default_empty_state_component(),
  color = NULL
)
```

Arguments:

`id` id of element which should be covered with `html_content`

`html_content` Content for empty state. Defaults to `default_empty_state_component()`

`color` Background color of empty state content. Defaults to `NULL`

Returns: A new `EmptyStateManager` R6 class object.

Method `is_empty_state_show()`**:** Returns the current visibility state of the empty state UI. Defaults to `FALSE`

Usage:

```
EmptyStateManager$is_empty_state_show()
```

Returns: boolean, `TRUE`/`FALSE`

Method `show()`**:** Show empty state component.

Usage:

```
EmptyStateManager$show()
```

Returns: Nothing, it changes state of empty state

Method `hide()`**:** Hides empty state component.

Usage:

```
EmptyStateManager$hide()
```

Returns: Nothing, it changes state of empty state

Method `clone()`**:** The objects of this class are cloneable with this method.

Usage:

```
EmptyStateManager$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
library(shiny)
library(shiny.emptystate)
library(fontawesome)

ui <- fluidPage(
  use_empty_state(),
  actionButton("show", "Show empty state!"),
  actionButton("hide", "Hide empty state!"),
  tableOutput("my_table")
)
```

```
server <- function(input, output) {
  # Creating a custom empty state component
  empty_state_content <- empty_state_component(
    content = fa("eye-slash", height = "10rem", fill = "#808000"),
    title = "Hide empty state to see table",
    subtitle = "This empty state uses a FontAwesome icon."
  )

  # Initialize a new empty state manager object
  manager_object <- EmptyStateManager$new(
    id = "my_table",
    html_content = empty_state_content
  )

  observeEvent(input$show, {
    # Show empty state
    manager_object$show()
  })

  observeEvent(input$hide, {
    # Hide empty state
    manager_object$hide()
  })

  output$my_table <- renderTable(mtcars)
}

if (interactive()) {
  shinyApp(ui = ui, server = server)
}
```

`empty_state_component` *Create an empty state component*

Description

Function to create a custom empty state component.

Usage

```
empty_state_component(content, title, subtitle = NULL)
```

Arguments

`content`	An HTML tag object used to render and provide the main content for the empty state.
`title`	A character string representing the main text that describes the empty state content.
`subtitle`	A character string providing supporting details about the empty state. Defaults to `NULL`

Details

`content` works best with `fontawesome::fa()` and `bsicons::bs_icon()`. `shiny::icon()` will also work, but this will require loading the html dependencies in the ui, i.e. calling `fontawesome::fa_html_dependency()` to use icons from FontAwesome.Glyphicon does not need any html dependency.

Value

a shiny.tag

Examples

```
library(shiny.emptystate)

if (interactive()) {
  empty_state_component(
    fontawesome::fa(name = "clipboard-question", height = "10rem"),
    title = "Content is not available",
    subtitle = "Please provide valid inputs to generate content."
  )

  empty_state_component(
    bsicons::bs_icon(
      name = "question-square",
      size = "15rem"
    ),
    title = "Content is not available",
    subtitle = "Please provide valid inputs to generate content."
  )
}
```

---

use_empty_state *Add empty state dependency*

Description

Empty state dependencies to include anywhere in your UI but ideally at the top.

Usage

```
use_empty_state()
```

Value

a html_dependency object

Examples

```
library(shiny)
library(shiny.emptystate)

if (interactive()) {
  ui <- fluidPage(
    use_empty_state(),
    dataTableOutput("my_table")
  )
}
```

Index

bsicons::bs_icon(), *5*

default_empty_state_component, 2

empty_state_component, 4
EmptyStateManager, 2

fontawesome::fa(), *5*
fontawesome::fa_html_dependency(), *5*

shiny::icon(), *5*

use_empty_state, 5