

Package ‘shinybrms’

July 23, 2025

Title Graphical User Interface ('shiny' App) for 'brms'

Version 1.8.0

Date 2022-07-30

Description A graphical user interface (GUI) for fitting Bayesian regression models using the package 'brms' which in turn relies on 'Stan' (<<https://mc-stan.org/>>). The 'shinybrms' GUI is a 'shiny' app.

License GPL-3 | file LICENSE

URL <https://fweber144.github.io/shinybrms/>

BugReports <https://github.com/fweber144/shinybrms/issues>

Depends R (>= 3.6.0)

Imports shiny (>= 1.7.0), brms (>= 2.16.0), rstan (>= 2.19.3), rlang

Suggests cmdstanr, ggplot2, shinystan (>= 2.4.0), callr (>= 3.4.0), rstanarm, MASS, lme4, testthat, shinytest

Additional_repositories <https://mc-stan.org/r-packages/>

Encoding UTF-8

RoxygenNote 7.2.1

NeedsCompilation no

Author Frank Weber [aut, cre] (ORCID: <<https://orcid.org/0000-0002-4842-7922>>),
Katja Ickstadt [ctb] (ORCID: <<https://orcid.org/0000-0001-5157-2496>>),
Änne Glass [ctb] (ORCID: <<https://orcid.org/0000-0002-7715-9058>>),
Thomas Park [ctb, cph] ('Bootswatch' theme ``United"),
Twitter, Inc. [ctb, cph] ('Bootstrap' (basis for the 'Bootswatch' theme
``United")),
Google, LLC [ctb, cph] (``Open Sans" font)

Maintainer Frank Weber <fweber144@protonmail.com>

Repository CRAN

Date/Publication 2022-08-05 22:50:07 UTC

Contents

launch_shinybrms	2
Index	4

launch_shinybrms	<i>Launch the shinybrms app</i>
------------------	--

Description

This function launches the **shinybrms** app.

Usage

```
launch_shinybrms(...)
```

Arguments

... Arguments passed to `shiny::runApp()`. For example, in order to force the **shinybrms** app to launch in the system's default web browser (even if using RStudio), set argument `launch.browser` to `TRUE`.

Value

`TRUE` (invisible).

Note

The following global options are introduced by **shinybrms**:

- `shinybrms.allow_upd`: Mainly for internal testing purposes. A single logical value indicating whether updating a previous model fit using `brms::update.brmsfit()` is allowed. Defaults to `TRUE`.
- `shinybrms.prog_browser`: The value for the global option browser to be used for opening the **Stan** progress file (an HTML file). Defaults to option browser (see `base::options()`). Note that RStudio's default for option browser cannot be used for the Stan progress file. Therefore, **shinybrms** automatically redefines RStudio's default for option browser to fix this issue.
- `shinybrms.shinystan_browser`: The value for the global option browser to be used for opening the **shinystan** app. Defaults to option browser (see `base::options()`). Note that RStudio's default for option browser cannot be used for opening the **shinystan** app from within **shinybrms**. Therefore, **shinybrms** automatically redefines RStudio's default for option browser to fix this issue.

External global options used by **shinybrms** are:

- `shiny.maxRequestSize` (see `shiny::shinyOptions()`): If not specified by the user, then **shinybrms** uses a value of $50 * 1024^2$ (corresponding to 50 MB).

- warn (see `base::options()`): Set and reset internally (necessary for catching some warning messages).
- browser (see `base::options()`): Set and reset internally (see above).
- mc.cores (see `base::options()`): If option `mc.cores` is set, then the advanced option "Cores" (in the **shinybrms** app) defaults to the value of this option. If option `mc.cores` is not set, then the advanced option "Cores" defaults to the value returned by `parallel::detectCores()`.
- brms.backend (see `brms::brm()`): If option `brms.backend` is set, then the advanced option "Backend" (in the **shinybrms** app) defaults to the value of this option. If option `brms.backend` is not set, then the advanced option "Backend" defaults to "rstan".

Note that **shinystan**'s global option `shinystan.rstudio` (see `shinystan::launch_shinystan()`) may not be used here as **shinystan** is called from an external R process where RStudio's browsers are not available.

Examples

```
if (interactive()) {  
  launch_shinybrms(launch.browser = TRUE)  
}
```

Index

`base::options()`, [2](#), [3](#)

`brms::brm()`, [3](#)

`launch_shinybrms`, [2](#)

`parallel::detectCores()`, [3](#)

`shiny::runApp()`, [2](#)

`shiny::shinyOptions()`, [2](#)

`shinytan::launch_shinytan()`, [3](#)