

Package ‘shinypivottabler’

July 23, 2025

Title Shiny Module to Create Pivot Tables

Version 1.2

Description Shiny Module to create, visualize, customize and export Excel-like pivot table.

License GPL-3

Encoding UTF-8

Depends R (>= 3.4)

RoxygenNote 7.2.1

Imports pivottabler (>= 1.5.0), shiny, openxlsx, colourpicker,
htmltools

NeedsCompilation no

Author Benoit Thieurmél [aut, cre],
Thibaut Dubois [aut]

Maintainer Benoit Thieurmél <bthieurmél@gmail.com>

Repository CRAN

Date/Publication 2023-01-06 10:30:02 UTC

Contents

shinypivottabler	1
Index	6

shinypivottabler	<i>Shiny module to render and export pivot tables.</i>
------------------	--

Description

Shiny module to render and export pivot tables.

Usage

```
shinypivottabler(
  input,
  output,
  session,
  data,
  pivot_cols = NULL,
  indicator_cols = NULL,
  max_n_pivot_cols = 100,
  additional_expr_num = list(),
  additional_expr_char = list(),
  additional_combine = list(),
  theme = NULL,
  export_styles = TRUE,
  show_title = TRUE,
  initialization = NULL
)

shinypivottablerUI(id, app_colors = c("#59bb28", "#217346"), app_linewidth = 8)
```

Arguments

<code>input</code>	shiny input
<code>output</code>	shiny input
<code>session</code>	shiny input
<code>data</code>	<code>data.frame</code> / <code>data.table</code> . Initial data table.
<code>pivot_cols</code>	character (NULL). Columns to be used as pivot in rows and cols.
<code>indicator_cols</code>	character (NULL). Columns on which indicators will be calculated.
<code>max_n_pivot_cols</code>	numeric (100). Maximum unique values for a <code>pivot_cols</code> if <code>pivot_cols = NULL</code>
<code>additional_expr_num</code>	named list (<code>list()</code>). Additional computations to be allowed for quantitative vars.
<code>additional_expr_char</code>	named list (<code>list()</code>). Additional computations to be allowed for qualitative vars.
<code>additional_combine</code>	named list (<code>list()</code>). Additional combinations to be allowed.
<code>theme</code>	list (NULL). Theme to customize the output of the pivot table. Use HEX color rather than <code>rgb</code> for export style
<code>export_styles</code>	boolean (TRUE). Whether or not to apply styles (like the theme) when exporting to Excel.
<code>show_title</code>	boolean (TRUE). Whether or not to display the app title. Some styles may not be supported by Excel.
<code>initialization</code>	named list (NULL). Initialization parameters to display a table when launching the module. Available fields are :

- rows: Selected pivot rows.
- cols: Selected pivot columns.
- target, combine_target: Selected target and combine_target columns..
- idc, combine_idc: Selected idc and combine_idc columns.
- combine: Selected combine operator.
- format_digit, format_prefix, format_suffix, format_sep_thousands, format_decimal: Selected formats for the table idc.
- idcs: idcs to be displayed (list of named list), see the example to get the fields.

id character. An ID string

app_colors character. Vector of two colors c("#59bb28", "#217346") (borders)

app_linewidth numeric. Borders width

Value

Nothing. Just Start a Shiny module.

Examples

```
if (interactive()) {
  require(shinypivottabler)
  require(shiny)

  # demo app
  runApp(system.file("demo_app", package = "shinypivottabler"))

  # create artificial dataset
  n <- 1000000
  data <- data.frame("gr1" = sample(c("A", "B", "C", "D"), size = n,
                                   prob = rep(1, 4), replace = T),
                    "gr2" = sample(c("E", "F", "G", "H"), size = n,
                                   prob = rep(1, 4), replace = T),
                    "gr3" = sample(c("I", "J", "K", "L"), size = n,
                                   prob = rep(1, 4), replace = T),
                    "gr4" = sample(c("M", "N", "O", "P"), size = n,
                                   prob = rep(1, 4), replace = T),
                    "value1" = 1:n,
                    "value2" = n:1)

  # Minimal example

  ui = shiny::fluidPage(
    shinypivottablerUI(id = "id")
  )

  server = function(input, output, session) {
    shiny::callModule(module = shinypivottabler,
                      id = "id",
                      data = data)
```

```

}

shiny::shinyApp(ui = ui, server = server)

# Complete example

initialization <- list(
  "rows" = "gr1",
  "cols" = "gr2",
  "target" = "gr3",
  "combine_target" = "gr4",
  "idc" = "Count",
  "combine_idc" = "Count",
  "combine" = "/",
  "idcs" = c(
    list(
      c("label" = "Init_variable_1",
        "target" = "gr3", "idc" = "Count",
        "nb_decimals" = 0,
        "sep_thousands" = " ",
        "sep_decimal" = ".",
        "prefix" = "",
        "suffix" = "",
        "combine" = "/",
        "combine_target" = "gr4",
        "combine_idc" = "Count")
    ),
    list(
      c("label" = "Init_variable_2",
        "target" = "gr3", "idc" = "Count")
    )
  )
)

theme <- list(
  fontName="Courier New, Courier",
  fontSize="1em",
  headerBackgroundColor = "red",
  headerColor = "#FFFFFF",
  cellBackgroundColor = "#FFFFFF",
  cellColor = "#000000",
  outlineCellBackgroundColor = "#C0C0C0",
  outlineCellColor = "#000000",
  totalBackgroundColor = "#59bb28",
  totalColor = "#000000",
  borderColor = "#404040"
)

ui = shiny::fluidPage(
  shinypivottablerUI(id = "id")
)

```

```
# we add two functions, one for quantitative variables (Q5) and
# one for qualitative variables (the mode, with a custom function), and
# one possible combination (the modulo).
my_mode <- function(x) names(which.max(table(x)))

server = function(input, output, session) {
  shiny::callModule(module = shinypivottabler,
    id = "id",
    data = data,
    pivot_cols = c("gr1", "gr2", "gr3", "gr4"),
    additional_expr_num = list(
      "Add_Q5" = "paste0('quantile(', target, ', probs = 0.05, na.rm = TRUE)')"
    ),
    additional_expr_char = list(
      "Add_mode" = "paste0('my_mode(', target, ')')"
    ),
    additional_combine = c("Add_modulo" = "%%"),
    theme = theme,
    initialization = initialization)
}

shiny::shinyApp(ui = ui, server = server)
}
```

Index

shinypivottabler, [1](#)
shinypivottablerUI (shinypivottabler), [1](#)