

Package ‘slap’

July 23, 2025

Title Simplified Error Handling

Version 2024.4.1

Description Alternative to using `withCallingHandlers()` in the simple case of catch and rethrow. The ``%!%`` operator evaluates the expression on its left hand side, and if an error occurs, the right hand side is used to construct a new error that embeds the original error.

License MIT + file LICENSE

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.3.1

Imports cli, rlang

URL <https://github.com/tadascience/slap>, <https://slap.tada.science>

BugReports <https://github.com/tadascience/slap/issues>

NeedsCompilation no

Author Romain François [aut, cre],
tada.science [cph, fnd]

Maintainer Romain François <romain@tada.science>

Repository CRAN

Date/Publication 2024-04-24 14:00:02 UTC

Contents

slap	2
Index	4

slap

*Slap Operator***Description**

Slap Operator

Usage

expr %!% message

expr %!!% message

Arguments

expr An expression or quosure to evaluate carefully

message A message meant to be formatted by `cli::cli_bullets()` or a function.**Value**

If expr succeeds, its result is returned.

When expr generates an error, the %!% and %!!% operators catch it and embed it in a new error thrown by `cli::cli_abort()`.

If message evaluates to a character vector, it is used as the message argument of `cli::cli_abort()`.

If message evaluates to a function, the function is called with one argument: the caught error from evaluating expr.

When the current environment has an `error_call` object, it is used as the call argument of `cli::cli_abort()`.

Examples

```
# g() throws an error
g <- function() {
  stop("ouch")
}

# h() catches that error and embed it in a new error
# with "bam" as its message, the g() error as the parent error,
# and the caller environment as call=
h <- function(error_call = rlang::caller_env()) {
  g() %!% "bam"
}

# f() will be used as the error call
f <- function() {
  h()
}
```

```
# Error in `f()`:  
# ! bam  
# Caused by error in `g()`:  
# ! ouch  
tryCatch(f(), error = function(err) {  
  print(err, backtrace = FALSE)  
})
```

Index

`%%!(slap)`, [2](#)

`%%(slap)`, [2](#)

`cli::cli_abort()`, [2](#)

`cli::cli_bullets()`, [2](#)

`slap`, [2](#)