

Package ‘surveyframe’

July 11, 2026

Title Survey Instrument Workflows

Version 0.3.3

Description Supports survey research workflows built around a typed instrument object (the `sframe`). Features include visual instrument design via a browser-based builder or 'Shiny' studio, export to a self-contained static HTML survey, an embeddable 'Shiny' module, SHA-256 integrity-checked serialisation to the `'.sframe'` format, multi-page survey rendering, branching logic, response quality checking, scale scoring, psychometric diagnostics, analysis-plan execution, model syntax planning, an interactive response dashboard, codebook generation, and reproducible HTML reporting.

License MIT + file LICENSE

URL <https://github.com/MohammedAliSharafuddin/surveyframe>

BugReports <https://github.com/MohammedAliSharafuddin/surveyframe/issues>

Encoding UTF-8

Language en-GB

Depends R (>= 4.1.0)

Imports jsonlite (>= 1.8.0), rlang (>= 1.1.0), openssl (>= 2.1.0)

Suggests ggplot2 (>= 3.4.0), googlesheets4 (>= 1.1.0), shiny (>= 1.7.0), psych (>= 2.3.0), MASS, nnet, digest (>= 0.6.0), lavaan (>= 0.6-0), testthat (>= 3.0.0), knitr, rmarkdown

VignetteBuilder knitr

Config/testthat/edition 3

Config/roxygen2/version 8.0.0

RoxygenNote 8.0.0

NeedsCompilation no

Author Mohammed Ali Sharafuddin [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-5247-2964>>)

Maintainer Mohammed Ali Sharafuddin <mohammedali.page@gmail.com>

Repository CRAN

Date/Publication 2026-07-11 18:30:03 UTC

Contents

add_model	3
assumption_report	4
cfa_lavaan_syntax	5
cfa_syntax	6
codebook_report	7
descriptives_report	8
efa_report	9
efa_solution	10
efa_syntax	11
export_google_sheet	11
export_static_survey	12
format.sframe	14
format.sf_branch	14
format.sf_check	15
format.sf_choices	15
format.sf_item	16
format.sf_model	16
format.sf_scale	17
item_report	17
launch_builder	18
launch_builder_demo	19
launch_dashboard	19
launch_dashboard_demo	21
launch_studio	22
launch_studio_demo	23
missing_data_report	24
model_json	24
model_report_template	25
outlier_report	25
posthoc_report	26
print.sframe	27
print.sf_branch	28
print.sf_check	28
print.sf_choices	29
print.sf_item	30
print.sf_model	30
print.sf_scale	31
quality_report	31
read_responses	33
read_sframe	34
read_sheet_responses	35
reliability_report	36
render_report	37
render_results	39
render_survey	40
run_analysis_plan	41

sample_size_plan	42
score_scales	43
seminr_syntax	44
sem_lavaan_syntax	45
sframe_builder_empty_state	45
sframe_builder_state_from_instrument	46
sframe_builder_validate_draft	46
sframe_demo_data	47
sframe_input_types_demo_data	47
sf_branch	48
sf_check	49
sf_choices	50
sf_construct	51
sf_covariance	52
sf_indirect	52
sf_instrument	53
sf_item	55
sf_model	56
sf_path	57
sf_scale	58
summary.sframe	59
summary.sf_branch	60
summary.sf_check	60
summary.sf_choices	61
summary.sf_item	61
summary.sf_model	62
summary.sf_scale	62
survey_module_server	63
survey_module_ui	63
theme_surveyframe	65
validate_model	65
validate_sframe	66
validity_report	67
write_sframe	68
Index	69

add_model	<i>Add a model specification to an instrument</i>
-----------	---

Description

Add a model specification to an instrument

Usage

```
add_model(instrument, model, validate = TRUE, replace = TRUE)
```

Arguments

instrument	An sframe object.
model	An <code>sf_model()</code> object.
validate	Logical. Whether to validate the model against the instrument before adding it.
replace	Logical. Whether to replace an existing model with the same ID. Defaults to TRUE.

Value

The updated sframe object.

assumption_report	<i>Assumption-check report</i>
-------------------	--------------------------------

Description

Performs common assumption checks for survey analyses using base R where possible: Shapiro-Wilk tests, skewness/kurtosis screening, Levene and Brown-Forsythe tests, regression residual checks, VIF, Cook's distance, expected-count checks, and sparse-cell warnings.

Usage

```
assumption_report(
  data,
  variables = NULL,
  group = NULL,
  outcome = NULL,
  predictors = NULL,
  table_vars = NULL
)
```

Arguments

data	A data.frame.
variables	Numeric variables for normality screening.
group	Optional grouping variable for Levene/Brown-Forsythe tests.
outcome	Optional regression outcome.
predictors	Optional regression predictors.
table_vars	Optional two categorical variables for expected-count checks.

Value

An object of class `sframe_assumption_report`.

cfa_lavaan_syntax	<i>Generate lavaan CFA syntax</i>
-------------------	-----------------------------------

Description

Generate lavaan CFA syntax

Usage

```
cfa_lavaan_syntax(  
  instrument = NULL,  
  model = NULL,  
  scales = NULL,  
  ordered = FALSE,  
  std_lv = TRUE,  
  residual_covariances = NULL,  
  latent_covariances = TRUE  
)
```

Arguments

instrument	Optional sframe object used to derive constructs from scales when model is not supplied.
model	Optional sf_model() object.
scales	Optional scale IDs when deriving a model from an instrument.
ordered	Logical. Whether to add an ordered-item note.
std_lv	Logical. Whether to add a std.lv = TRUE note.
residual_covariances	Optional list of sf_covariance() objects for correlated residuals.
latent_covariances	Logical. Whether to include model-level latent covariances supplied in model.

Value

A lavaan syntax string.

cfa_syntax

*Generate lavaan CFA syntax from an instrument object***Description**

Produces a character string of lavaan model syntax derived from the scale structure in the instrument. The syntax can be passed directly to `lavaan::cfa()`. Reverse-coded items are noted in a comment but are not transformed in the syntax; recoding should be applied to the data before fitting the model.

Usage

```
cfa_syntax(instrument, scales = NULL, std_lv = TRUE)
```

Arguments

<code>instrument</code>	An <code>sframe</code> object.
<code>scales</code>	Character vector or <code>NULL</code> . A subset of scale IDs to include. When <code>NULL</code> , all scales are included.
<code>std_lv</code>	Logical. Whether to include the <code>std.lv = TRUE</code> argument note in the output comment header. Defaults to <code>TRUE</code> .

Value

A character string of lavaan CFA model syntax.

See Also

[efa_report\(\)](#), [reliability_report\(\)](#)

Examples

```
cs    <- sf_choices("ag5", 1:5,
                    c("Strongly disagree", "Disagree", "Neutral",
                      "Agree", "Strongly agree"))
i1    <- sf_item("sat_1", "Item 1", type = "likert",
                choice_set = "ag5", scale_id = "sat")
i2    <- sf_item("sat_2", "Item 2", type = "likert",
                choice_set = "ag5", scale_id = "sat")
i3    <- sf_item("sat_3", "Item 3 (reverse)", type = "likert",
                choice_set = "ag5", scale_id = "sat", reverse = TRUE)
scale <- sf_scale("sat", "Satisfaction",
                 items = c("sat_1", "sat_2", "sat_3"))
instr <- sf_instrument("Demo Survey", components = list(cs, i1, i2, i3, scale))

syntax <- cfa_syntax(instr)
cat(syntax)
```

```
## Not run:
# lavaan is not installed by default; install it before fitting.
demo <- sframe_demo_data()
scored <- score_scales(demo$responses, demo$instrument)
fit <- lavaan::cfa(syntax, data = scored, std.lv = TRUE)
summary(fit, fit.measures = TRUE)

## End(Not run)
```

codebook_report

Generate a survey codebook from an instrument object

Description

Produces a structured codebook listing all items, their types, choice sets, scale membership, and reverse-coding status. The codebook can be rendered as HTML or Markdown.

Usage

```
codebook_report(instrument, format = c("html", "md"))
```

Arguments

instrument	An sframe object.
format	Character. Output format. Either "html" or "md".

Value

An object of class `sframe_codebook`, a list with elements `instrument_meta`, `items_table`, `choices_table`, and `scales_table`. Call `print()` to display a compact summary or use `render_report()` to include the codebook in a full report.

See Also

[render_report\(\)](#)

Examples

```
cs <- sf_choices("ag5", 1:5,
  c("Strongly disagree", "Disagree", "Neutral",
    "Agree", "Strongly agree"))
i1 <- sf_item("sat_1", "Item 1", type = "likert",
  choice_set = "ag5", scale_id = "sat")
i2 <- sf_item("sat_2", "Item 2", type = "likert",
  choice_set = "ag5", scale_id = "sat")
scale <- sf_scale("sat", "Satisfaction", items = c("sat_1", "sat_2"))
instr <- sf_instrument("Demo Survey", components = list(cs, i1, i2, scale))

cb <- codebook_report(instr)
```

```
print(cb)
nrow(cb$items_table)
nrow(cb$scales_table)
```

descriptives_report	<i>Descriptive statistics report</i>
---------------------	--------------------------------------

Description

Computes survey descriptives for numeric, Likert, and scale-score columns, including missingness, mean, standard deviation, median, IQR, range, skewness, kurtosis, standard error, and confidence intervals.

Usage

```
descriptives_report(
  data,
  variables = NULL,
  split_by = NULL,
  conf_level = 0.95,
  weights = NULL
)
```

Arguments

data	A data.frame of responses.
variables	Character vector of variables. When NULL, numeric-like columns are used.
split_by	Optional grouping variable.
conf_level	Confidence level for the mean interval.
weights	Optional case-weight column.

Value

An object of class `sframe_descriptives_report`.

efa_report

*Prepare a survey instrument for exploratory factor analysis***Description**

Reports KMO sampling adequacy, Bartlett's test of sphericity, and a parallel analysis scree plot to inform factor number selection. The suggested number of factors from parallel analysis is returned in `$suggested_nfactors`. The report prepares the researcher to estimate an EFA solution with a separate package such as `psych` or `lavaan`.

Usage

```
efa_report(
  data,
  instrument,
  scales = NULL,
  nfactors = NULL,
  rotation = "oblimin"
)
```

Arguments

<code>data</code>	A tibble or <code>data.frame</code> of responses.
<code>instrument</code>	An <code>sframe</code> object.
<code>scales</code>	Character vector or <code>NULL</code> . Scale IDs whose items to include. When <code>NULL</code> , all scale items are pooled.
<code>nfactors</code>	Integer or <code>NULL</code> . Suggested number of factors to highlight on the scree plot. When <code>NULL</code> , the parallel analysis recommendation is used.
<code>rotation</code>	Character. The rotation method to display in the diagnostic notes. Does not affect the diagnostics themselves. Defaults to "oblimin".

Value

An object of class `sframe_efa_report` with elements `kmo`, `bartlett`, `parallel`, and `suggested_nfactors`.

See Also

[reliability_report\(\)](#), [cfa_syntax\(\)](#)

Examples

```
if (requireNamespace("psych", quietly = TRUE)) {
  demo <- sframe_demo_data()
  er <- efa_report(demo$responses, demo$instrument)
  print(er)
}
```

`efa_solution`*Estimate an exploratory factor solution*

Description

Runs `psych::fa()` on selected item columns and returns loadings, communalities, uniqueness, variance summaries, and simple item retention flags. The `psych` package is optional and is only required when this function is called.

Usage

```
efa_solution(  
  data,  
  instrument,  
  items = NULL,  
  scales = NULL,  
  nfactors = 1L,  
  extraction = c("minres", "pa", "ml"),  
  rotation = c("oblimin", "promax", "varimax"),  
  min_loading = 0.3,  
  cross_loading = 0.3  
)
```

Arguments

<code>data</code>	A <code>data.frame</code> of responses.
<code>instrument</code>	An <code>sframe</code> object.
<code>items</code>	Character vector of item IDs. When <code>NULL</code> , scale items are used.
<code>scales</code>	Optional scale IDs used to select item columns.
<code>nfactors</code>	Number of factors.
<code>extraction</code>	Extraction method passed to <code>psych::fa()</code> .
<code>rotation</code>	Rotation method passed to <code>psych::fa()</code> .
<code>min_loading</code>	Minimum salient loading.
<code>cross_loading</code>	Maximum secondary loading before a warning is raised.

Value

An object of class `sframe_efa_solution`.

efa_syntax	<i>Generate EFA planning syntax</i>
------------	-------------------------------------

Description

Generate EFA planning syntax

Usage

```
efa_syntax(  
  items,  
  nfactors = 1L,  
  extraction = c("minres", "pa", "ml"),  
  rotation = c("oblimin", "promax", "varimax"),  
  data_name = "data"  
)
```

Arguments

items	Character vector of item IDs.
nfactors	Number of factors.
extraction	Extraction method.
rotation	Rotation method.
data_name	Name of the data object in generated R code.

Value

A character string with R syntax.

export_google_sheet	<i>Export a survey instrument to Google Sheets collection format</i>
---------------------	--

Description

Generates a Google Apps Script file that, when run in a Google Sheet, creates a response collection endpoint for a survey instrument. The builder can store the deployed Apps Script URL in survey metadata, and the same sheet can be read back with [read_sheet_responses\(\)](#).

Usage

```
export_google_sheet(instrument, sheet_url, output_dir = ".")
```

Arguments

instrument	An sframe object.
sheet_url	Character. The URL of an existing Google Sheet. The sheet must be shared so that anyone with the link can edit, or use service account credentials via googlesheets4.
output_dir	Character. Directory to write the Apps Script file. Defaults to the current working directory.

Value

The path to the generated .gs Apps Script file, invisibly.

See Also

[read_sheet_responses\(\)](#), [read_responses\(\)](#), [write_sframe\(\)](#)

Examples

```
instr <- read_sframe(
  system.file("extdata", "tourism_services_demo.sframe",
    package = "surveyframe")
)
script <- export_google_sheet(
  instr,
  sheet_url = "https://docs.google.com/spreadsheets/d/demo",
  output_dir = tempdir()
)
file.exists(script)
```

export_static_survey *Export a self-contained static HTML survey*

Description

Generates a single HTML file that presents the survey instrument in a browser without requiring a Shiny server or any internet connection. All thirteen item types, branching logic, required-field validation, and multi-page navigation are handled entirely in client-side JavaScript.

Usage

```
export_static_survey(
  instrument,
  output_path = NULL,
  open = interactive(),
  endpoint_url = NULL,
  overwrite = FALSE
)
```



```
# Write to a temp file and open in the default browser
export_static_survey(instr,
                     output_path = file.path(tempdir(), "sat_browser.html"),
                     overwrite = TRUE)

# Write with a Google Apps Script endpoint for server-side collection
export_static_survey(
  instr,
  output_path = file.path(tempdir(), "sat_endpoint.html"),
  endpoint_url = "https://script.google.com/macros/s/XXXXX/exec",
  open        = FALSE,
  overwrite   = TRUE
)
```

format.sframe

Format an sframe instrument object as a string

Description

Format an sframe instrument object as a string

Usage

```
## S3 method for class 'sframe'
format(x, ...)
```

Arguments

x	An object of class sframe.
...	Ignored. Present for S3 consistency.

Value

A single character string.

format.sf_branch

Format an sf_branch object as a string

Description

Format an sf_branch object as a string

Usage

```
## S3 method for class 'sf_branch'
format(x, ...)
```

Arguments

x	An object of class sf_branch.
...	Ignored. Present for S3 consistency.

Value

A single character string.

format.sf_check	<i>Format an sf_check object as a string</i>
-----------------	--

Description

Format an sf_check object as a string

Usage

```
## S3 method for class 'sf_check'
format(x, ...)
```

Arguments

x	An object of class sf_check.
...	Ignored. Present for S3 consistency.

Value

A single character string.

format.sf_choices	<i>Format an sf_choices object as a string</i>
-------------------	--

Description

Format an sf_choices object as a string

Usage

```
## S3 method for class 'sf_choices'
format(x, ...)
```

Arguments

x	An object of class sf_choices.
...	Ignored. Present for S3 consistency.

Value

A single character string.

<code>format.sf_item</code>	<i>Format an sf_item object as a string</i>
-----------------------------	---

Description

Format an sf_item object as a string

Usage

```
## S3 method for class 'sf_item'
format(x, ...)
```

Arguments

- `x` An object of class sf_item.
- `...` Ignored. Present for S3 consistency.

Value

A single character string.

<code>format.sf_model</code>	<i>Format an sf_model object as a string</i>
------------------------------	--

Description

Format an sf_model object as a string

Usage

```
## S3 method for class 'sf_model'
format(x, ...)
```

Arguments

- `x` An object of class sf_model.
- `...` Ignored. Present for S3 consistency.

Value

A single character string.

format.sf_scale	<i>Format an sf_scale object as a string</i>
-----------------	--

Description

Format an sf_scale object as a string

Usage

```
## S3 method for class 'sf_scale'  
format(x, ...)
```

Arguments

x	An object of class sf_scale.
...	Ignored. Present for S3 consistency.

Value

A single character string.

item_report	<i>Generate item-level diagnostics</i>
-------------	--

Description

Produces item-total correlations, floor and ceiling effect proportions, and item means and standard deviations for each item within each scale.

Usage

```
item_report(data, instrument, scales = NULL)
```

Arguments

data	A tibble or data.frame of responses.
instrument	An sframe object.
scales	Character vector or NULL. A subset of scale IDs to analyse. When NULL (default), all scales are included.

Value

An object of class sframe_item_report, a list with one data.frame per scale.

See Also

[reliability_report\(\)](#), [sf_scale\(\)](#)

Examples

```
demo <- sframe_demo_data()
ir <- item_report(demo$responses, demo$instrument)
print(ir)
```

launch_builder

Launch the surveyframe visual survey builder

Description

Opens the SurveyBuilder, a self-contained HTML application for visual survey design. The builder runs client-side without an R session or Shiny server. Save instruments as .sframe files from the browser and load them into R with [read_sframe\(\)](#).

Usage

```
launch_builder(open = TRUE)
```

Arguments

open	Logical. When TRUE (the default), the builder HTML file is opened in the system's default web browser with utils::browseURL() . Set to FALSE to return the file path without opening it, which is useful for automated testing.
------	---

Details

The builder includes a three-mode interface.

Build An item editor with a persistent inspector panel, drag-to-reorder, undo/redo, and autosave to browser localStorage.

Preview A full live render of the survey showing welcome, body, and thank-you pages.

Analyse A role-based analysis planner with method-specific options, planned outputs, reporting references, and decision rules.

The builder includes a pure-JavaScript SHA-256 fallback for browsers or security policies where crypto.subtle is unavailable on file:// origins. Saved .sframe files can be loaded and validated with [read_sframe\(\)](#).

Value

The path to the bundled builder HTML file, invisibly.

See Also

[launch_studio\(\)](#), [read_sframe\(\)](#), [run_analysis_plan\(\)](#)

Examples

```
# Retrieve the builder path for inspection without opening the browser
path <- launch_builder(open = FALSE)
file.exists(path)
```

launch_builder_demo	<i>Launch SurveyBuilder with the bundled input-types demo preloaded</i>
---------------------	---

Description

Opens a temporary copy of the SurveyBuilder with the bundled input-types instrument already injected into the JavaScript state. The demo questions, scales, and analysis plan are visible immediately — no manual file-load step is required.

Usage

```
launch_builder_demo(open = TRUE)
```

Arguments

open	Logical. When TRUE (the default), the pre-populated builder HTML is opened in the system's default web browser.
------	---

Value

Invisibly returns a list with `builder_path`, `demo_file`, and `responses_path`.

launch_dashboard	<i>Launch the interactive response dashboard</i>
------------------	--

Description

Opens a Shiny dashboard to explore collected response data alongside the instrument definition. Use this interface after response collection for analysis and quality control. Use [launch_builder\(\)](#) to design new questionnaires. The dashboard includes five panels:

Usage

```
launch_dashboard(
  instrument = NULL,
  responses = NULL,
  port = NULL,
  host = "127.0.0.1",
  launch.browser = interactive()
)
```

Arguments

instrument	An sframe object. Required. Calling <code>launch_dashboard()</code> with no instrument errors with guidance; use launch_dashboard_demo() for the bundled demo or launch_studio() to upload interactively.
responses	A data.frame or tibble of survey responses, as produced by read_responses() or read_sheet_responses() . When NULL the dashboard opens with instrument metadata and no response summaries.
port	Integer or NULL. TCP port for the Shiny server. When NULL, Shiny selects an available port automatically.
host	Character. Host address passed to shiny::runApp() . Defaults to "127.0.0.1".
launch.browser	Logical. Whether to open the dashboard in the default browser automatically. Defaults to TRUE in interactive sessions.

Details

Overview Response count, date range, and instrument metadata.

Items Per-item frequency bar charts, histograms, and tabulated frequency counts for choice-type questions.

Scales Scale score distributions with mean overlay, and a summary table of scale definitions.

Quality Attention check pass rates for each check defined in the instrument.

Raw data Scrollable response table with a CSV download button.

The dashboard is read-only and takes its data from R. It has no upload screen, so pass instrument and responses directly. To open and upload data interactively, use [launch_studio\(\)](#), which includes this same dashboard as its Dashboard tab. For a quick look at bundled demo data, use [launch_dashboard_demo\(\)](#).

Value

Called for its side effect. Returns nothing.

See Also

[run_analysis_plan\(\)](#), [quality_report\(\)](#), [score_scales\(\)](#)

Examples

```
## Not run:
# For the bundled demo, use launch_dashboard_demo().
# To upload data interactively, use launch_studio().

# Open the dashboard with your own instrument and responses
instr <- read_sframe(
  system.file("extdata", "tourism_services_demo.sframe",
    package = "surveyframe")
)
responses <- read_responses(
  system.file("extdata", "tourism_services_responses.csv",
    package = "surveyframe"),
  instr,
  respondent_id = "respondent_id",
  submitted_at = "submitted_at",
  meta_cols = "started_at"
)
launch_dashboard(instr, responses)

## End(Not run)
```

launch_dashboard_demo *Launch the response dashboard with the bundled input-types demo*

Description

Opens the dashboard with the bundled input-types questionnaire and 120 simulated responses already loaded. The browser is opened automatically by default.

Usage

```
launch_dashboard_demo(port = NULL, host = "127.0.0.1", launch.browser = TRUE)
```

Arguments

port	TCP port for the Shiny server.
host	Host address for the Shiny server.
launch.browser	Whether to open the browser automatically. Defaults to TRUE for this demo helper.

Value

Called for its side effect.

launch_studio	<i>Launch the SurveyStudio interface</i>
---------------	--

Description

Opens the SurveyStudio Shiny application, a visual interface for the complete surveyframe workflow. The studio includes screens to build a survey draft, open an existing instrument, preview the survey, upload responses, review data quality, inspect reliability, plan analyses, and export outputs.

Usage

```
launch_studio(
  instrument = NULL,
  responses = NULL,
  respondent_id = NULL,
  submitted_at = NULL,
  meta_cols = NULL,
  strict = TRUE,
  screen = c("auto", "build", "preview", "data", "quality", "analysis", "dashboard"),
  port = NULL,
  host = "127.0.0.1",
  launch.browser = interactive()
)
```

Arguments

instrument	An sframe object or NULL.
responses	A data.frame, tibble, CSV file path, or NULL.
respondent_id	Character or NULL. Response ID column when responses is a CSV path.
submitted_at	Character or NULL. Submission time column when responses is a CSV path.
meta_cols	Character vector or NULL. Metadata columns when responses is a CSV path.
strict	Logical. Passed to read_responses() when responses is a CSV path.
screen	Initial studio screen. One of "auto", "build", "preview", "data", "quality", "analysis", or "dashboard".
port	TCP port for the Shiny server.
host	Host address passed to shiny::runApp() .
launch.browser	Whether to open the browser automatically.

Value

Called for its side effect.

See Also

[launch_builder\(\)](#), [launch_dashboard\(\)](#), [read_sframe\(\)](#), [read_responses\(\)](#)

Examples

```
## Not run:
launch_studio()

demo <- sframe_demo_data()
launch_studio(instrument = demo$instrument, launch.browser = FALSE)

launch_studio(
  instrument    = demo$instrument,
  responses     = demo$responses,
  respondent_id = "respondent_id",
  submitted_at  = "submitted_at"
)

## End(Not run)
```

launch_studio_demo	<i>Launch SurveyStudio with the bundled input-types demo</i>
--------------------	--

Description

Opens SurveyStudio with the bundled input-types questionnaire and simulated response data already loaded. The browser is opened automatically by default.

Usage

```
launch_studio_demo(
  screen = "preview",
  port = NULL,
  host = "127.0.0.1",
  launch.browser = TRUE
)
```

Arguments

screen	Initial studio screen. Defaults to "preview" so the demo content is immediately visible.
port	TCP port for the Shiny server.
host	Host address for the Shiny server.
launch.browser	Whether to open the browser automatically. Defaults to TRUE for this demo helper.

Value

Called for its side effect.

missing_data_report	<i>Missing-data report</i>
---------------------	----------------------------

Description

Reports item-wise missingness, respondent-wise missingness, missing-data patterns, listwise and pairwise deletion counts, and scale scoring missing rules. No imputation is performed.

Usage

```
missing_data_report(data, instrument = NULL, variables = NULL)
```

Arguments

data	A data.frame of responses.
instrument	Optional sframe object.
variables	Optional response columns. Defaults to instrument item IDs when an instrument is supplied, otherwise all columns.

Value

An object of class `sframe_missing_data_report`.

model_json	<i>Serialise a model specification to JSON</i>
------------	--

Description

Serialise a model specification to JSON

Usage

```
model_json(model, pretty = TRUE)
```

Arguments

model	An <code>sf_model()</code> object.
pretty	Logical. Whether to pretty-print the JSON.

Value

A JSON string.

model_report_template *Create a model reporting template*

Description

Create a model reporting template

Usage

```
model_report_template(model, include_json = TRUE)
```

Arguments

model An `sf_model()` object.

include_json Logical. Whether to include the JSON schema block.

Value

A character string.

outlier_report *Flag univariate and multivariate outliers*

Description

Uses transparent screening rules for numeric survey response variables. The report supports data review before modelling, not automatic deletion.

Usage

```
outlier_report(  
  data,  
  variables = NULL,  
  method = c("zscore", "iqr", "mahalanobis"),  
  z_cut = 3,  
  iqr_multiplier = 1.5,  
  p_cut = 0.975  
)
```

Arguments

data	A data.frame.
variables	Character vector of numeric variables to screen. When NULL, all numeric columns are used.
method	Outlier rule. "zscore" flags absolute z scores above z_cut; "iqr" flags values outside Tukey fences; "mahalanobis" flags rows above the chi-square cutoff for the selected variables.
z_cut	Numeric cutoff for "zscore". Defaults to 3.
iqr_multiplier	Numeric multiplier for "iqr" fences. Defaults to 1.5.
p_cut	Probability cutoff for "mahalanobis". Defaults to 0.975.

Value

An object of class `sframe_outlier_report` with the method, screened variables, a result table, flagged row numbers, and a reporting prompt.

Examples

```
demo <- sframe_demo_data()
outliers <- outlier_report(
  demo$responses,
  variables = c("dm_1", "dm_2", "sat_1"),
  method = "zscore"
)
outliers$flagged_rows
```

posthoc_report	<i>Post-hoc and pairwise comparison report</i>
----------------	--

Description

Post-hoc and pairwise comparison report

Usage

```
posthoc_report(
  data,
  method = c("anova", "kruskal_wallis", "chi_square", "cochran_q"),
  outcome = NULL,
  group = NULL,
  table_vars = NULL,
  measures = NULL,
  correction = c("holm", "bonferroni", "BH")
)
```

Arguments

data	A data.frame.
method	Comparison family. Supports "anova", "kruskal_wallis", "chi_square", and "cochran_q".
outcome	Outcome variable for group comparisons.
group	Grouping variable for group comparisons.
table_vars	Two categorical variables for chi-square residuals and pairwise proportion tests.
measures	Repeated binary measures for pairwise McNemar tests.
correction	Multiple-comparison correction.

Value

An object of class sframe_posthoc_report.

print.sframe	<i>Print an sframe instrument object</i>
--------------	--

Description

Displays a compact summary of an sframe instrument object, showing the title, version, item count, scale count, and validation status.

Usage

```
## S3 method for class 'sframe'
print(x, ...)
```

Arguments

x	An object of class sframe.
...	Ignored. Present for S3 consistency.

Value

x, invisibly.

Examples

```
item <- sf_item("q1", "How satisfied are you?", type = "likert",
               choice_set = "agree5")
instr <- sf_instrument("My Survey", components = list(item))
print(instr)
```

print.sf_branch	<i>Print an sf_branch object</i>
-----------------	----------------------------------

Description

Print an sf_branch object

Usage

```
## S3 method for class 'sf_branch'
print(x, ...)
```

Arguments

x	An object of class sf_branch.
...	Ignored. Present for S3 consistency.

Value

x, invisibly.

Examples

```
br <- sf_branch("q2", depends_on = "q1", operator = "==",
               value = "yes", action = "show")
print(br)
```

print.sf_check	<i>Print an sf_check object</i>
----------------	---------------------------------

Description

Print an sf_check object

Usage

```
## S3 method for class 'sf_check'
print(x, ...)
```

Arguments

x	An object of class sf_check.
...	Ignored. Present for S3 consistency.

print.sf_item	<i>Print an sf_item object</i>
---------------	--------------------------------

Description

Print an sf_item object

Usage

```
## S3 method for class 'sf_item'  
print(x, ...)
```

Arguments

x	An object of class sf_item.
...	Ignored. Present for S3 consistency.

Value

x, invisibly.

Examples

```
it <- sf_item("q1", "How satisfied are you?", type = "likert",  
             choice_set = "agree5")  
print(it)
```

print.sf_model	<i>Print an sf_model object</i>
----------------	---------------------------------

Description

Print an sf_model object

Usage

```
## S3 method for class 'sf_model'  
print(x, ...)
```

Arguments

x	An object of class sf_model.
...	Ignored. Present for S3 consistency.

Value

x, invisibly.

print.sf_scale	<i>Print an sf_scale object</i>
----------------	---------------------------------

Description

Print an sf_scale object

Usage

```
## S3 method for class 'sf_scale'
print(x, ...)
```

Arguments

x	An object of class sf_scale.
...	Ignored. Present for S3 consistency.

Value

x, invisibly.

Examples

```
sc <- sf_scale("sat", "Satisfaction", items = c("q1", "q2", "q3"))
print(sc)
```

quality_report	<i>Generate a data quality report for survey responses</i>
----------------	--

Description

Evaluates collected response data against the instrument specification and produces a structured quality report. The report covers attention check performance, completion time, straight-lining within scale blocks, item-level missingness, respondent-level missingness, and duplicate respondent IDs where supplied.

Usage

```
quality_report(
  data,
  instrument,
  respondent_id = NULL,
  submitted_at = NULL,
  started_at = NULL,
  time_min = NULL,
  straightline_scales = TRUE,
  missing_threshold = 0.2
)
```

Arguments

<code>data</code>	A tibble or <code>data.frame</code> of responses, typically produced by <code>read_responses()</code> .
<code>instrument</code>	An <code>sframe</code> object created by <code>sf_instrument()</code> .
<code>respondent_id</code>	Character or <code>NULL</code> . The column name holding unique respondent identifiers. Used for duplicate detection.
<code>submitted_at</code>	Character or <code>NULL</code> . The column name holding submission timestamps. Used for completion time analysis.
<code>started_at</code>	Character or <code>NULL</code> . The column name holding survey start timestamps. When <code>NULL</code> , <code>quality_report()</code> looks for a recognised start-time column automatically.
<code>time_min</code>	Numeric or <code>NULL</code> . Minimum acceptable completion time in seconds. Respondents with a submission time below this threshold are flagged as speeders when timing data are available.
<code>straightline_scales</code>	Logical. Whether to check for straight-lining within each defined scale block. Defaults to <code>TRUE</code> .
<code>missing_threshold</code>	Numeric. The proportion of missing item responses above which a respondent is flagged. Defaults to <code>0.2</code> .

Details

Timing analysis is available when the data contain a submission timestamp column and either an explicit `started_at` column or one of the recognised defaults: `started_at`, `start_time`, `started`, or `.started_at`.

Value

An object of class `sframe_quality_report`, a named list with elements: `summary`, `attention`, `timing`, `straightline`, `missing`, and `duplicates`. Use `print()` for a formatted summary.

See Also

`sf_check()`, `read_responses()`, `score_scales()`

Examples

```
instr <- read_sframe(
  system.file("extdata", "tourism_services_demo.sframe",
    package = "surveyframe")
)
responses <- read_responses(
  system.file("extdata", "tourism_services_responses.csv",
    package = "surveyframe"),
  instr,
  respondent_id = "respondent_id",
  submitted_at = "submitted_at",
  meta_cols = "started_at"
```

```

)
qr <- quality_report(
  responses,
  instr,
  respondent_id = "respondent_id",
  submitted_at = "submitted_at",
  started_at = "started_at",
  straightline_scales = FALSE
)
print(qr)

```

read_responses

Read and validate survey responses

Description

Loads survey response data and checks that it conforms to the instrument specification. Column names in the response file must match item IDs defined in the instrument. Non-item columns are allowed only when declared through `respondent_id`, `submitted_at`, or `meta_cols`.

Usage

```

read_responses(
  x,
  instrument,
  respondent_id = NULL,
  submitted_at = NULL,
  meta_cols = NULL,
  strict = TRUE
)

```

Arguments

<code>x</code>	A file path to a CSV file, a <code>data.frame</code> , or a tibble.
<code>instrument</code>	An <code>sframe</code> object created by <code>sf_instrument()</code> .
<code>respondent_id</code>	Character or <code>NULL</code> . The name of the column containing unique respondent identifiers. If <code>NULL</code> , no respondent ID column is expected.
<code>submitted_at</code>	Character or <code>NULL</code> . The name of the column containing submission timestamps.
<code>meta_cols</code>	Character vector or <code>NULL</code> . Additional column names that are not item IDs but should be retained (for example, condition assignment or source URL).
<code>strict</code>	Logical. When <code>TRUE</code> (default), columns in the response data outside the declared item IDs and metadata columns raise an error. When <code>FALSE</code> , undeclared columns are retained with a warning.

Value

A `data.frame` with columns ordered as: metadata columns first, then item columns in instrument order. Unrecognised columns are dropped when `strict = TRUE` or appended with a warning when `strict = FALSE`.

See Also

[quality_report\(\)](#), [score_scales\(\)](#)

Examples

```
responses <- read_responses(
  x = system.file("extdata", "tourism_services_responses.csv",
    package = "surveyframe"),
  instrument = read_sframe(
    system.file("extdata", "tourism_services_demo.sframe",
      package = "surveyframe")
  ),
  respondent_id = "respondent_id",
  submitted_at = "submitted_at",
  meta_cols = "started_at"
)
head(responses[, c("respondent_id", "visit_type", "dm_1")])
```

read_sframe

Read an instrument from a .sframe file

Description

Reads a `.sframe` JSON file and reconstructs an `sframe` instrument object. The SHA-256 integrity hash is verified on load unless `validate = FALSE`.

Usage

```
read_sframe(path, validate = TRUE)
```

Arguments

<code>path</code>	Character. The path to a <code>.sframe</code> file.
<code>validate</code>	Logical. Whether to validate the loaded instrument with validate_sframe() . Defaults to <code>TRUE</code> .

Value

An `sframe` object.

See Also

[write_sframe\(\)](#), [validate_sframe\(\)](#)

Examples

```
instr <- read_sframe(
  system.file("extdata", "tourism_services_demo.sframe",
    package = "surveyframe")
)
print(instr)
```

read_sheet_responses *Read survey responses from a Google Sheet*

Description

Reads response data collected by the surveyframe Google Apps Script endpoint and returns a validated data frame ready for the surveyframe analysis pipeline.

Usage

```
read_sheet_responses(
  sheet_id,
  instrument,
  sheet_name = "Responses",
  respondent_id = "respondent_id",
  submitted_at = "submitted_at",
  meta_cols = NULL
)
```

Arguments

sheet_id	Character. The Google Sheet ID or full URL.
instrument	An sframe object.
sheet_name	Character. The name of the sheet tab holding responses. Defaults to "Responses".
respondent_id	Character or NULL. Column holding respondent IDs. Defaults to "respondent_id".
submitted_at	Character or NULL. Column holding submission timestamps. Defaults to "submitted_at".
meta_cols	Character vector or NULL. Additional sheet columns to accept as metadata without a warning, for example bridge fields a host application appends to each submission. "started_at" is always included.

Value

A data.frame validated against the instrument, ready for [quality_report\(\)](#), [score_scales\(\)](#), and [reliability_report\(\)](#).

See Also

[export_google_sheet\(\)](#), [read_responses\(\)](#), [quality_report\(\)](#)

Examples

```
## Not run:
responses <- read_sheet_responses(
  sheet_id = "your-sheet-id",
  instrument = instr
)
qr <- quality_report(responses, instr, respondent_id = "respondent_id")

## End(Not run)
```

reliability_report	<i>Compute reliability statistics for scored scales</i>
--------------------	---

Description

Produces Cronbach's alpha and McDonald's omega for each scale defined in the instrument, along with the number of items and sample size.

Usage

```
reliability_report(data, instrument, scales = NULL, alpha = TRUE, omega = TRUE)
```

Arguments

data	A tibble or data.frame of responses. Item columns must be present.
instrument	An sframe object.
scales	Character vector or NULL. A subset of scale IDs to analyse. When NULL (default), all scales in the instrument are included.
alpha	Logical. Whether to compute Cronbach's alpha. Defaults to TRUE.
omega	Logical. Whether to compute McDonald's omega. Defaults to TRUE.

Value

An object of class `sframe_reliability_report`, a list with one element per scale. Each element is a list of statistics and a summary tibble.

See Also

[sf_scale\(\)](#), [item_report\(\)](#)

Examples

```
if (requireNamespace("psych", quietly = TRUE)) {
  demo <- sframe_demo_data()
  rr <- reliability_report(demo$responses, demo$instrument, omega = FALSE)
  print(rr)
}
```

render_report	<i>Render a reproducible survey report</i>
---------------	--

Description

Generates an HTML report that includes the instrument codebook, data quality summary, reliability diagnostics, and analysis-plan content. When Quarto and the bundled template are available, the report is rendered through Quarto. Otherwise, surveyframe writes an internal HTML fallback so the reporting workflow still runs on machines without Quarto.

Usage

```
render_report(
  instrument,
  data = NULL,
  output_file = NULL,
  output_path = NULL,
  format = c("html"),
  include_quality = TRUE,
  include_reliability = TRUE,
  include_codebook = TRUE,
  include_missing = TRUE,
  include_descriptives = TRUE,
  include_analysis = TRUE,
  include_models = TRUE
)
```

Arguments

instrument	An sframe object.
data	A tibble or data.frame of responses, or NULL to generate a codebook-only report.
output_file	Character or NULL. The output file path. When NULL, a temporary file is written and its path returned.
output_path	Character or NULL. Alias for output_file. If both are supplied, output_file takes precedence.
format	Character. Output format. Currently "html".
include_quality	Logical. Whether to include the data quality report. Requires data. Defaults to TRUE.
include_reliability	Logical. Whether to include reliability diagnostics. Requires data. Defaults to TRUE.
include_codebook	Logical. Whether to include the instrument codebook. Defaults to TRUE.

`include_missing` Logical. Whether to include the missing-data report. Requires data. Defaults to TRUE.

`include_descriptives` Logical. Whether to include descriptive statistics. Requires data. Defaults to TRUE.

`include_analysis` Logical. Whether to include analysis-plan results when data are supplied and the instrument has an `analysis_plan`.

`include_models` Logical. Whether to include saved model JSON and generated syntax blocks. Defaults to TRUE.

Value

The output file path, invisibly.

See Also

[codebook_report\(\)](#), [quality_report\(\)](#), [reliability_report\(\)](#)

Examples

```
instr <- read_sframe(
  system.file("extdata", "tourism_services_demo.sframe",
    package = "surveyframe")
)
responses <- read_responses(
  system.file("extdata", "tourism_services_responses.csv",
    package = "surveyframe"),
  instr,
  respondent_id = "respondent_id",
  submitted_at = "submitted_at",
  meta_cols = "started_at"
)
old <- options(surveyframe.use_quarto = FALSE)
out <- tryCatch(
  render_report(
    instr,
    data = responses,
    output_file = tempfile(fileext = ".html"),
    include_reliability = FALSE,
    include_analysis = FALSE
  ),
  finally = options(old)
)
file.exists(out)
```

render_results	<i>Render analysis results to a formatted HTML report</i>
----------------	---

Description

Generates a self-contained HTML report from the output of [run_analysis_plan\(\)](#). Each section corresponds to one research question and includes the APA-formatted statistical result, an interpretation space, and a reference list.

Usage

```
render_results(
  results = NULL,
  instrument,
  output_file = NULL,
  output_path = NULL,
  citation_format = c("apa", "ama", "vancouver"),
  title = NULL
)
```

Arguments

results	An <code>sframe_analysis_results</code> object from run_analysis_plan() .
instrument	An <code>sframe</code> object.
output_file	Character or <code>NULL</code> . Path to the output HTML file. When <code>NULL</code> , a temporary file is written and its path returned.
output_path	Character or <code>NULL</code> . Alias for <code>output_file</code> .
citation_format	Character. Reference format. One of "apa", "ama", or "vancouver". Defaults to "apa".
title	Character or <code>NULL</code> . Report title. Defaults to the instrument title with " – Results" appended.

Value

The output file path, invisibly.

See Also

[run_analysis_plan\(\)](#), [render_report\(\)](#)

Examples

```
instr <- read_sframe(
  system.file("extdata", "tourism_services_demo.sframe",
    package = "surveyframe")
)
responses <- read_responses(
  system.file("extdata", "tourism_services_responses.csv",
    package = "surveyframe"),
  instr,
  respondent_id = "respondent_id",
  submitted_at = "submitted_at",
  meta_cols = "started_at"
)
results <- run_analysis_plan(responses, instr)
out <- render_results(results, instr,
  output_file = tempfile(fileext = ".html"))
file.exists(out)
```

render_survey	<i>Render a survey from an instrument object</i>
---------------	--

Description

Launches a Shiny survey with a welcome page, configurable header, all item types, branching logic, required-field enforcement, progress tracking, standard and conversational (one-question-at-a-time) display modes, and a customisable thank-you page. Responses can be persisted to CSV or passed to a callback.

Usage

```
render_survey(
  instrument,
  mode = c("shiny"),
  title = NULL,
  theme = NULL,
  save_responses = c("none", "csv"),
  output_path = NULL,
  on_submit = NULL
)
```

Arguments

instrument	An sframe object.
mode	Character. Deployment mode. Currently "shiny".
title	Character or NULL. Override for the survey title.
theme	Character or NULL. Hex colour for the survey theme.
save_responses	Character. "none" (default) or "csv".

output_path	Character or NULL. CSV path when save_responses = "csv".
on_submit	Function or NULL. Callback receiving the submitted row.

Value

A shiny.appobj.

See Also

[launch_studio\(\)](#), [read_responses\(\)](#)

Examples

```
cs    <- sf_choices("ag5", 1:5,
                    c("Strongly disagree", "Disagree", "Neutral",
                      "Agree", "Strongly agree"))
item  <- sf_item("sat_1", "How satisfied are you?",
                 type = "likert", choice_set = "ag5")
instr <- sf_instrument("My Survey", components = list(cs, item))
app   <- render_survey(instr)
app   <- render_survey(instr, save_responses = "csv", output_path = tempfile(fileext = ".csv"))
```

run_analysis_plan	<i>Run a pre-planned analysis from an instrument's analysis plan</i>
-------------------	--

Description

Executes every analysis block defined in the instrument's analysis_plan slot against the supplied response data. Each block corresponds to one research question defined during instrument design in the SurveyBuilder. Results include APA-formatted statistics, effect sizes, interpretation prompts, and reporting references.

Usage

```
run_analysis_plan(data, instrument, scored = TRUE, plots = FALSE)
```

Arguments

data	A tibble or data.frame of responses, typically produced by read_responses() or read_sheet_responses() .
instrument	An sframe object containing an analysis_plan.
scored	Logical. Whether to automatically score scales before running the analysis. Defaults to TRUE.
plots	Logical. When TRUE and ggplot2 is installed, supported blocks gain a \$plot element holding a brand-styled ggplot object: bar charts for frequency and chi-square blocks, scatter plots with a regression overlay for correlation and linear-regression blocks. Defaults to FALSE.

Value

An object of class `sframe_analysis_results`, a list with one element per analysis block. Each element contains the test result, APA string, interpretation prompt, and reporting-reference meta-data. Inferential blocks also carry a `$table` data frame suitable for `knitr::kable()`. Pass to `render_results()` to generate a formatted report.

See Also

`render_results()`, `read_sheet_responses()`

Examples

```
instr <- read_sframe(
  system.file("extdata", "tourism_services_demo.sframe",
    package = "surveyframe")
)
responses <- read_responses(
  system.file("extdata", "tourism_services_responses.csv",
    package = "surveyframe"),
  instr,
  respondent_id = "respondent_id",
  submitted_at = "submitted_at",
  meta_cols = "started_at"
)
results <- run_analysis_plan(responses, instr)
print(results)
```

sample_size_plan

Sample-size and power planning helper

Description

Sample-size and power planning helper

Usage

```
sample_size_plan(
  type = c("proportion", "mean", "correlation", "t_test", "anova", "regression", "sem"),
  margin_error = NULL,
  sd = NULL,
  p = 0.5,
  r = NULL,
  alpha = 0.05,
  power = 0.8,
  groups = 2L,
  predictors = NULL
)
```

Arguments

type	Planning target: "proportion", "mean", "correlation", "t_test", "anova", "regression", or "sem".
margin_error	Margin of error for mean/proportion planning.
sd	Standard deviation for mean planning.
p	Expected proportion.
r	Expected correlation.
alpha	Significance level.
power	Desired power.
groups	Number of groups for ANOVA/t-test planning.
predictors	Number of predictors for regression planning.

Value

A list of planning estimates and warnings.

score_scales	<i>Score defined scales from survey responses</i>
--------------	---

Description

Applies scale scoring rules from the instrument to response data. Handles reverse coding, optional weighted composite score computation, and minimum valid item thresholds. Returns a data frame with one scored column per scale.

Usage

```
score_scales(data, instrument, keep_items = TRUE, keep_meta = TRUE)
```

Arguments

data	A tibble or data.frame of responses.
instrument	An sframe object.
keep_items	Logical. Whether to retain individual item columns in the output. Defaults to TRUE.
keep_meta	Logical. Whether to retain non-item columns (metadata) in the output. Defaults to TRUE.

Value

A data.frame with scored scale columns appended. Scale columns are named using the scale id.

See Also

[sf_scale\(\)](#), [reliability_report\(\)](#)

Examples

```
cs    <- sf_choices("ag5", 1:5,
                    c("Strongly disagree", "Disagree", "Neutral",
                      "Agree", "Strongly agree"))
i1    <- sf_item("sat_1", "Item 1", type = "likert",
                 choice_set = "ag5", scale_id = "sat")
i2    <- sf_item("sat_2", "Item 2", type = "likert",
                 choice_set = "ag5", scale_id = "sat")
i3    <- sf_item("sat_3", "Item 3 (reverse)", type = "likert",
                 choice_set = "ag5", scale_id = "sat", reverse = TRUE)
scale <- sf_scale("sat", "Satisfaction",
                  items = c("sat_1", "sat_2", "sat_3"), min_valid = 2L)
instr <- sf_instrument("Demo", components = list(cs, i1, i2, i3, scale))

responses <- data.frame(
  sat_1 = c(4, 5, 3),
  sat_2 = c(4, 4, 3),
  sat_3 = c(2, 1, 3),
  stringsAsFactors = FALSE
)

scored <- score_scales(responses, instr)
scored$sat
```

seminr_syntax

Generate seminr PLS-SEM syntax

Description

Generate seminr PLS-SEM syntax

Usage

```
seminr_syntax(model, data_name = "data", nboot = NULL, seed = 123)
```

Arguments

model	An sf_model() object of type "pls_sem".
data_name	Name of the data object in generated R code.
nboot	Number of bootstrap samples.
seed	Random seed for bootstrap syntax.

Value

An R syntax string for seminr.

sem_lavaan_syntax	<i>Generate lavaan CB-SEM syntax</i>
-------------------	--------------------------------------

Description

Generate lavaan CB-SEM syntax

Usage

```
sem_lavaan_syntax(model, instrument = NULL, standardised = TRUE)
```

Arguments

model	An <code>sf_model()</code> object of type "cb_sem".
instrument	Optional sframe object for indicator validation.
standardised	Logical. Adds a standardised-estimates fitting note.

Value

A lavaan syntax string.

sframe_builder_empty_state	<i>Create an empty SurveyStudio builder state</i>
----------------------------	---

Description

Create an empty SurveyStudio builder state

Usage

```
sframe_builder_empty_state()
```

Value

A list containing empty metadata, choice, item, scale, branching, and check collections suitable for SurveyStudio.

```
sframe_builder_state_from_instrument
```

Convert an instrument into a SurveyStudio builder state

Description

Convert an instrument into a SurveyStudio builder state

Usage

```
sframe_builder_state_from_instrument(instrument = NULL)
```

Arguments

`instrument` An sframe object or NULL.

Value

A builder state list. Component classes are restored so the state can be edited or validated by SurveyStudio.

```
sframe_builder_validate_draft
```

Validate a SurveyStudio draft state

Description

Validate a SurveyStudio draft state

Usage

```
sframe_builder_validate_draft(
  meta,
  choices = list(),
  items = list(),
  scales = list(),
  branching = list(),
  checks = list(),
  analysis_plan = list(),
  models = list(),
  render = list()
)
```

Arguments

- meta List of instrument metadata.
- choices, items, scales, branching, checks Lists of draft components.
- analysis_plan List of draft analysis-plan blocks.
- models List of draft model specifications.
- render List of rendering settings (welcome, header/logo, thankyou, theme) carried from the loaded instrument so previews and exports match.

Value

A list with valid, problems, and instrument.

sframe_demo_data	<i>Load bundled surveyframe demo data</i>
------------------	---

Description

Loads the bundled tourism-services .sframe instrument and simulated response dataset used in package examples and statistical workflow demos.

Usage

sframe_demo_data()

Value

A list with instrument, responses, instrument_path, and responses_path.

sframe_input_types_demo_data	<i>Load bundled input-types demo data</i>
------------------------------	---

Description

Loads the bundled .sframe instrument and simulated response dataset that cover all main survey input types supported by surveyframe.

Usage

sframe_input_types_demo_data()

Value

A list with instrument, responses, instrument_path, and responses_path.

sf_branch	<i>Define a branching rule</i>
-----------	--------------------------------

Description

Creates a single-condition branching rule that shows or hides a survey item depending on the value of a preceding item. Only single-condition rules are supported. Multi-condition AND/OR logic is planned for a later release.

Usage

```
sf_branch(
  item_id,
  depends_on,
  operator = c("==", "!=", "%in%", ">", ">=", "<", "<="),
  value,
  action = c("show", "hide")
)
```

Arguments

item_id	Character. The id of the item whose visibility this rule controls.
depends_on	Character. The id of the item whose response value triggers this rule.
operator	Character. The comparison operator. One of "==", "!=", "%in%", ">", ">=", "<", "<=", or "<=".
value	The value to compare against the response to depends_on. For "%in%", supply a character or numeric vector.
action	Character. What to do when the condition is met. Either "show" (default) or "hide".

Value

An object of class sf_branch (a named list).

See Also

[sf_instrument\(\)](#), [validate_sframe\(\)](#)

Examples

```
# Show an open-text follow-up only when the respondent selects "Other"
rule <- sf_branch(
  item_id = "gender_other",
  depends_on = "gender",
  operator = "==",
  value = "other",
  action = "show"
)
```

sf_check

*Define a design-time survey check***Description**

Specifies an attention, instructional, or trap check item at instrument design time. The check is stored in the instrument object and evaluated against collected response data by [quality_report\(\)](#). This function only defines the check. Evaluation happens later in [quality_report\(\)](#).

Usage

```
sf_check(
  id,
  item_id,
  type = c("attention", "instructional", "trap"),
  pass_values = NULL,
  fail_action = c("flag", "exclude"),
  label = NULL,
  notes = NULL
)
```

Arguments

id	Character. A unique identifier for this check.
item_id	Character. The id of the item used as the check. The item must be defined separately with sf_item() and included in the same instrument.
type	Character. The check type. One of: • "attention": the item has a stated correct answer and flags respondents who answer incorrectly. • "instructional": a manipulation check item used to test whether instructions were followed. • "trap": an item designed to be selected only by inattentive respondents (e.g. "Please select Strongly agree for this item.").
pass_values	Vector or NULL. The response value or values that constitute a pass. For "attention" and "instructional" types, at least one value should be supplied. For "trap" types, this is the value that should NOT be selected.
fail_action	Character. What quality_report() does with respondents who fail this check. Either "flag" (mark in the report but retain) or "exclude" (mark for exclusion).
label	Character or NULL. An optional human-readable label for the check, used in the quality report.
notes	Character or NULL. Optional free-text notes about the purpose or rationale of this check.

Value

An object of class sf_check (a named list).

See Also

[sf_item\(\)](#), [sf_instrument\(\)](#), [quality_report\(\)](#)

Examples

```
# An attention check: respondent must select 4
chk <- sf_check(
  id          = "attn_1",
  item_id     = "attention_check_q",
  type        = "attention",
  pass_values = 4,
  fail_action = "flag",
  label       = "Attention check 1"
)
```

sf_choices

Define a reusable choice set

Description

Creates a named set of response options that can be referenced by one or more items. Defining choices once and referencing them by id keeps the instrument consistent and reduces the risk of label mismatches across items that share the same response format.

Usage

```
sf_choices(id, values, labels, allow_other = FALSE, randomise = FALSE)
```

Arguments

id	Character. A unique identifier for this choice set. Referenced in the choice_set argument of sf_item() .
values	Character or numeric vector. The stored values corresponding to each response option. Must have the same length as labels.
labels	Character vector. The display labels shown to respondents. Must have the same length as values.
allow_other	Logical. Whether to append an open-text "Other" option at the end of the choice list. Defaults to FALSE.
randomise	Logical. Whether to randomise the display order of options at render time. Defaults to FALSE.

Value

An object of class sf_choices (a named list).

See Also

[sf_item\(\)](#), [sf_instrument\(\)](#)

Examples

```
# A five-point agreement scale
agree5 <- sf_choices(
  id      = "agree5",
  values  = 1:5,
  labels  = c("Strongly disagree", "Disagree", "Neutral",
              "Agree", "Strongly agree")
)

# A yes/no set
yn <- sf_choices(
  id      = "yn",
  values  = c("yes", "no"),
  labels  = c("Yes", "No")
)
```

sf_construct

*Define a latent or composite construct***Description**

Define a latent or composite construct

Usage

```
sf_construct(
  id,
  label = NULL,
  items = character(0),
  mode = c("reflective", "composite", "formative", "single_item"),
  weights = NULL
)
```

Arguments

id	Construct identifier. Must start with a letter and contain only letters, numbers, and _ characters.
label	Human-readable construct label.
items	Character vector of indicator item IDs.
mode	Measurement mode. One of "reflective", "composite", "formative", or "single_item".
weights	Optional indicator weights for later PLS-SEM planning.

Value

An object of class sf_construct.

sf_covariance	<i>Define a covariance between constructs</i>
---------------	---

Description

Define a covariance between constructs

Usage

```
sf_covariance(from, to, label = NULL)
```

Arguments

from	First construct ID.
to	Second construct ID.
label	Optional label.

Value

An object of class sf_covariance.

sf_indirect	<i>Define an indirect effect path</i>
-------------	---------------------------------------

Description

Define an indirect effect path

Usage

```
sf_indirect(from, through, to, label = NULL)
```

Arguments

from	Source construct ID.
through	Character vector of mediator construct IDs.
to	Target construct ID.
label	Optional effect label.

Value

An object of class sf_indirect.

sf_instrument

*Create a survey instrument object***Description**

Assembles a survey instrument from its component objects. This is the top-level constructor for the `sframe` class. All other constructors (`sf_item()`, `sf_choices()`, `sf_scale()`, `sf_branch()`, `sf_check()`) produce components that are passed into this function via components.

Usage

```
sf_instrument(
  title,
  version = "0.1.0",
  description = NULL,
  authors = NULL,
  languages = "en",
  components = list(),
  render = NULL,
  analysis_plan = list(),
  models = list()
)
```

Arguments

<code>title</code>	Character. The title of the survey instrument.
<code>version</code>	Character. A semantic version string. Defaults to "0.1.0".
<code>description</code>	Character or NULL. A brief description of the instrument and its intended population or purpose.
<code>authors</code>	Character vector or NULL. Author names, used in codebooks and reports.
<code>languages</code>	Character vector. Language codes for the instrument. Defaults to "en". Multi-language support is planned for a later release.
<code>components</code>	List. A list of component objects created by the constructor family: <code>sf_item()</code> , <code>sf_choices()</code> , <code>sf_scale()</code> , <code>sf_branch()</code> , and <code>sf_check()</code> . Components are sorted by class automatically. Supply components created by the surveyframe constructors.
<code>render</code>	List or NULL. Optional rendering hints passed to <code>render_survey()</code> , such as theme colour or progress bar visibility.
<code>analysis_plan</code>	List. Optional pre-planned analysis blocks created in the HTML SurveyBuilder Analyse mode.
<code>models</code>	List. Optional model specifications created with <code>sf_model()</code> or imported from a <code>.sframe</code> file.

Value

An object of class `sframe` with slots `meta`, `items`, `choices`, `scales`, `branching`, `checks`, `analysis_plan`, `models`, and `render`.

See Also

`sf_item()`, `sf_choices()`, `sf_scale()`, `sf_branch()`, `sf_check()`, `validate_sframe()`, `write_sframe()`

Examples

```
choices <- sf_choices("agree5", 1:5,
  c("Strongly disagree", "Disagree", "Neutral", "Agree", "Strongly agree"))

visitor_cs <- sf_choices("visitor", c("new", "returning"),
  c("New visitor", "Returning visitor"))

item1 <- sf_item("sat_1", "The service met my expectations.",
  type = "likert", choice_set = "agree5",
  scale_id = "sat", required = TRUE)
item2 <- sf_item("sat_2", "I would recommend this service.",
  type = "likert", choice_set = "agree5",
  scale_id = "sat", required = TRUE)
item3 <- sf_item("visitor_type", "I am a",
  type = "single_choice", choice_set = "visitor")

scale <- sf_scale("sat", "Satisfaction", items = c("sat_1", "sat_2"))

# The analysis_plan binds each research question to a statistical method
# and the variable roles it needs. Declare it before any data arrive.
plan <- list(
  list(
    id = "RQ1",
    research_question = "Do new and returning visitors differ in satisfaction?",
    family = "group_comparison",
    method = "mann_whitney",
    roles = list(group = "visitor_type", outcome = "sat"),
    options = list(alpha = 0.05)
  )
)

instr <- sf_instrument(
  title = "Service Quality Survey",
  version = "1.0.0",
  components = list(choices, visitor_cs, item1, item2, item3, scale),
  analysis_plan = plan
)
print(instr)
length(instr$analysis_plan)
```

sf_item

*Define a survey item***Description**

Creates a single survey item object for inclusion in an sframe instrument. Items are the atomic units of a survey instrument. Every item must have a unique id within the instrument it is added to.

Usage

```
sf_item(
  id,
  label,
  type = c("likert", "single_choice", "multiple_choice", "numeric", "text", "textarea",
    "date", "matrix", "slider", "ranking", "rating", "section_break", "text_block"),
  required = FALSE,
  choice_set = NULL,
  scale_id = NULL,
  reverse = FALSE,
  help = NULL,
  placeholder = NULL,
  matrix_items = NULL,
  slider_min = NULL,
  slider_max = NULL,
  slider_step = NULL,
  rating_max = NULL,
  rating_icon = NULL,
  section_intro = NULL,
  page = NULL
)
```

Arguments

id	Character. A unique identifier for this item. Used as the column name in response data. Must contain only letters, numbers, and _ characters.
label	Character. The question text or content displayed to the respondent.
type	Character. The response type. One of "likert", "single_choice", "multiple_choice", "numeric", "text", "textarea", "date", "matrix", "slider", "ranking", "rating", "section_break", or "text_block".
required	Logical. Whether the respondent must answer this item.
choice_set	Character or NULL. The id of a choice set defined with sf_choices() .
scale_id	Character or NULL. The id of the scale this item belongs to.
reverse	Logical. Whether this item is reverse-coded within its scale.
help	Character or NULL. Help text displayed beneath the question.
placeholder	Character or NULL. Placeholder text for text inputs.

matrix_items	Character vector or NULL. Row labels for "matrix" type.
slider_min	Numeric or NULL. Minimum value for "slider" type.
slider_max	Numeric or NULL. Maximum value for "slider" type.
slider_step	Numeric or NULL. Step size for "slider" type.
rating_max	Integer or NULL. Maximum rating for "rating" type.
rating_icon	Character or NULL. Icon type: "star" or "heart".
section_intro	Character or NULL. Intro text for "section_break" type.
page	Integer or NULL. Page number for multi-page surveys.

Value

An object of class `sf_item` (a named list).

See Also

`sf_instrument()`, `sf_choices()`, `sf_scale()`

Examples

```
item <- sf_item(
  id = "sat_overall", label = "Overall, how satisfied are you?",
  type = "likert", required = TRUE, choice_set = "agree5",
  scale_id = "satisfaction"
)

sec <- sf_item("sec_1", "Demographic Information", type = "section_break",
  section_intro = "Please answer the following questions.")
```

sf_model

Create a surveyframe model specification

Description

Create a surveyframe model specification

Usage

```
sf_model(
  id,
  label = NULL,
  type = c("efa", "cfa", "cb_sem", "pls_sem"),
  engine = NULL,
  constructs = list(),
  paths = list(),
  covariances = list(),
  indirect = list(),
  options = list()
)
```

Arguments

id	Model identifier.
label	Human-readable model label.
type	Model type. One of "efa", "cfa", "cb_sem", or "pls_sem".
engine	Optional engine name. Defaults to "lavaan" for CFA/CB-SEM and "semnr" for PLS-SEM.
constructs	List of <code>sf_construct()</code> objects.
paths	List of <code>sf_path()</code> objects.
covariances	List of <code>sf_covariance()</code> objects.
indirect	List of <code>sf_indirect()</code> objects.
options	List of model options, such as estimator, missing, bootstrap, or standardised.

Value

An object of class `sf_model`.

sf_path	<i>Define a structural path between constructs</i>
---------	--

Description

Define a structural path between constructs

Usage

```
sf_path(from, to, label = NULL)
```

Arguments

from	Source construct ID.
to	Target construct ID.
label	Optional lavaan label for the path.

Value

An object of class `sf_path`.

sf_scale	<i>Define a scored scale</i>
----------	------------------------------

Description

Creates a scale definition that groups items and specifies how composite scores are computed. The scale carries scoring rules used by [score_scales\(\)](#) and measurement structure used by [reliability_report\(\)](#), [item_report\(\)](#), and [cfa_syntax\(\)](#).

Usage

```
sf_scale(
  id,
  label,
  items,
  method = c("mean", "sum"),
  min_valid = NULL,
  reverse_items = NULL,
  weights = NULL
)
```

Arguments

id	Character. A unique identifier for this scale. Referenced in the scale_id argument of sf_item() .
label	Character. A human-readable name for the scale, used in reports and codebooks.
items	Character vector. The id values of items that belong to this scale. Order controls presentation in reports; scoring uses the same item IDs regardless of order.
method	Character. Scoring method. Either "mean" (default) or "sum".
min_valid	Integer or NULL. The minimum number of non-missing items required to compute a score for a respondent. When NULL, all items must be present. Used by score_scales() .
reverse_items	Character vector or NULL. A subset of items that are reverse-coded. These can also be flagged at the item level with the reverse argument in sf_item() . Both sources are respected.
weights	Numeric vector or NULL. Item weights for weighted scoring. Must have the same length as items if supplied. score_scales() applies the weights to either method = "mean" or method = "sum".

Value

An object of class sf_scale (a named list).

See Also

[sf_item\(\)](#), [score_scales\(\)](#), [reliability_report\(\)](#)

Examples

```
sat_scale <- sf_scale(
  id      = "satisfaction",
  label   = "Customer Satisfaction",
  items   = c("sat_overall", "sat_speed", "sat_quality"),
  method  = "mean",
  min_valid = 2,
  reverse_items = NULL
)
```

summary.sframe	<i>Summarise an sframe instrument object</i>
----------------	--

Description

Prints a structured summary of an sframe object including metadata, item type counts, scale definitions, branching rules, and check specifications.

Usage

```
## S3 method for class 'sframe'
summary(object, ...)
```

Arguments

object	An object of class sframe.
...	Ignored. Present for S3 consistency.

Value

object, invisibly.

Examples

```
item <- sf_item("q1", "How satisfied are you?", type = "likert",
               choice_set = "agree5")
instr <- sf_instrument("My Survey", components = list(item))
summary(instr)
```

summary.sf_branch	<i>Summarise an sf_branch object</i>
-------------------	--------------------------------------

Description

Summarise an sf_branch object

Usage

```
## S3 method for class 'sf_branch'  
summary(object, ...)
```

Arguments

object	An object of class sf_branch.
...	Ignored. Present for S3 consistency.

Value

object, invisibly.

summary.sf_check	<i>Summarise an sf_check object</i>
------------------	-------------------------------------

Description

Summarise an sf_check object

Usage

```
## S3 method for class 'sf_check'  
summary(object, ...)
```

Arguments

object	An object of class sf_check.
...	Ignored. Present for S3 consistency.

Value

object, invisibly.

summary.sf_choices	<i>Summarise an sf_choices object</i>
--------------------	---------------------------------------

Description

Summarise an sf_choices object

Usage

```
## S3 method for class 'sf_choices'  
summary(object, ...)
```

Arguments

object	An object of class sf_choices.
...	Ignored. Present for S3 consistency.

Value

object, invisibly.

summary.sf_item	<i>Summarise an sf_item object</i>
-----------------	------------------------------------

Description

Summarise an sf_item object

Usage

```
## S3 method for class 'sf_item'  
summary(object, ...)
```

Arguments

object	An object of class sf_item.
...	Ignored. Present for S3 consistency.

Value

object, invisibly.

summary.sf_model	<i>Summarise an sf_model object</i>
------------------	-------------------------------------

Description

Summarise an sf_model object

Usage

```
## S3 method for class 'sf_model'  
summary(object, ...)
```

Arguments

object	An object of class sf_model.
...	Ignored. Present for S3 consistency.

Value

object, invisibly.

summary.sf_scale	<i>Summarise an sf_scale object</i>
------------------	-------------------------------------

Description

Summarise an sf_scale object

Usage

```
## S3 method for class 'sf_scale'  
summary(object, ...)
```

Arguments

object	An object of class sf_scale.
...	Ignored. Present for S3 consistency.

Value

object, invisibly.

survey_module_server	<i>Shiny module server for an embedded survey</i>
----------------------	---

Description

Renders the survey instrument and collects the respondent's answers. Returns a reactive that holds NULL until the form is submitted, then returns the response as a named list (one element per visible item).

Usage

```
survey_module_server(id, instrument, on_submit = NULL)
```

Arguments

id	A character string matching the id passed to survey_module_ui() .
instrument	An sframe object, or a reactive that returns one. Changing the reactive value resets the survey.
on_submit	Optional function of one argument. Called immediately after submission with the response list. Useful for writing to a database or sending an email without waiting for an shiny::observeEvent() elsewhere in the app.

Value

A reactive that returns NULL before submission and the response list after.

See Also

[survey_module_ui\(\)](#)

Examples

```
# See survey_module_ui() for a complete example.
```

survey_module_ui	<i>Shiny module UI for an embedded survey</i>
------------------	---

Description

Places a survey rendered by surveyframe inside a larger Shiny application. Pair with [survey_module_server\(\)](#) in the server function. The module renders the full instrument including welcome page, all item types, branching logic, required-field validation, and a thank-you screen.

Usage

```
survey_module_ui(id, width = "100%")
```

Arguments

<code>id</code>	A character string. The module namespace ID, passed identically to survey_module_server() .
<code>width</code>	Character. CSS width for the survey card. Defaults to "100%".

Value

A shiny.tag object.

See Also

[survey_module_server\(\)](#), [launch_studio\(\)](#), [export_static_survey\(\)](#)

Examples

```
## Not run:
# Minimal embedding example:
library(shiny)
library(surveyframe)

cs    <- sf_choices("ag5", 1:5, c("SD", "D", "N", "A", "SA"))
item  <- sf_item("q1", "Rate your experience.", type = "likert",
               choice_set = "ag5", required = TRUE)
instr <- sf_instrument("Quick Survey", components = list(cs, item))

ui <- fluidPage(
  survey_module_ui("demo"),
  verbatimTextOutput("result")
)

server <- function(input, output, session) {
  resp <- survey_module_server("demo", instrument = instr)
  output$result <- renderPrint({
    req(resp())
    resp()
  })
}

shinyApp(ui, server)

## End(Not run)
```

theme_surveyframe	<i>surveyframe brand theme for ggplot2</i>
-------------------	--

Description

A light, publication-oriented ggplot2 theme matching the surveyframe report brand: dark ink typography, a teal accent, and quiet horizontal grid lines. Apply it to any ggplot object, including the plots returned by `run_analysis_plan()` when `plots = TRUE`.

Usage

```
theme_surveyframe(base_size = 12, base_family = "")
```

Arguments

<code>base_size</code>	Numeric. Base font size in points. Defaults to 12.
<code>base_family</code>	Character. Base font family. Defaults to "" (the device default).

Value

A ggplot2 theme object.

See Also

[run_analysis_plan\(\)](#)

Examples

```
library(ggplot2)
ggplot(mtcars, aes(wt, mpg)) +
  geom_point(colour = "#16B3B1") +
  theme_surveyframe()
```

validate_model	<i>Validate a surveyframe model specification</i>
----------------	---

Description

Checks model IDs, construct IDs, indicators, structural path endpoints, duplicate paths, indirect paths, and engine/type compatibility.

Usage

```
validate_model(model, instrument = NULL, strict = TRUE)
```

Arguments

model	An <code>sf_model()</code> object or compatible list.
instrument	Optional sframe object. When supplied, model indicators must match instrument item IDs.
strict	Logical. When TRUE, invalid models raise an error. When FALSE, a list with valid and problems is returned.

Value

The model invisibly when valid and `strict = TRUE`, otherwise a validation result list.

validate_sframe	<i>Validate an instrument object</i>
-----------------	--------------------------------------

Description

Checks the internal consistency of an sframe instrument object and reports all detected problems. Validation is performed automatically by `write_sframe()` and optionally by `read_sframe()`. It can also be run independently at any point during instrument construction.

Usage

```
validate_sframe(instrument, strict = TRUE)
```

Arguments

instrument	An sframe object created by <code>sf_instrument()</code> .
strict	Logical. When TRUE (default), any detected problem raises an error of class <code>sframe_validation_error</code> . When FALSE, problems are returned as a character vector of messages without stopping.

Details

The following checks are performed:

- Duplicate item IDs
- Invalid item IDs
- Duplicate choice-set IDs
- Duplicate scale IDs
- Items with missing labels
- Items referencing a missing `choice_set` in the instrument
- Items referencing a missing `scale_id` in the instrument
- Items marked `reverse = TRUE` without a `scale_id`
- Choice sets referenced by items but not present in the instrument

- Scale items vectors containing IDs not present in the instrument
- Branching rules referencing item IDs not present in the instrument
- Attention checks referencing item IDs not present in the instrument
- Analysis plan roles referencing missing variables or models
- Model specifications referencing missing indicators or constructs

Value

When `strict = TRUE` and the instrument is valid, the instrument is returned invisibly with `meta$validated` set to `TRUE`. When `strict = FALSE`, a named list with elements `valid` (logical) and `problems` (character vector) is returned.

See Also

`sf_instrument()`, `write_sframe()`

Examples

```
# Build a minimal valid instrument and validate it
cs  <- sf_choices("ag5", 1:5,
  c("Strongly disagree", "Disagree", "Neutral",
    "Agree", "Strongly agree"))
item <- sf_item("sat_1", "The service met my expectations.",
  type = "likert", choice_set = "ag5", scale_id = "sat")
scale <- sf_scale("sat", "Satisfaction", items = "sat_1")
instr <- sf_instrument("Demo Survey", components = list(cs, item, scale))

# Non-strict: returns a list without stopping
result <- validate_sframe(instr, strict = FALSE)
result$valid
result$problems

# Strict: returns instrument invisibly when valid
validated <- validate_sframe(instr, strict = TRUE)
isTRUE(validated$meta$validated)
```

validity_report

Validity report for construct models

Description

Validity report for construct models

Usage

```
validity_report(loadings, construct_scores = NULL)
```

Arguments

loadings	A data.frame with columns construct, item, and loading, or a named list of loading vectors by construct.
construct_scores	Optional data.frame of construct scores for Fornell-Larcker, HTMT, and inter-construct correlations.

Value

An object of class `sframe_validity_report`.

write_sframe	<i>Write an instrument to a .sframe file</i>
--------------	--

Description

Serialises an sframe instrument object to a UTF-8 JSON file with a SHA-256 integrity hash. The instrument is validated before writing unless the object already carries a valid status. The hash is computed over the full serialised content with the `hash.value` field set to an empty string.

Usage

```
write_sframe(instrument, path, pretty = TRUE, overwrite = FALSE)
```

Arguments

instrument	An sframe object created by <code>sf_instrument()</code> .
path	Character. The file path to write to. The .sframe extension is appended automatically if not already present.
pretty	Logical. Whether to write formatted JSON with indentation. Defaults to TRUE. Set to FALSE for compact files.
overwrite	Logical. Whether to overwrite an existing file. Defaults to FALSE.

Value

The file path, invisibly.

See Also

`read_sframe()`, `validate_sframe()`

Examples

```
instr <- read_sframe(
  system.file("extdata", "tourism_services_demo.sframe",
    package = "surveyframe")
)
out <- write_sframe(instr, tempfile(fileext = ".sframe"))
file.exists(out)
```

Index

`add_model`, [3](#)
`assumption_report`, [4](#)

`cfa_lavaan_syntax`, [5](#)
`cfa_syntax`, [6](#)
`cfa_syntax()`, [9](#), [58](#)
`codebook_report`, [7](#)
`codebook_report()`, [38](#)

`descriptives_report`, [8](#)

`efa_report`, [9](#)
`efa_report()`, [6](#)
`efa_solution`, [10](#)
`efa_syntax`, [11](#)
`export_google_sheet`, [11](#)
`export_google_sheet()`, [35](#)
`export_static_survey`, [12](#)
`export_static_survey()`, [64](#)

`format.sf_branch`, [14](#)
`format.sf_check`, [15](#)
`format.sf_choices`, [15](#)
`format.sf_item`, [16](#)
`format.sf_model`, [16](#)
`format.sf_scale`, [17](#)
`format.sframe`, [14](#)

`item_report`, [17](#)
`item_report()`, [36](#), [58](#)

`launch_builder`, [18](#)
`launch_builder()`, [13](#), [19](#), [22](#)
`launch_builder_demo`, [19](#)
`launch_dashboard`, [19](#)
`launch_dashboard()`, [22](#)
`launch_dashboard_demo`, [21](#)
`launch_dashboard_demo()`, [20](#)
`launch_studio`, [22](#)
`launch_studio()`, [13](#), [19](#), [20](#), [41](#), [64](#)
`launch_studio_demo`, [23](#)

`missing_data_report`, [24](#)
`model_json`, [24](#)
`model_report_template`, [25](#)

`outlier_report`, [25](#)

`posthoc_report`, [26](#)
`print.sf_branch`, [28](#)
`print.sf_check`, [28](#)
`print.sf_choices`, [29](#)
`print.sf_item`, [30](#)
`print.sf_model`, [30](#)
`print.sf_scale`, [31](#)
`print.sframe`, [27](#)

`quality_report`, [31](#)
`quality_report()`, [20](#), [34](#), [35](#), [38](#), [49](#), [50](#)

`read_responses`, [33](#)
`read_responses()`, [12](#), [20](#), [22](#), [32](#), [35](#), [41](#)
`read_sframe`, [34](#)
`read_sframe()`, [18](#), [19](#), [22](#), [66](#), [68](#)
`read_sheet_responses`, [35](#)
`read_sheet_responses()`, [11](#), [12](#), [20](#), [41](#), [42](#)
`reliability_report`, [36](#)
`reliability_report()`, [6](#), [9](#), [18](#), [35](#), [38](#), [43](#),
[58](#)
`render_report`, [37](#)
`render_report()`, [7](#), [39](#)
`render_results`, [39](#)
`render_results()`, [42](#)
`render_survey`, [40](#)
`render_survey()`, [13](#), [53](#)
`run_analysis_plan`, [41](#)
`run_analysis_plan()`, [19](#), [20](#), [39](#), [65](#)

`sample_size_plan`, [42](#)
`score_scales`, [43](#)
`score_scales()`, [20](#), [32](#), [34](#), [35](#), [58](#)
`sem_lavaan_syntax`, [45](#)
`semnr_syntax`, [44](#)

sf_branch, 48
sf_branch(), 53, 54
sf_check, 49
sf_check(), 32, 53, 54
sf_choices, 50
sf_choices(), 53–56
sf_construct, 51
sf_construct(), 57
sf_covariance, 52
sf_covariance(), 5, 57
sf_indirect, 52
sf_indirect(), 57
sf_instrument, 53
sf_instrument(), 32, 33, 48, 50, 56, 66–68
sf_item, 55
sf_item(), 49, 50, 53, 54, 58
sf_model, 56
sf_model(), 4, 5, 24, 25, 44, 45, 53, 66
sf_path, 57
sf_path(), 57
sf_scale, 58
sf_scale(), 18, 36, 43, 53, 54, 56
sframe_builder_empty_state, 45
sframe_builder_state_from_instrument,
46
sframe_builder_validate_draft, 46
sframe_demo_data, 47
sframe_input_types_demo_data, 47
shiny::observeEvent(), 63
shiny::runApp(), 20, 22
summary.sf_branch, 60
summary.sf_check, 60
summary.sf_choices, 61
summary.sf_item, 61
summary.sf_model, 62
summary.sf_scale, 62
summary.sframe, 59
survey_module_server, 63
survey_module_server(), 63, 64
survey_module_ui, 63
survey_module_ui(), 63

tempdir(), 13
theme_surveyframe, 65

utils::browseURL(), 18

validate_model, 65
validate_sframe, 66
validate_sframe(), 34, 48, 54, 68
validity_report, 67

write_sframe, 68
write_sframe(), 12, 34, 54, 66, 67