

Package ‘svUnit’

July 23, 2025

Type Package

Version 1.0.6

Date 2021-04-18

Title 'SciViews' - Unit, Integration and System Testing

Description A complete unit test system and functions to implement its GUI part.

Maintainer Philippe Grosjean <phgrosjean@sciviews.org>

Depends R (>= 1.9.0)

Imports utils

Suggests svGUI, datasets, XML, RUnit, knitr, markdown, covr, spelling

License GPL-2

URL <https://github.com/SciViews/svUnit>,
<https://www.sciviews.org/svUnit/>

BugReports <https://github.com/SciViews/svUnit/issues>

RoxygenNote 7.1.0

VignetteBuilder knitr

Encoding UTF-8

Language en-US

NeedsCompilation no

Author Philippe Grosjean [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-2694-9471>>)

Repository CRAN

Date/Publication 2021-04-19 05:20:02 UTC

Contents

check	2
guiTestReport	4
koUnit	5

Log	7
makeTestListFromExamples	8
svSuite	12
svSuiteData	16
svTestData	19
unitTests.svUnit	21

Index	22
--------------	-----------

check	<i>SciViews-R Unit assertions (check functions)</i>
-------	---

Description

These functions define the assertions in test functions. They are designed to check the result of some test calculation.

Usage

```

checkEquals(
  target,
  current,
  msg = "",
  tolerance = .Machine$double.eps^0.5,
  checkNames = TRUE,
  ...
)

checkEqualsNumeric(
  target,
  current,
  msg = "",
  tolerance = .Machine$double.eps^0.5,
  ...
)

checkIdentical(target, current, msg = "")

checkTrue(expr, msg = "")

checkException(expr, msg = "", silent = getOption("svUnit.silentException"))

DEACTIVATED(msg = "")

```

Arguments

target	a target object as reference for comparison.
current	An object created for comparison (not an S4 class object).

msg	An optional (short!) message to document a test. This message is stored in the log and printed in front of each test report.
tolerance	numeric ≥ 0 . A numeric check does not fail if differences are smaller than 'tolerance'.
checkNames	Flag, if FALSE the names attributes are set to NULL for both current and target before performing the check.
...	Optional arguments passed to all.equal() or all.equal.numeric() .
expr	Syntactically valid R expression which can be evaluated and must return a logical vector (TRUE FALSE). A named expression is also allowed but the name is disregarded. In checkException() , expr is supposed to generate an error to pass the test.
silent	Flag passed on to try, which determines if the error message generated by the checked function is displayed at the R console. By default, it is FALSE.

Details

These check functions are equivalent to various methods of the class `junit.framework.Assert` of Java `junit` framework. They should be code-compatible with functions of same name in 'RUnit' 0.4.17, except for [checkTrue\(\)](#) that is vectorized here, but accept only a scalar result in 'RUnit'. For scalar test, the behavior of the function is the same in both packages. See [svTest\(\)](#) for examples of use of these functions in actual test cases attached to R objects. See also the note about S4 objects in the [RUnit::checkTrue\(\)](#) online help of the 'RUnit' package.

Value

These function return TRUE if the test succeeds, FALSE if it fails, possibly with a 'result' attribute containing more information about the problem. This is very different from corresponding functions in 'RUnit' that stop with an error in case of test failure. Consequently, current functions do not require the complex evaluation framework designed in 'RUnit' for that reason.

Author(s)

Written by Ph. Grosjean, inspired from the general design of the 'RUnit' package by Thomas Konig, Klaus Junemann & Matthias Burger.

See Also

[svTest\(\)](#), [Log\(\)](#), [guiTestReport\(\)](#), [RUnit::checkTrue](#)

Examples

```
clearLog()      # Clear the svUnit log

# All these tests are correct
(checkEquals(c("A", "B", "C"), LETTERS[1:3]))
(checkEqualsNumeric(1:10, seq(1, 10)))
(checkIdentical(iris[1:50, ], iris[iris$Species == "setosa",]))
(checkTrue(1 < 2))
(checkException(log("a")))
```

```

Log()    # See what's recorded in the log

# ... but these ones fail
(checkEquals("A", LETTERS[1:3]))
(checkEqualsNumeric(2:11, seq(1, 10)))
(checkIdentical(iris[1:49, ], iris[iris$Species == "setosa",]))
(checkTrue(1 > 2))
(checkException(log(1)))
Log()    # See what's recorded in the log

# Create a test function and run it
foo <- function(x, y = 2)
  return(x * y)
test(foo) <- function() {
  #DEACTIVATED()
  checkEqualsNumeric(5, foo(2))
  checkEqualsNumeric(6, foo(2, 3))
  checkTrue(is.test(foo))
  checkTrue(is.test(test(foo)))
  checkIdentical(test(foo), attr(foo, "test"))
  checkException(foo("b"))
  checkException(foo(2, "a"))
}
(runTest(foo))

# Of course, everything is recorded in the log
Log()

clearLog()

```

guiTestReport

Report or give feedback to the GUI client about running test units

Description

These functions are usually not called from the command line. They return data to compatible GUI clients, like Komodo Edit with the SciViews-K extension.

Usage

```

guiTestReport(object, sep = "\t", path = NULL, ...)

guiSuiteList(sep = "\t", path = NULL, compare = TRUE)

guiSuiteAutoList(...)

guiTestFeedback(object, path = NULL, ...)

```

Arguments

object	a 'svUnitData' object.
sep	Field separator to use in the results.
path	Path where to write a 'Suites.txt' file with the list of currently available test suites (to be used by the GUI client). If NULL, no file is written (by default).
...	Not used currently.
compare	Do we compare the list of available test suite and return something to the GUI client only if there are changes in the list? This is used (when TRUE) to avoid unnecessary multiple processing of the same list by the GUI client.

Value

[guiSuiteList\(\)](#) returns the list of available test suites invisibly. [guiSuiteAutoList\(\)](#) is used to establish a callback to automatically list the available test suites in the GUI. It is not intended to be called directly by the user. The other functions just return TRUE invisibly. They are used for their side effect of sending data to compatible GUI clients.

Author(s)

Philippe Grosjean

See Also

[svTest\(\)](#), [svSuite\(\)](#), [koUnit_version\(\)](#)

 koUnit

Interact with the test unit GUI in Komodo/SciViews-K

Description

These functions allow controlling the test unit module (R Unit tab at right) in Komodo with SciViews-K and SciViews-K Unit extensions. R must be correctly connected to Komodo, meaning that the 'svGUI' package must be loaded with proper configuration of client/server socket connections between R and Komodo. See the manual about SciViews-K for more information. The functions defined here are the same as JavaScript functions defined in the 'sv.r.unit' namespace in Komodo/SciViews-K Unit. For instance, [koUnit_runTest\(\)](#) is equivalent to `sv.r.unit.runTest()`; in a Javascript macro in Komodo.

Usage

```
koUnit_setAutoTest(state)
```

```
koUnit_isAutoTest()
```

```
koUnit_runTest()
```

```
koUnit_showRUnitPane(state)
```

```
koUnit_version()
```

Arguments

state	TRUE or FALSE, or missing for <code>koUnit_showRUnitPane()</code> , in this case, the R Unit pane visibility is toggled.
-------	--

Value

`koUnit_isAutoTest()` returns TRUE if the test unit is in auto mode in Komodo (the selected tests are run automatically each time a .R file edited in Komodo is saved).

`koUnit_version()` returns the version for which the SciViews-K Unit extension was designed for. This allow to check if this version is compatible with current 'svUnit' R package version, and to propose to update the Komodo extension if needed (this mechanism is not running currently, but it will be implemented in the future to avoid or limit incompatibilities between respective R and Komodo extensions).

The other functions are invoked for their side-effect and they return nothing. Note, however, that correct execution of this code in Komodo is verified, and the functions issue an error in R if they fail to execute correctly in Komodo.

Author(s)

Philippe Grosjean

See Also

`guiTestReport()`

Examples

```
## Not run:
# Make sure R is communicating with Komodo before use, see ?koCmd in svGUI
koUnit_version()

# Toggle visibility of the R Unit pane in Komodo twice
koUnit_showRUnitPane()
koUnit_showRUnitPane()

# Make sure that the R Unit pane is visible
koUnit_showRUnitPane(TRUE)

# Is the test unit running in auto mode?
koUnit_isAutoTest()

# Toggle auto test mode off
koUnit_setAutoTest(FALSE)

# Run the test units from within Komodo
```

```
koUnit_runTest()

## End(Not run)
```

Log

SciViews-R log management functions

Description

These functions define the code of test functions. They are designed to check the result of some test calculation.

Usage

```
Log(description = NULL)

createLog(description = NULL, deleteExisting = FALSE)

clearLog()

errorLog(stopit = TRUE, summarize = TRUE)

lastTest()

lastSuite()
```

Arguments

<code>description</code>	A (short) character string describing this test suite log.
<code>deleteExisting</code>	Do we delete an existing a <code>.Log</code> object already defined in <code>.GlobalEnv</code> (no, by default)?
<code>stopit</code>	Do we issue an error (stop()) in case of any error or failure? This is particularly useful if you want to interrupt R CMD check on packages, when you included one or more test suites in examples (see <code>?unitTests</code>).
<code>summarize</code>	Should the summary of the log be printed in case we stop execution of the code when an error is found (see <code>stopit = argument</code>). It is, indeed, useful to indicate at this time which tests failed or raised an error. So, this argument should usually be left at its default value.

Details

`svUnit` records results of assertions (using the `checkxxx()` functions) in a `'svSuiteData'` object named `.Log` and located in `.GlobalEnv`. Hence, this log is easy to access. However, in order to avoid errors in your code in case this object was deleted, or not created, it is better to access it using [Log\(\)](#) which take care to create the object if it is missing.

Value

`log()` and `createLog()` return the `.Log` object defined in `.GlobalEnv` by reference (it is indeed an environment). So, you can use its content (and change it, if you write functions to manipulate this log).

`clearLog()` return invisibly TRUE or FALSE, depending if an existing log object was deleted or not.

`errorLog()` is mainly used for its side-effect of stopping code execution and/or printing a summary of the test runs in the context of example massaging in R CMD check (see the "Writing R extensions" manual). However, this function also returns invisibly a contingency table with the number of successes, failures, errors and deactivated tests recorded so far.

`lastTest()` and `lastSuite()` recall results of last test and last suite run, respectively.

Author(s)

Philippe Grosjean

See Also

`svSuiteData()`, `svSuite()`, `svTest()`, `checkEquals()`

Examples

```
clearLog()           # Clear the svUnit log

# Two correct tests
(checkTrue(1 < 2))
(checkException(log("a")))
errorLog()           # Nothing, because there is no error

## Not run:
(checkTrue(1 > 2))    # This test fails
lastTest()           # Print results of last test
errorLog()           # Stop and summarize the tests run so far

## End(Not run)

clearLog()
```

makeTestListFromExamples

Create, attach to and manipulate test functions in R objects

Description

Test functions are functions without arguments with class 'svTest' containing one or more assertions using `checkxxx()` functions. They can be attached to any object as a 'test' attribute. They can also be transferred into a more formal test unit file on disk by applying the `makeUnit()` method.

Usage

```
makeTestListFromExamples(packageName, manFilesDir, skipFailing = FALSE)

svTest(testFun)

## S3 method for class 'svTest'
print(x, ...)

as.svTest(x)

is.svTest(x)

is.test(x)

test(x)

test(x) <- value

makeUnit(x, ...)

## Default S3 method:
makeUnit(
  x,
  name = make.names(deparse(substitute(x))),
  dir = tempdir(),
  objfile = "",
  codeSetUp = NULL,
  codeTearDown = NULL,
  ...
)

## S3 method for class 'svTest'
makeUnit(
  x,
  name = make.names(deparse(substitute(x))),
  dir = tempdir(),
  objfile = "",
  codeSetUp = NULL,
  codeTearDown = NULL,
  ...
)

runTest(x, ...)

## Default S3 method:
runTest(
  x,
  name = deparse(substitute(x)),
```

```

    objfile = "",
    tag = "",
    msg = "",
    ...
)

## S3 method for class 'list'
runTest(x, ...)

## S3 method for class 'svTest'
runTest(
  x,
  name = deparse(substitute(x)),
  objfile = "",
  tag = "",
  msg = "",
  ...
)

```

Arguments

packageName	A character string identifying the package from which to extract examples.
manFilesDir	A character string identifying the directory holding the manual pages and examples.
skipFailing	A logical indicating whether missing or failing documentation examples should be marked as skipped instead of as failure.
testFun	A function without arguments defining assertions (using checkxxx() functions) for tests to be transformed into a 'svTest' object.
x	Any kind of object.
...	Further arguments to the method (not used yet).
value	The tests to place in the object (as 'test' attribute); could be a 'svTest' object, or a function without arguments with assertions (checkxxx() functions).
name	The name of a test.
dir	The directory where to create the test unit file.
objfile	The path to the file containing the original source code of the object being tested. This argument is used to bring a context for a test and allow a GUI to automatically open the source file for edition when the user clicks on a test that failed or raised an error.
codeSetUp	An expression with some code you want to add to the .setUp() function in your unit file (this function is executed before each test.
codeTearDown	An expression with some code you want to add to the .tearDown() function in your unit file (this function is executed after each test.
tag	A tag is a character string identifying a location in source code files (either a test unit file, or the original source code of the tested objects defined in objfile =. This character string will be searched by the text editor for easy location of the

cursor near the corresponding test command, or near the location in the original object that is concerned by this test. Use any string you want to uniquely identify your tag, both in your files, and in this argument.

`msg` A message you want to associate with this test run.

Value

A 'svTest' object for `svTest()`, `as.svTest()` and `test()`. Function `is.svTest()` returns TRUE if 'x' is a 'svTest' object, and `is.test()` does the same but also looks in the 'test' attribute if the class of 'x' is not 'svTest' and returns TRUE if it finds something there.

`makeUnit()` takes an object, extract its test function and write it in a sourceable test unit on the disk (it should be compatible with 'RUnit' test unit files too).

`runTest()` returns invisibly a 'svTestData' object with all results after running specified tests.

Author(s)

Philippe Grosjean

See Also

`svSuite()`, `is.svTestData()`, `Log()`, `checkEquals()`

Examples

```
clearLog()    # Clear the log file

foo <- function(x, y = 2)
  return(x * y)
is.test(foo)   # No
# Create test cases for this function
test(foo) <- function() {
  checkEqualsNumeric(4, foo(2))
  checkEqualsNumeric(6, foo(2, 3))
  checkTrue(is.test(foo))
  checkTrue(is.test(test(foo)))
  checkIdentical(attr(foo, "test"), test(foo))
  checkException(foo(2, "aa"))
  checkException(foo("bb"))
}
is.test(foo)   # Yes

## Not run:
# Create a test unit on disk and view it
unit <- makeUnit(foo)
file.show(unit, delete.file = TRUE)

## End(Not run)

# Run the test
(runTest(foo))
# Same as...
```

```

bar <- test(foo)
(runTest(bar))

# How fast can we run 100 times such kind of tests (700 test in total)?
# (just an indication because in real situation with test unit files, we
# have also the time required to source the units!)
system.time(for (i in 1:100) runTest(foo))[3]

is.svTest(test(foo))    # Yes, of course!
# When an object without associated test is passed to runTest(),
# a simple test containing only a DEACTIVATED entry is build
x <- 1:10
summary(runTest(x))

summary(Log())

rm(foo, bar, x)

```

svSuite

Create and run test suites by collecting together unit tests and function tests defined in objects

Description

A 'svSuite' object is essentially a list of test units directories (or packages, in this case, corresponding directories are PKG/unitTests and its subdirectories), and of object names containing tests to add temporarily to the test suite. These must be formatted in a concise way as described for the 'tests' argument.

Usage

```

svSuite(tests)

as.svSuite(x)

is.svSuite(x)

## S3 method for class 'svSuite'
print(x, ...)

svSuiteList(
  packages = TRUE,
  objects = TRUE,
  dirs = getOption("svUnit.dirs"),
  excludeList = getOption("svUnit.excludeList"),
  pos = .GlobalEnv,
  loadPackages = FALSE
)

```

```
## S3 method for class 'svSuite'
makeUnit(
  x,
  name = make.names(deparse(substitute(x))),
  dir = tempdir(),
  objfile = "",
  codeSetUp = NULL,
  codeTearDown = NULL,
  pos = .GlobalEnv,
  ...
)

## S3 method for class 'svSuite'
runTest(x, name = make.names(deparse(substitute(x))), unitname = NULL, ...)
```

Arguments

tests	A character string with items to include in the test suite. It could be 'package:PKG' for including test units located in the /unitTests subdirectory of the package PKG, or 'package:PKG (SUITE)' for test units located in the subdirectory /unitTests/SUITE of package PKG, or 'dir:MYDIR' for including test units in MYDIR, or 'test(OBJ)' for tests embedded in an object, or 'OBJ' for 'svTest' object directly.
x	Any kind of object.
...	Further arguments to pass to <code>makeUnit()</code> or <code>runTest()</code> (not used yet).
packages	Do we list test units available in loaded packages? Alternatively one can provide a character vector of package names, and it will be used to filter packages (take care: in this case it will look at installed packages, not only loaded packages)!
objects	Do we list test available in objects? Alternatively, one can provide a character vector of object names, and it will filter objects in 'pos' according to this vector.
dirs	An additional list of directories where to look for more test units. For convenience, this list can simply be saved as an 'svUnit.dirs' options.
excludeList	A list of items to exclude from the listing. The function uses regular expression to match the exclusions. So, for instance, specifying "package:MYPKG" will exclude all items from package 'MYPKG', while using "package:MYPKG\$" will exclude only tests suites defined in the ../MYPKG/unitTests directory, but not in its subdirectories. For convenience, it can be saved in a 'svUnit.excludeList' option. By default, all tests for packages whose name start with 'sv' or 'RUnit' are excluded, that is, <code>c("package:sv", "package:RUnit")</code> .
pos	The environment to look for 'objects' (environment, character string with name of an environment, or integer with position of the environment in the search path.
loadPackages	In the case a list of packages is provided in <code>packages =</code> , do we make sure that these packages are loaded? If yes, the function will try to load all packages in that list that are not loaded yet and will issue a warning for the packages not found. Default, FALSE.

name	The name of the test suite to build.
dir	The directory where to create the test unit file.
objfile	The path to the file containing the original source code of the object being tested. This argument is used to bring a context for a test and allow a GUI to automatically open the source file for edition when the user clicks on a test that failed or raised an error.
codeSetUp	An expression with some code you want to add to the <code>.setUp()</code> function in your unit file (this function is executed before each test).
codeTearDown	An expression with some code you want to add to the <code>.tearDown()</code> function in your unit file (this function is executed after each test).
unitname	The name of a unit to run inside the suite. If NULL (by default), all units are run.

Details

`svSuiteList()` lists all loaded packages having `/unitTests/runit*.R` files (or similar files in subdirectories), and all objects in the user workspace that have a `'test'` attribute, or are `'svTest'` objects (by default). It is a rather exhaustive list of all test items currently available in the current R session, but restricted by `getOption("svUnit.excludeList")`.

`makeUnit()` writes a test unit on disk with the tests from the objects listed in the `'svSuite'` object that do not belong yet to a test unit. `runTest()` runs all the test in packages, directories and objects listed in the `'svSuite'` object.

Thanks to the variety of sources allowed for tests, it is possible to define these tests in a structured way, inside packages, like for the `'RUnit'` package (but with automatic recognition of test units associated to packages, in the present case). It is also easy to define tests more loosely by just attaching those tests to the objects you want to check. Whenever there objects are loaded in the user's workspace, their tests are available. In both cases, a test unit file on disk is sourced in a local environment and test functions are run (same approach as in the `'RUnit'` package, and the same test unit files should be compatibles with both `'RUnit'` and `'svUnit'` packages), but in the case of a loosely definition of the tests by attachment to objects, the test unit file is created on the fly in the temporary directory (by default).

At any time, you can transform a series of tests loosely attached to objects into a test unit file by applying `makeUnit()` to a `'svSuite'` object, probably specifying another directory than the (default) temporary dir for more permanent storage of your test unit file. The best choice is the `'/inst/unitTests'` directory of a package source, or one of its subdirectories. That way, your test unit file(s) will be automatically listed and available each time you load the compiled package in R (if you list them using `svSuiteList()`). Of course, you still can exclude tests from given packages by adding `'package:PKG'` in the exclusion list with something like: `options(svUnit.excludeList = c(getOption("svUnit.excludeList"), "package:PKG"))`.

Value

`svSuite()`, `as.svSuite()` and `svSuiteList()` return a `'svSuite'` object. `is.svSuite()` returns TRUE if the object is an `'svSuite'`.

`makeUnit()` creates a test unit file on disk, and `runTest()` runs the tests in such a file. They are used for their side-effect, but the first one also returns the file created, and the second one returns invisibly the list of all test unit files that where sourced and run.

Author(s)

Philippe Grosjean

See Also

[svSuiteData\(\)](#), [svTest\(\)](#), [Log\(\)](#), [checkEquals\(\)](#), [RUnit::checkEquals\(\)](#)

Examples

```
svSuiteList() # List all currently available test units and test cases
# Exclusion list is used (regular expression filtering!). It contains:
(oex <- getOption("svUnit.excludeList"))
# Clear it, and relist available test units
options(svUnit.excludeList = NULL)
svSuiteList()

# Two functions that include their test cases
Square <- function(x)
  return(x^2)
test(Square) <- function() {
  checkEquals(9, Square(3))
  checkEquals(c(1, 4, 9), Square(1:3))
  checkException(Square("xx"))
}

Cube <- function(x)
  return(x^3)
test(Cube) <- function() {
  checkEquals(27, Cube(3))
  checkEquals(c(1, 8, 27), Cube(1:3))
  checkException(Cube("xx"))
}

# A separate test case object (not attached to a particular object)
# This is the simplest way to define quick and dirty integration tests
test_Integrate <- svTest(function() {
  checkTrue(1 < 2, "check1")
  v <- 1:3 # The reference
  w <- 1:3 # The value to compare to the reference
  checkEquals(v, w)
})

# A function without test cases (will be filtered out of the suite list)
foo <- function(x)
  return(x)

# Look now which tests are available
svSuiteList()

# Only objects, no package units
svSuiteList(packages = FALSE)
```

```
## Not run:
# Create the test unit file for all objects with tests in .GlobalEnv
myunit <- makeUnit(svSuiteList(), name = "AllTests")
file.show(myunit, delete.file = TRUE)

## End(Not run)

# Filter objects using a list (object with/without tests and a nonexisting obj)
svSuiteList(packages = FALSE, objects = c("Cube", "foo", "bar"))

# Create another svSuite object with selected test items
(mysuite <- svSuite(c("package:svUnit (VirtualClass)", "test(Cube)")))
is.svSuite(mysuite) # Should be!

## Not run:
# Run all the tests currently available
(runTest(svSuiteList(), name = "AllTests"))
summary(Log())

## End(Not run)

# Restore previous exclusion list, and clean up the environment
options(svUnit.excludeList = oex)
rm(Square, Cube, foo, test_Integrate, mysuite, myunit, oex)
```

svSuiteData

Objects of class 'svSuiteData' contain results from running test suites

Description

The 'svSuiteData' object contains results of all test run in one or more test suites. The `checkxxx()` functions and the `runTest()` method generate data (objects 'svTestData') contained in the default 'svSuiteData' named `.Log` and located in `.GlobalEnv`. It is then possible to display and report information it contains in various ways to analyze the results.

Usage

```
is.svSuiteData(x)

## S3 method for class 'svSuiteData'
stats(object, ...)

metadata(object, ...)

## S3 method for class 'svSuiteData'
metadata(
  object,
  fields = c("R.version", "sessionInfo", "time", "description"),
  ...
```



```

)

## S3 method for class 'svSuiteData'
print(x, all = FALSE, file = "", append = FALSE, ...)

## S3 method for class 'svSuiteData'
summary(object, ...)

protocol(object, type = "text", file = "", append = FALSE, ...)

## Default S3 method:
protocol(object, type = "text", file = "", append = FALSE, ...)

## S3 method for class 'svSuiteData'
protocol(object, type = "text", file = "", append = FALSE, ...)

protocol_text(object, file = "", append = FALSE, ...)

## S3 method for class 'svSuiteData'
protocol_text(object, file = "", append = FALSE, ...)

protocol_junit(object, ...)

## S3 method for class 'svSuiteData'
protocol_junit(object, file = "", append = FALSE, ...)

```

Arguments

x	Any kind of object, or a 'svSuiteData' object in the case of <code>print()</code> .
object	A 'svSuiteData' object.
...	Further arguments to pass to methods. Not used yet.
fields	Character vector. The name of all metadata items you want to extract for the object. The default value is an exhaustive list of all available metadata (i.e., defined by default) in the object, but you can add more: just add a corresponding attribute to your object.
all	Do we print concise report for all test, or only for the tests that fail or produce an error?
file	Character. The path to the file where to write the report. If <code>file = ""</code> , the protocol report is output to the console.
append	Do we append to this file?
type	Character. The type of protocol report to create. For the moment, only <code>type = "text"</code> and <code>type = "junit"</code> are supported, but further types (HTML, LaTeX, Wiki, etc.) could be provided later.

Details

A 'svSuiteData' is, indeed, an environment. The results for the various tests runs are in non hidden (i.e., names not starting with a dot) objects that are of class 'svTestData' in this environment. Var-

ious other objects that control the execution of the test, their context, etc. are contained as hidden objects with name starting with a dot. Note that using an environment instead of a list for this object allows for a call by reference instead of a usual call by value in R, when passing this object to a function. This property is largely exploited in all svUnit functions to make sure results of test runs are centralized in the same log ('svSuiteData' object).

Value

`is.svSuiteData()` returns TRUE if the object is an 'svSuiteData'. The various methods serve to extract or print content in the object.

Author(s)

Philippe Grosjean; Mario Frasca for the junit protocol.

See Also

`svSuite()`, `is.svTestData()`, `Log()`, `checkEquals()`

Examples

```
clearLog()    # Clear any existing log

# Run some tests
checkTrue(1 < 2)
checkException(log("a"))
foo <- function(x, y = 2)
  return(x * y)
test(foo) <- function() {
  checkEqualsNumeric(4, foo(2))
  checkEqualsNumeric(6, foo(2, nonexisting))
  checkTrue(is.test(foo))
  warning("This is a warning")
  cat("Youhou from test!\n") # Don't use, except for debugging!
  checkTrue(is.test(test(foo)))
  checkIdentical(attr(foo, "test"), test(foo))
  checkException(foo(2, nonexisting))
  #DEACTIVATED("My deactivation message")
  checkException(foo(2)) # This test fails
}
runTest(foo)

# Now inspect the log, which is a 'svSuiteData' object
is.svSuiteData(Log())
stats(Log())
metadata(Log())
Log()    # Print method
summary(Log())

## Not run:
# To get a print of the test protocol on file, use:
protocol(Log(), type = "text", file = "RprofProtocol.out")
```

```

file.show("RprofProtocol.out")
unlink("RprofProtocol.out")

## End(Not run)

rm(foo)

## Not run:
# Profiling of very simple test runs
library(utils)
createLog(description = "test profiling", deleteExisting = TRUE)
imax <- 3
jmax <- 100
l <- 50
Rprof()
for (i in 1:imax) {
  # Change the context for these tests
  .Log$..Test <- paste("Test", i, sep = "")
  .Log$..Tag <- paste("#", i, sep = "")
  res <- system.time({
    for (j in 1:jmax) checkTrue(i <= j, "My test")
  }, gcFirst = TRUE)[3]
  print(res)
  flush.console()
}
Rprof(NULL)
# Look at profile
summaryRprof()
unlink("Rprof.out")

# Look at the log
summary(Log())

## End(Not run)

```

svTestData

Objects of class 'svTestData' contain results from running a test

Description

The 'svTestData' contains results of test run. The checkxxx() functions and the runTest() method generate one such object which is located in the .Log object in .GlobalEnv. It is then possible to display and report information it contains in various ways to analyze the results.

Usage

```
is.svTestData(x)
```

```
stats(object, ...)
```

```
## S3 method for class 'svTestData'
stats(object, ...)

## S3 method for class 'svTestData'
print(x, all = FALSE, header = TRUE, file = "", append = FALSE, ...)

## S3 method for class 'svTestData'
summary(object, header = TRUE, file = "", append = FALSE, ...)

## S3 method for class 'svTestData'
protocol_junit(object, ...)
```

Arguments

x	Any kind of object, or a 'svTestData' object in the case of print() .
object	A 'svTestData' object.
...	Further arguments to pass to methods. Not used yet.
all	Do we print concise report for all test, or only for the tests that fail or produce an error?
header	Do we print a header or not?
file	Character. The path to the file where to write the report. If file = "", the report is output to the console.
append	Do we append to this file?

Value

[is.svTestData\(\)](#) returns TRUE if the object is an 'svTestData'. The various methods serve to extract or print content in the object.

Author(s)

Philippe Grosjean

See Also

[svTest\(\)](#), [is.svSuiteData\(\)](#), [Log\(\)](#), [checkEquals\(\)](#)

Examples

```
foo <- function(x, y = 2)
  return(x * y)
is.test(foo) # No
# Create test cases for this function
test(foo) <- function() {
  checkEqualsNumeric(4, foo(2))
  checkEqualsNumeric(5, foo(2, 3))
  checkEqualsNumeric(5, foo(nonexists))
}
# Generate a 'svTestData' object by running the test
```

```
obj <- runTest(foo) # Equivalent to runTest(test(foo)), but shorter
obj
summary(obj)
stats(obj)
is.svTestData(obj)

rm(foo, obj)
```

`unitTests.svUnit`*Unit tests for the package 'svUnit'*

Description

Performs unit tests defined in this package by running `example(unitTests.svUnit)`. Tests are in `runit*.R` files located in the `'/unitTests'` subdirectory or one of its subdirectories (`'/inst/unitTests'` and subdirectories in package sources).

Author(s)

Philippe Grosjean

Examples

```
if (require(svUnit)) {
  clearLog()
  runTest(svSuite("package:svUnit"), "svUnit")

  # Tests to run with example() but not with R CMD check
  runTest(svSuite("package:svUnit (VirtualClass)"), "VirtualClass")

  ## Not run:
  # Tests to present in ?unitTests.svUnit but not run automatically
  # Run all currently loaded packages test cases and test suites
  runTest(svSuiteList(), "AllTests")

  ## End(Not run)

  # Check errors at the end (needed to interrupt R CMD check)
  errorLog()
}
```

Index

- * **unit testing**
 - check, [2](#)
 - guiTestReport, [4](#)
 - koUnit, [5](#)
 - Log, [7](#)
 - makeTestListFromExamples, [8](#)
 - svSuite, [12](#)
 - svSuiteData, [16](#)
 - svTestData, [19](#)
- * **utilities**
 - check, [2](#)
 - guiTestReport, [4](#)
 - koUnit, [5](#)
 - Log, [7](#)
 - makeTestListFromExamples, [8](#)
 - svSuite, [12](#)
 - svSuiteData, [16](#)
 - svTestData, [19](#)
 - unitTests.svUnit, [21](#)
- all.equal(), [3](#)
- all.equal.numeric(), [3](#)
- as.svSuite (svSuite), [12](#)
- as.svSuite(), [14](#)
- as.svTest (makeTestListFromExamples), [8](#)
- as.svTest(), [11](#)
- check, [2](#)
- checkEquals (check), [2](#)
- checkEquals(), [8](#), [11](#), [15](#), [18](#), [20](#)
- checkEqualsNumeric (check), [2](#)
- checkException (check), [2](#)
- checkException(), [3](#)
- checkIdentical (check), [2](#)
- checkTrue (check), [2](#)
- checkTrue(), [3](#)
- clearLog (Log), [7](#)
- clearLog(), [8](#)
- createLog (Log), [7](#)
- createLog(), [8](#)
- DEACTIVATED (check), [2](#)
- errorLog (Log), [7](#)
- errorLog(), [8](#)
- guiSuiteAutoList (guiTestReport), [4](#)
- guiSuiteAutoList(), [5](#)
- guiSuiteList (guiTestReport), [4](#)
- guiSuiteList(), [5](#)
- guiTestFeedback (guiTestReport), [4](#)
- guiTestReport, [4](#)
- guiTestReport(), [3](#), [6](#)
- is.svSuite (svSuite), [12](#)
- is.svSuite(), [14](#)
- is.svSuiteData (svSuiteData), [16](#)
- is.svSuiteData(), [18](#), [20](#)
- is.svTest (makeTestListFromExamples), [8](#)
- is.svTest(), [11](#)
- is.svTestData (svTestData), [19](#)
- is.svTestData(), [11](#), [18](#), [20](#)
- is.test (makeTestListFromExamples), [8](#)
- koUnit, [5](#)
- koUnit_isAutoTest (koUnit), [5](#)
- koUnit_isAutoTest(), [6](#)
- koUnit_runTest (koUnit), [5](#)
- koUnit_runTest(), [5](#)
- koUnit_setAutoTest (koUnit), [5](#)
- koUnit_showRUnitPane (koUnit), [5](#)
- koUnit_version (koUnit), [5](#)
- koUnit_version(), [5](#), [6](#)
- lastSuite (Log), [7](#)
- lastSuite(), [8](#)
- lastTest (Log), [7](#)
- lastTest(), [8](#)
- Log, [7](#)
- Log(), [3](#), [7](#), [8](#), [11](#), [15](#), [18](#), [20](#)
- makeTestListFromExamples, [8](#)

makeUnit (makeTestListFromExamples), 8
makeUnit(), 8, 11, 13, 14
makeUnit.svSuite (svSuite), 12
metadata (svSuiteData), 16

print(), 17, 20
print.svSuite (svSuite), 12
print.svSuiteData (svSuiteData), 16
print.svTest
 (makeTestListFromExamples), 8
print.svTestData (svTestData), 19
protocol (svSuiteData), 16
protocol_junit (svSuiteData), 16
protocol_junit.svTestData (svTestData),
 19
protocol_text (svSuiteData), 16

RUnit::checkEquals(), 15
RUnit::checkTrue, 3
RUnit::checkTrue(), 3
runTest (makeTestListFromExamples), 8
runTest(), 11, 13, 14, 16
runTest.svSuite (svSuite), 12

stats (svTestData), 19
stats.svSuiteData (svSuiteData), 16
stop(), 7
summary.svSuiteData (svSuiteData), 16
summary.svTestData (svTestData), 19
svSuite, 12
svSuite(), 5, 8, 11, 14, 18
svSuiteData, 16
svSuiteData(), 8, 15
svSuiteList (svSuite), 12
svSuiteList(), 14
svTest (makeTestListFromExamples), 8
svTest(), 3, 5, 8, 11, 15, 20
svTestData, 19

test (makeTestListFromExamples), 8
test(), 11
test<- (makeTestListFromExamples), 8

unitTests.svUnit, 21