

Package ‘textrar’

July 22, 2025

Title Interface to 'TexTra' from R
Version 0.8.0
Description A wrapper for the 'TexTra' API <<https://mt-auto-minhon-mlt.ucri.jgn-x.jp/>>, a web service for translating texts between different languages. 'TexTra' API account is required to use the service.
License MIT + file LICENSE
Encoding UTF-8
RoxygenNote 7.3.1
URL <https://github.com/matutosi/textrar>
Imports jsonlite, http
Suggests knitr, rmarkdown, spelling
Language en-US
Depends R (>= 2.10)
NeedsCompilation no
Author Toshikazu Matsumura [aut, cre] (ORCID: <<https://orcid.org/0000-0003-2306-6355>>)
Maintainer Toshikazu Matsumura <matutosi@gmail.com>
Repository CRAN
Date/Publication 2024-04-23 11:50:03 UTC

Contents

base_url	2
extract_result	2
gen_params	3
get_token	3
post_request	4
textra	5
Index	6

base_url	<i>Return the base URL for the API</i>
----------	--

Description

Return the base URL for the API

Usage

```
base_url()
```

Value

A string containing the base URL.

Examples

```
base_url()
```

extract_result	<i>Extract Translated Text from Response</i>
----------------	--

Description

This function extracts the translated text from the response. returned by the `post_request()` function.

Usage

```
extract_result(res)
```

Arguments

res	The response object returned by the <code>post_request()</code> .
-----	---

Value

A character string containing the translated text.

Examples

```
## Not run:  
res <- post_request(params, "Hello world!")  
translated <- extract_result(res)  
  
## End(Not run)
```

gen_params	<i>Generate parameters for API call</i>
------------	---

Description

This function generates a list of parameters that can be used to make an API call.

Usage

```
gen_params(key, secret, name, api_name = "mt")
```

Arguments

key	The API key.
secret	The API secret.
name	The name of the API.
api_name	The name of the API to use. Defaults to "mt".

Value

A list of parameters.

Examples

```
## Not run:
key <- "abcdefghijklmnopqrstuvwxyz01234567890abcdef1" # API key
secret <- "xyzabcdefghijklmnopqrstuvwxyz012345" # API secret
name <- "login_ID" # login_ID
params <- gen_params(key = key, secret = secret, name = name)

## End(Not run)
```

get_token	<i>Get Access Token</i>
-----------	-------------------------

Description

This function retrieves an access token from the API using the provided key and secret.

Usage

```
get_token(key, secret)
```

Arguments

key	The API key.
secret	The API secret.

Value

A character string containing the access token.

Examples

```
## Not run:
key <- "abcdefghijklmnopqrstuvw01234567890abcdef1" # API key
secret <- "xyzabcdefghijklmnopqrstuvw012345" # API secret
token <- get_token(key = key, secret = secret)

## End(Not run)
```

post_request	<i>Send a POST request to the API</i>
--------------	---------------------------------------

Description

This function sends a POST request to the API with the specified parameters and text.

Usage

```
post_request(params, text)
```

Arguments

params	A list of parameters to be passed to the API.
text	The text to be translated.

Value

The response from the API.

Examples

```
## Not run:
post_request(params = , text = "Hello, world!")

## End(Not run)
```

textra

Translate text using Transliteration Model

Description

This function translates text using a transliteration model.

Usage

```
textra(text, params, model = "transLM", from = "en", to = "ja")
```

Arguments

text	The text to be translated.
params	A list of parameters to be passed to the API.
model	The model to be used for translation.
from	The source language.
to	The target language.

Value

The translated text.

Examples

```
## Not run:
text <- "Hello world"
key <- "abcdefghijklmnopqrstuvwxyz01234567890abcdef1" # API key
secret <- "abcdefghijklmnopqrstuvwxyz012345" # API secret
name <- "login_ID" # login_ID
params <- gen_params(key = key, secret = secret, name = name)
translated <-
  textra(text, params, model = "transLM", from = "en", to = "ja")
translated

## End(Not run)
```

Index

base_url, [2](#)

extract_result, [2](#)

gen_params, [3](#)

get_token, [3](#)

post_request, [4](#)

textra, [5](#)