

Package ‘theft’

July 22, 2025

Type Package

Title Tools for Handling Extraction of Features from Time Series

Version 0.8.1

Date 2025-07-10

Maintainer Trent Henderson <then6675@uni.sydney.edu.au>

Description Consolidates and calculates different sets of time-series features from multiple 'R' and 'Python' packages including 'Rcatch22' Henderson, T. (2021) <[doi:10.5281/zenodo.5546815](https://doi.org/10.5281/zenodo.5546815)>, 'feasts' O'Hara-Wild, M., Hyndman, R., and Wang, E. (2021) <<https://CRAN.R-project.org/package=feasts>>, 'tsfeatures' Hyndman, R., Kang, Y., Montero-Manso, P., Talagala, T., Wang, E., Yang, Y., and O'Hara-Wild, M. (2020) <<https://CRAN.R-project.org/package=tsfeatures>>, 'tsfresh' Christ, M., Braun, N., Neuffer, J., and Kempa-Liehr A.W. (2018) <[doi:10.1016/j.neucom.2018.03.067](https://doi.org/10.1016/j.neucom.2018.03.067)>, 'TSFEL' Barandas, M., et al. (2020) <[doi:10.1016/j.softx.2020.100456](https://doi.org/10.1016/j.softx.2020.100456)>, and 'Kats' Facebook Infrastructure Data Science (2021) <<https://facebookresearch.github.io/Kats/>>.

BugReports <https://github.com/hendersontrent/theft/issues>

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Depends R (>= 3.5.0)

Imports utils, stats, rlang, dplyr, tidyr, purrr, tsibble, fabletools, feasts, tsfeatures, Rcatch22, reticulate, R.matlab

Suggests lifecycle, cachem, bslib, knitr, rmarkdown, pkgdown, testthat

RoxygenNote 7.3.2

VignetteBuilder knitr

URL <https://hendersontrent.github.io/theft/>

NeedsCompilation no

Author Trent Henderson [cre, aut],
Annie Bryant [ctb]
Repository CRAN
Date/Publication 2025-07-10 07:10:02 UTC

Contents

calculate_features	2
check_vector_quality	3
feature_list	4
init_theft	4
install_kats	5
install_python_pkgs	6
install_tsfel	6
install_tsfresh	7
process_hctsa_file	8
simData	8
theft	9
Index	10

calculate_features	<i>Compute features on an input time series dataset</i>
--------------------	---

Description

Compute features on an input time series dataset

Usage

```
calculate_features(  
  data,  
  feature_set = c("catch22", "feasts", "tsfeatures", "kats", "tsfresh", "tsfel"),  
  features = NULL,  
  catch24 = FALSE,  
  tsfresh_cleanup = FALSE,  
  use_compengine = FALSE,  
  seed = 123  
)
```

Arguments

data	tbl_ts containing the time series data
feature_set	character or vector of character denoting the set of time-series features to calculate. Can be one of "catch22", "feasts", "tsfeatures", "tsfresh", "tsfel", or "kats"

features	named list containing a set of user-supplied functions to calculate on data. Each function should take a single argument which is the time series. Defaults to NULL for no manually-specified features. Each list entry must have a name as calculate_features looks for these to name the features. If you don't want to use the existing feature sets and only compute those passed to features, set feature_set = NULL
catch24	Boolean specifying whether to compute catch24 in addition to catch22 if catch22 is one of the feature sets selected. Defaults to FALSE
tsfresh_cleanup	Boolean specifying whether to use the in-built tsfresh relevant feature filter or not. Defaults to FALSE
use_compengine	Boolean specifying whether to use the "compengine" features in tsfeatures. Defaults to FALSE to provide immense computational efficiency benefits
seed	integer denoting a fixed number for R's random number generator to ensure reproducibility. Defaults to 123

Value

object of class feature_calculations that contains the summary statistics for each feature

Author(s)

Trent Henderson

Examples

```
featMat <- calculate_features(data = simData,
  feature_set = "catch22")
```

check_vector_quality *Check for presence of NAs and non-numerics in a vector*

Description

Check for presence of NAs and non-numerics in a vector

Usage

```
check_vector_quality(x)
```

Arguments

x input vector

Value

Boolean of whether the data is good to extract features on or not

Author(s)

Trent Henderson

feature_list	<i>All features available in theft in tidy format</i>
--------------	---

Description

The variables include:

Usage

feature_list

Format

A tidy data frame with 2 variables:

feature_set Name of the set the feature is from**feature** Name of the feature

init_theft	<i>Communicate to R the Python virtual environment containing the relevant libraries for calculating features</i>
------------	---

Description

Communicate to R the Python virtual environment containing the relevant libraries for calculating features

Usage

init_theft(venv)

Arguments

venv	character specifying the name of the to the Python virtual environment where "tsfresh", "TSFEL", and/or "Kats" are installed
------	--

Value

no return value; called for side effects

Author(s)

Trent Henderson

Examples

```
## Not run:
install_python_pkgs("theft-test")
init_theft("theft-test")

## End(Not run)
```

install_kats

Download and install Kats from Python into a new virtual environment

Description

Download and install Kats from Python into a new virtual environment

Usage

```
install_kats(venv, python)
```

Arguments

venv	character specifying the name of the new virtual environment to create
python	character specifying the filepath to the Python interpreter to use. Python 3.10 is recommended

Value

no return value; called for side effects

Author(s)

Trent Henderson

Examples

```
## Not run:
install_kats("theft-test", "/usr/local/bin/python3.10")

## End(Not run)
```

install_python_pkgs	<i>Download and install tsfresh, TSFEL, and Kats from Python into a new virtual environment</i>
---------------------	---

Description

Download and install tsfresh, TSFEL, and Kats from Python into a new virtual environment

Usage

```
install_python_pkgs(venv, python)
```

Arguments

venv	character specifying the name of the new virtual environment to create
python	character specifying the filepath to the Python interpreter to use. Python 3.10 is recommended

Value

no return value; called for side effects

Author(s)

Trent Henderson

Examples

```
## Not run:  
install_python_pkgs("theft-test", "/usr/local/bin/python3.10")  
  
## End(Not run)
```

install_tsfel	<i>Download and install TSFEL from Python into a new virtual environment</i>
---------------	--

Description

Download and install TSFEL from Python into a new virtual environment

Usage

```
install_tsfel(venv, python)
```

Arguments

venv	character specifying the name of the new virtual environment to create
python	character specifying the filepath to the Python interpreter to use. Python 3.10 is recommended

Value

no return value; called for side effects

Author(s)

Trent Henderson

Examples

```
## Not run:  
install_tsfresh("theft-test", "/usr/local/bin/python3.10")  
  
## End(Not run)
```

install_tsfresh	<i>Download and install tsfresh from Python into a new virtual environment</i>
-----------------	--

Description

Download and install tsfresh from Python into a new virtual environment

Usage

```
install_tsfresh(venv, python)
```

Arguments

venv	character specifying the name of the new virtual environment to create
python	character specifying the filepath to the Python interpreter to use. Python 3.10 is recommended

Value

no return value; called for side effects

Author(s)

Trent Henderson

Examples

```
## Not run:
install_tsfresh("theft-test", "/usr/local/bin/python3.10")

## End(Not run)
```

process_hctsa_file	<i>Load in hctsa formatted MATLAB files of time series data into a tidy format ready for feature extraction</i>
--------------------	---

Description

Load in hctsa formatted MATLAB files of time series data into a tidy format ready for feature extraction

Usage

```
process_hctsa_file(data)
```

Arguments

data	string specifying the filepath to the MATLAB file to parse
------	--

Value

an object of class `data.frame` in tidy format

Author(s)

Trent Henderson

simData	<i>Sample of randomly-generated time series to produce function tests and vignettes</i>
---------	---

Description

The variables include:

Usage

```
simData
```


Format

- A tidy tsibble with 4 variables:
- id** Unique identifier for the time series
- timepoint** Time index
- values** Value
- process** Group label for the type of time series

theft	<i>Tools for Handling Extraction of Features from Time-series</i>
-------	---

Description

Tools for Handling Extraction of Features from Time-series

Index

* **datasets**

feature_list, [4](#)

simData, [8](#)

calculate_features, [2](#)

check_vector_quality, [3](#)

feature_list, [4](#)

init_theft, [4](#)

install_kats, [5](#)

install_python_pkgs, [6](#)

install_tsfel, [6](#)

install_tsfresh, [7](#)

process_hctsa_file, [8](#)

simData, [8](#)

theft, [9](#)