

Package ‘tidytree’

July 22, 2025

Title A Tidy Tool for Phylogenetic Tree Data Manipulation

Version 0.4.6

Description Phylogenetic tree generally contains multiple components including node, edge, branch and associated data. 'tidytree' provides an approach to convert tree object to tidy data frame as well as provides tidy interfaces to manipulate tree data.

Depends R (>= 3.4.0)

Imports ape, dplyr, lazyeval, magrittr, methods, rlang, tibble, tidyr, tidyselect, yulab.utils (>= 0.0.4), pillar, cli

Suggests knitr, rmarkdown, prettydoc, testthat, utils

VignetteBuilder knitr

ByteCompile true

License Artistic-2.0

URL <https://www.amazon.com/Integration-Manipulation-Visualization-Phylogenetic-Computational-ebook/dp/B0B5NLZR1Z/>

BugReports <https://github.com/YuLab-SMU/tidytree/issues>

Encoding UTF-8

RoxygenNote 7.2.3

NeedsCompilation no

Author Guangchuang Yu [aut, cre, cph] (ORCID: <https://orcid.org/0000-0002-6485-8781>),
Bradley Jones [ctb],
Zebulun Arendsee [ctb]

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Repository CRAN

Date/Publication 2023-12-12 11:40:02 UTC

Contents

ancestor	2
as.treedata	3
as.ultrametric	4
child	4
drop.tip	5
get.data	6
get.fields	7
get.treetext	7
getNodeNum	8
get_tree_data	9
groupClade	9
groupOTU	10
isTip	10
MRCA	11
Nnode.treedata	12
node.label	12
nodeid	13
nodelab	13
offspring	14
parent	15
root.treedata	15
rootnode	16
show	17
sibling	17
td-label-assign	18
tip.label	18
treedata	19
treedata-class	19
tree_subset	20
Index	22

ancestor	<i>ancestor</i>
----------	-----------------

Description

access ancestor data

Usage

```
ancestor(.data, .node, ...)

## S3 method for class 'tbl_tree'
ancestor(.data, .node, ...)
```

Arguments

.data	phylo or tbl_tree object
.node	node number
...	additional parameters

Value

ancestor data

Author(s)

Guangchuang Yu

Examples

```
library(ape)
tree <- rtree(4)
x <- as_tibble(tree)
ancestor(x, 3)
```

as.treedata

as.treedata

Description

convert a tree object to treedata object

Usage

```
as.treedata(tree, ...)
```

```
## S3 method for class 'tbl_tree'
as.treedata(tree, ...)
```

Arguments

tree	tree object
...	additional parameters

Value

treedata object

Examples

```
library(ape)
set.seed(2017)
tree <- rtree(4)
d <- tibble(label = paste0('t', 1:4),
            trait = rnorm(4))
x <- as_tibble(tree)
full_join(x, d, by = 'label') %>% as.treedata
```

as.ultrametric	<i>as.ultrametric</i>
----------------	-----------------------

Description

as.ultrametric

Usage

```
as.ultrametric(tree, ...)
```

Arguments

tree	tree object
...	additional parameters

Value

treedata or phylo object

child	<i>child</i>
-------	--------------

Description

access child data

Usage

```
child(.data, .node, ...)

## S3 method for class 'tbl_tree'
child(.data, .node, ...)
```

Arguments

.data	phylo or tbl_tree object
.node	node number
...	additional parameters

Value

child data

Author(s)

Guangchuang Yu

Examples

```
library(ape)
tree <- rtree(4)
x <- as_tibble(tree)
child(x, 4)
```

drop.tip

drop.tip method

Description

drop.tip method

Usage

```
drop.tip(object, tip, ...)

keep.tip(object, tip, ...)

## S4 method for signature 'treedata'
drop.tip(object, tip, ...)

## S4 method for signature 'phylo'
drop.tip(object, tip, ...)

## S4 method for signature 'treedata'
keep.tip(object, tip, ...)

## S4 method for signature 'phylo'
keep.tip(object, tip, ...)
```

Arguments

object	A treedata or phylo object
tip	a vector of mode numeric or character specifying the tips to delete
...	additional parameters

Value

updated object

Author(s)

Casey Dunn <http://dunnlab.org> and Guangchuang Yu <https://guangchuangyu.github.io>

Source

drop.tip for phylo object is a wrapper method of ape::drop.tip from the ape package. The documentation you should read for the drop.tip function can be found here: [drop.tip](#)

See Also

[drop.tip](#)

Examples

```
library(tidytree)
set.seed(123)
tr <- ape::rtree(6)
da <- data.frame(id=tip.label(tr), value = letters[seq_len(6)])
trda <- tr %>% dplyr::left_join(da, by = c('label'='id'))
tr1 <- drop.tip(tr, c("t2", "t1"))
tr2 <- keep.tip(tr, c("t2", "t1"))
```

get.data

get.data method

Description

get.data method

get.data method

Usage

```
get.data(object, ...)
```

```
## S4 method for signature 'treedata'
get.data(object)
```

Arguments

object	treedata object
...	additional parameter

Value

associated data of phylogeny

get.fields	<i>get.fields method</i>
------------	--------------------------

Description

get.fields method

Usage

```
get.fields(object, ...)
```

```
## S4 method for signature 'treedata'  
get.fields(object)
```

Arguments

object	treedata object
...	additional parameter

Value

available annotation variables

get.treetext	<i>get.treetext method</i>
--------------	----------------------------

Description

access tree text (newick text) from tree object

Usage

```
get.treetext(object, ...)
```

```
## S4 method for signature 'treedata'  
get.treetext(object)
```

Arguments

object	treedata object
...	additional parameter

Value

phylo object

getNodeNum	<i>getNodeNum</i>
------------	-------------------

Description

calculate total number of nodes

Usage

```
getNodeNum(tree)
```

Arguments

tree	tree object
------	-------------

Value

number

Author(s)

Guangchuang Yu

Examples

```
getNodeNum(rtree(30))
```

get_tree_data	<i>get_tree_data</i>
---------------	----------------------

Description

get associated data stored in treedata object

Usage

get_tree_data(tree_object)

Arguments

tree_object a treedata object

Value

tbl_df

Author(s)

guangchuang yu

groupClade	<i>groupClade</i>
------------	-------------------

Description

grouping clades

Usage

groupClade(.data, .node, group_name = "group", overlap = "overwrite", ...)

Arguments

.data tree object (phylo, treedata, tbl_tree, ggtree etc.)
.node selected nodes
group_name character the name of the group cluster, default is group.
overlap character one of overwrite,origin and abandon, default is overwrite.
... additional parameter

Value

updated tree with group information or group index

Author(s)

Guangchuang Yu

groupOTU	<i>groupOTU</i>
----------	-----------------

Description

grouping OTUs

Usage

```
groupOTU(.data, .node, group_name = "group", ...)
```

Arguments

.data	tree object (phylo, treedata, tbl_tree, ggtree etc.)
.node	selected nodes
group_name	character the name of the group cluster, default is group.
...	additional parameter

Value

updated tree with group information or group index

Author(s)

Guangchuang Yu

isTip	<i>isTip</i>
-------	--------------

Description

whether the node is a tip

Usage

```
isTip(.data, .node, ...)

## S3 method for class 'tbl_tree'
isTip(.data, .node, ...)

## S3 method for class 'phylo'
isTip(.data, .node, ...)

## S3 method for class 'treedata'
isTip(.data, .node, ...)
```

Arguments

.data phylo, treedata or tbl_tree object
.node node number
... additional parameters

Value

logical value

Author(s)

Guangchuang Yu

MRCA	<i>MRCA</i>
------	-------------

Description

access most recent common ancestor data

Usage

MRCA(.data, ...)

Arguments

.data phylo or tbl_tree object
... additional parameters

Value

MRCA data

Author(s)

Guangchuang Yu

<code>Nnode.treedata</code>	<i>Nnode</i>
-----------------------------	--------------

Description

number of nodes

Usage

```
## S3 method for class 'treedata'  
Nnode(phy, internal.only = TRUE, ...)
```

Arguments

<code>phy</code>	treedata object
<code>internal.only</code>	whether only count internal nodes
<code>...</code>	additional parameters

Value

number of nodes

Author(s)

Guangchuang Yu

Examples

```
Nnode(rtree(30))
```

<code>node.label</code>	<i>extract the node label of phylo, treedata or tbl_tree</i>
-------------------------	--

Description

extract the node label of phylo, treedata or tbl_tree

Usage

```
node.label(x, node = "internal", ...)
```

Arguments

<code>x</code>	object, should be one of treedata,phylo or tbl_tree.
<code>node</code>	character, to extract which type node label, default is internal, should be one of internal, external, all, tip.
<code>...</code>	additional parameters.

Value

label character vector.

nodeid	<i>nodeid</i>
--------	---------------

Description

convert tree label to internal node number

Usage

nodeid(tree, label)

Arguments

tree	tree object
label	tip/node label(s)

Value

node number

Author(s)

Guangchuang Yu

nodeid	<i>nodeid</i>
--------	---------------

Description

convert internal node number tip/node label

Usage

nodeid(tree, id)

Arguments

tree	tree object
id	node number

Value

tip/node label(s)

Author(s)

Guangchuang Yu

offspring*offspring*

Description

access offspring data

Usage

```
offspring(.data, .node, tiponly, self_include, ...)

## S3 method for class 'tbl_tree'
offspring(.data, .node, tiponly = FALSE, self_include = FALSE, ...)
```

Arguments

<code>.data</code>	phylo or <code>tbl_tree</code> object
<code>.node</code>	node number
<code>tiponly</code>	whether only return tip nodes
<code>self_include</code>	whether include the input node, only applicable for <code>tiponly = FALSE</code>
<code>...</code>	additional parameters

Value

offspring data

Author(s)

Guangchuang Yu

Examples

```
library(ape)
tree <- rtree(4)
x <- as_tibble(tree)
offspring(x, 4)
```

parent	<i>parent</i>
--------	---------------

Description

access parent data

Usage

```
parent(.data, .node, ...)  
  
## S3 method for class 'tbl_tree'  
parent(.data, .node, ...)
```

Arguments

.data	phylo or <code>tbl_tree</code> object
.node	node number
...	additional parameters

Value

parent data

Author(s)

Guangchuang Yu

Examples

```
library(ape)  
tree <- rtree(4)  
x <- as_tibble(tree)  
parent(x, 2)
```

root.treedata	<i>root</i>
---------------	-------------

Description

re-root a tree

Usage

```
## S3 method for class 'treedata'  
root(phy, outgroup, node = NULL, edgelabel = TRUE, ...)
```

Arguments

phy	tree object
outgroup	a vector of mode numeric or character specifying the new outgroup
node	node to reroot
edgelabel	a logical value specifying whether to treat node labels as edge labels and thus eventually switching them so that they are associated with the correct edges.
...	additional parameters passed to ape::root.phylo

Value

rerooted treedata

rootnode	<i>rootnode</i>
----------	-----------------

Description

access root node data

Usage

rootnode(.data, ...)

Arguments

.data	phylo or tbl_tree object
...	additional parameters

Value

root node data

Author(s)

Guangchuang Yu

show	<i>show method</i>
------	--------------------

Description

show method for treedata instance

Usage

```
show(object)
```

Arguments

object	treedata object
--------	-----------------

Value

print info

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

sibling	<i>sibling</i>
---------	----------------

Description

access sibling data

Usage

```
sibling(.data, ...)
```

Arguments

.data	phylo or tbl_tree object
...	additional parameters

Value

sibling

Author(s)

Guangchuang Yu

td-label-assign	<i>the tip or internal node label assign of tbl_tree phylo and treedata</i>
-----------------	---

Description

the tip or internal node label assign of tbl_tree phylo and treedata

Usage

```
tip.label(x) <- value

node.label(x) <- value

## S3 replacement method for class 'phylo'
node.label(x) <- value

## S3 replacement method for class 'treedata'
node.label(x) <- value

## S3 replacement method for class 'tbl_tree'
node.label(x) <- value

## S3 replacement method for class 'phylo'
tip.label(x) <- value

## S3 replacement method for class 'treedata'
tip.label(x) <- value

## S3 replacement method for class 'tbl_tree'
tip.label(x) <- value
```

Arguments

x	object, should be one of tbl_tree, phylo or treedata
value	character, the character vector

tip.label	<i>extract the tip label of phylo treedata or tbl_tree</i>
-----------	--

Description

extract the tip label of phylo treedata or tbl_tree

Usage

```
tip.label(x, ...)
```

Arguments

x object, should be one of treedata,phylo or tbl_tree.
... additional parameters.

treedata	<i>treedata</i>
----------	-----------------

Description

treedata object contructor

Usage

treedata(...)

Arguments

... parameters

Value

treedata object

Author(s)

guangchuang yu

treedata-class	<i>Class "treedata" This class stores phylogenetic tree with associated data</i>
----------------	--

Description

Class "treedata" This class stores phylogenetic tree with associated data

Slots

file tree file
treetext newick tree string
phylo phylo object for tree structure
data associated data
extraInfo extra information, reserve for merge_tree
tip_seq tip sequences
anc_seq ancestral sequences

seq_type sequence type, one of NT or AA
 tipseq_file tip sequence file
 ancseq_file ancestral sequence file
 info extra information, e.g. metadata, software version etc.

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

tree_subset	<i>Subset tree objects by related nodes</i>
-------------	---

Description

This function allows for a tree object to be subset by specifying a node and returns all related nodes within a selected number of levels

Usage

```
tree_subset(
  tree,
  node,
  levels_back = 5,
  group_node = TRUE,
  group_name = "group",
  root_edge = TRUE
)

## S3 method for class 'phylo'
tree_subset(
  tree,
  node,
  levels_back = 5,
  group_node = TRUE,
  group_name = "group",
  root_edge = TRUE
)

## S3 method for class 'treedata'
tree_subset(
  tree,
  node,
  levels_back = 5,
  group_node = TRUE,
  group_name = "group",
  root_edge = TRUE
)
```

Arguments

tree	a tree object of class phylo
node	either a tip label or a node number for the given tree that will be the focus of the subsetted tree
levels_back	a number specifying how many nodes back from the selected node the subsetted tree should include
group_node	whether add grouping information of selected node
group_name	group name (default 'group') for storing grouping information if group_node = TRUE
root_edge	If TRUE (by default), set root.edge to path length of original root to the root of subset tree

Details

This function will take a tree and a specified node from that tree and subset the tree showing all relatives back to a specified number of nodes. This function allows for a combination of ancestor and offspring to return a subsetted tree that is of class phylo. This allows for easy graphing of the tree with ggtree

Examples

```
set.seed(123)
tree <- ape::rtree(6)
sub_tree <- tree_subset(tree, node = "t1", levels_back = 2)
```

Index

- * **classes**
 - treedata-class, [19](#)
- ancestor, [2](#)
- as.treedata, [3](#)
- as.ultrametric, [4](#)
- child, [4](#)
- drop.tip, [5](#), [6](#)
- drop.tip, phylo(drop.tip), [5](#)
- drop.tip, phylo-method(drop.tip), [5](#)
- drop.tip, treedata(drop.tip), [5](#)
- drop.tip, treedata-method(drop.tip), [5](#)
- get.data, [6](#)
- get.data, treedata-method(get.data), [6](#)
- get.fields, [7](#)
- get.fields, treedata(get.fields), [7](#)
- get.fields, treedata-method
(get.fields), [7](#)
- get.treetext, [7](#)
- get.treetext, treedata-method
(get.treetext), [7](#)
- get_tree_data, [9](#)
- getNodeNum, [8](#)
- groupClade, [9](#)
- groupOTU, [10](#)
- isTip, [10](#)
- keep.tip(drop.tip), [5](#)
- keep.tip, phylo-method(drop.tip), [5](#)
- keep.tip, treedata-method(drop.tip), [5](#)
- MRCA, [11](#)
- Nnode.treedata, [12](#)
- node.label, [12](#)
- node.label<- (td-label-assign), [18](#)
- nodeid, [13](#)
- nodelab, [13](#)
- offspring, [14](#)
- parent, [15](#)
- root.treedata, [15](#)
- rootnode, [16](#)
- show, [17](#)
- show, treedata-method(treedata-class),
[19](#)
- sibling, [17](#)
- td-label-assign, [18](#)
- tip.label, [18](#)
- tip.label<- (td-label-assign), [18](#)
- tree_subset, [20](#)
- treedata, [19](#)
- treedata-class, [19](#)