

Package ‘tinytable’

July 22, 2025

Type Package

Title Simple and Configurable Tables in 'HTML', 'LaTeX', 'Markdown', 'Word', 'PNG', 'PDF', and 'Typst' Formats

Description Create highly customized tables with this simple and dependency-free package. Data frames can be converted to 'HTML', 'LaTeX', 'Markdown', 'Word', 'PNG', 'PDF', or 'Typst' tables. The user interface is minimalist and easy to learn. The syntax is concise. 'HTML' tables can be customized using the flexible 'Bootstrap' framework, and 'LaTeX' code with the 'tabularray' package.

Version 0.10.0

Imports methods

Depends R (>= 4.1.0)

Enhances knitr

Suggests base64enc, data.table (>= 1.15.2), estimatr, fansi, ggplot2, gh, htmltools, litedown (>= 0.6), magrittr, margineffects, modelsummary, pandoc, quarto, rmarkdown, rstudioapi, scales, stringi, tibble, tinysnapshot, tinytest, tinytex, xfun (>= 0.51), webshot2

URL <https://vincentarelbundock.github.io/tinytable/>

BugReports <https://github.com/vincentarelbundock/tinytable/issues>

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.3.2

NeedsCompilation no

Author Vincent Arel-Bundock [aut, cre] (ORCID:
<<https://orcid.org/0000-0003-2042-7063>>)

Maintainer Vincent Arel-Bundock <vincent.arel-bundock@umontreal.ca>

Repository CRAN

Date/Publication 2025-07-03 12:40:02 UTC

Contents

tinytable-package	2
format_tt	3
group_tt	7
plot_tt	9
print.tinytable	11
rbind2,tinytable,tinytable-method	12
save_tt	13
strip_tt	16
style_tt	18
theme_tt	22
tt	25
Index	31

tinytable-package	<i>Simple and Configurable Tables in 'HTML', 'LaTeX', 'Markdown', 'Word', 'PNG', 'PDF', and 'Typst' Formats</i>
-------------------	---

Description

Create highly customized tables with this simple and dependency-free package. Data frames can be converted to 'HTML', 'LaTeX', 'Markdown', 'Word', 'PNG', 'PDF', or 'Typst' tables. The user interface is minimalist and easy to learn. The syntax is concise. 'HTML' tables can be customized using the flexible 'Bootstrap' framework, and 'LaTeX' code with the 'tabulararray' package.

Package Content

Index of help topics:

format_tt	Format columns of a data frame
group_tt	Spanning labels to identify groups of rows or columns
plot_tt	Insert images and inline plots into tinytable objects
print.tinytable	Print, display, or convert a tinytable object
rbind2,tinytable,tinytable-method	Combine 'tinytable' objects by rows (vertically)
save_tt	Save a Tiny Table to File
strip_tt	Strip elements from a Tiny Table
style_tt	Style a Tiny Table
theme_tt	Themes for 'tinytable'
tinytable-package	Simple and Configurable Tables in 'HTML', 'LaTeX', 'Markdown', 'Word', 'PNG', 'PDF', and 'Typst' Formats
tt	Draw a Tiny Table

Maintainer

Vincent Arel-Bundock <vincent.arel-bundock@umontreal.ca>

Author(s)

Vincent Arel-Bundock [aut, cre] (<<https://orcid.org/0000-0003-2042-7063>>)

format_tt	<i>Format columns of a data frame</i>
-----------	---------------------------------------

Description

This function formats the columns of a data frame based on the column type (logical, date, numeric). It allows various formatting options like significant digits, decimal points, and scientific notation. It also includes custom formatting for date and boolean values. If this function is applied several times to the same cell, the last transformation is retained and the previous calls are ignored, except for the escape argument which can be applied to previously transformed data.

Usage

```
format_tt(
  x,
  i = NULL,
  j = NULL,
  digits = get_option("tinytable_format_digits", default = NULL),
  num_fmt = get_option("tinytable_format_num_fmt", default = "significant"),
  num_zero = get_option("tinytable_format_num_zero", default = FALSE),
  num_suffix = get_option("tinytable_format_num_suffix", default = FALSE),
  num_mark_big = get_option("tinytable_format_num_mark_big", default = ""),
  num_mark_dec = get_option("tinytable_format_num_mark_dec", default =
    getOption("OutDec", default = ".")),
  date = get_option("tinytable_format_date", default = NULL),
  bool = get_option("tinytable_format_bool", default = NULL),
  math = get_option("tinytable_format_math", default = FALSE),
  other = get_option("tinytable_format_other", default = NULL),
  replace = get_option("tinytable_format_replace", default = FALSE),
  escape = get_option("tinytable_format_escape", default = FALSE),
  markdown = get_option("tinytable_format_markdown", default = FALSE),
  quarto = get_option("tinytable_format_quarto", default = FALSE),
  fn = get_option("tinytable_format_fn", default = NULL),
  sprintf = get_option("tinytable_format_sprintf", default = NULL)
)
```

Arguments

<code>x</code>	A data frame or a vector to be formatted.
<code>i</code>	Row indices where the formatting should be applied.
<code>j</code>	Column indices where the styling should be applied. Can be: • Integer vectors indicating column positions. • Character vector indicating column names. • A single string specifying a Perl-style regular expression used to match column names.
<code>digits</code>	Number of significant digits or decimal places.
<code>num_fmt</code>	The format for numeric values; one of 'significant', 'significant_cell', 'decimal', or 'scientific'.
<code>num_zero</code>	Logical; if TRUE, trailing zeros are kept in "decimal" format (but not in "significant" format).
<code>num_suffix</code>	Logical; if TRUE display short numbers with <code>digits</code> significant digits and K (thousands), M (millions), B (billions), or T (trillions) suffixes.
<code>num_mark_big</code>	Character to use as a thousands separator.
<code>num_mark_dec</code>	Decimal mark character. Default is the global option 'OutDec'.
<code>date</code>	A string passed to the <code>format()</code> function, such as "%Y-%m-%d". See the "Details" section in <code>?strptime</code>
<code>bool</code>	A function to format logical columns. Defaults to title case.
<code>math</code>	Logical. If TRUE, wrap cell values in math mode $$. . $$. This is useful for LaTeX output or with HTML MathJax options(<code>tinytable_html_mathjax=TRUE</code>).
<code>other</code>	A function to format columns of other types. Defaults to <code>as.character()</code> .
<code>replace</code>	Logical, String or Named list of vectors • TRUE: Replace NA and NaN by an empty string. • FALSE: Print NA and NaN as strings. • String: Replace NA and NaN entries by the user-supplied string. • Named list: Replace matching elements of the vectors in the list by their names. Example: <pre>list("-", c(NA, NaN), "Tiny" = -Inf, "Massive" = Inf)</pre>
<code>escape</code>	Logical or "latex" or "html". If TRUE, escape special characters to display them as text in the format of the output of a <code>tt()</code> table. • If <code>i</code> and <code>j</code> are both NULL, escape all cells, column names, caption, notes, and spanning labels created by <code>group_tt()</code>.
<code>markdown</code>	Logical; if TRUE, render markdown syntax in cells. Ex: <code>_italicized text_</code> is properly italicized in HTML and LaTeX.
<code>quarto</code>	Logical. Enable Quarto data processing and wrap cell content in a <code>data-qmdspan</code> (HTML) or <code>\QuartoMarkdownBase64{}</code> macro (LaTeX). See warnings in the Global Options section below.
<code>fn</code>	Function for custom formatting. Accepts a vector and returns a character vector of the same length.
<code>sprintf</code>	String passed to the <code>?sprintf</code> function to format numbers or interpolate strings with a user-defined pattern (similar to the <code>glue</code> package, but using Base R).

Value

A data frame with formatted columns.

Global options

Options can be set with `options()` and change the default behavior of `tinytable`. For example:

```
options(tinytable_tt_digits = 4)
tt(head(iris))
```

You can set options in a script or via `.Rprofile`. Note: be cautious with `.Rprofile` settings as they may affect reproducibility.

Default values for function arguments:

tt():

- `tinytable_tt_digits`
- `tinytable_tt_caption`
- `tinytable_tt_notes`
- `tinytable_tt_width`
- `tinytable_tt_theme`
- `tinytable_tt_rownames`

format_tt():

- `tinytable_format_digits`
- `tinytable_format_num_fmt`
- `tinytable_format_num_zero`
- `tinytable_format_num_suffix`
- `tinytable_format_num_mark_big`
- `tinytable_format_num_mark_dec`
- `tinytable_format_date`
- `tinytable_format_bool`
- `tinytable_format_other`
- `tinytable_format_replace`
- `tinytable_format_escape`
- `tinytable_format_markdown`
- `tinytable_format_quarto`
- `tinytable_format_fn`
- `tinytable_format_sprintf`

save_tt():

- `tinytable_save_overwrite`

theme_tt():

Placement:

- `tinytable_theme_placement_float`
- `tinytable_theme_placement_horizontal`

Resize:

- `tinytable_theme_resize_width`
- `tinytable_theme_resize_direction`

Multipage:

- `tinytable_theme_multipage_rowhead`
- `tinytable_theme_multipage_rowfoot`

Tabular:

- `tinytable_theme_tabular_style`

`print.tinytable()`:

- `tinytable_print_output`

Output-specific options:

HTML:

- `tinytable_html_mathjax`: Insert MathJax scripts (warning: may conflict if MathJax is loaded elsewhere)
- `tinytable_html_portable`: Insert base64 encoded images directly in HTML for `plot_tt()`

PDF:

- `tinytable_pdf_clean`: Delete temporary and log files
- `tinytable_pdf_engine`: Choose between "xelatex", "pdflatex", "lualatex"

Quarto:

The `format_tt(quarto=TRUE)` argument enables Quarto data processing with some limitations:

1. The `\QuartoMarkdownBase64{}` LaTeX macro may not process references and markdown as expected
2. Quarto processing may conflict with `tinytable` styling/formatting

Options:

- `tinytable_quarto_disable_processing`: Disable Quarto cell processing
- `tinytable_print_rstudio_notebook`: Display tables "inline" or in "viewer" for RStudio notebooks
- `tinytable_quarto_figure`: Control Typst figure environment in Quarto

Example of Quarto-specific code in cells:

```
x <- data.frame(Math = "x^2^", Citation = "@Lovelace1842")
fn <- function(z) sprintf("<span data-qmd='%s'></span>", z)
tt(x) |> format_tt(i = 1, fn = fn)
```

For more details on Quarto table processing: <https://quarto.org/docs/authoring/tables.html#disabling-quarto-table-processing>

Examples

```
dat <- data.frame(
  a = rnorm(3, mean = 10000),
  b = rnorm(3, 10000)
)
tab <- tt(dat)
format_tt(tab,
```

```

    digits = 2,
    num_mark_dec = ",",
    num_mark_big = " "
  )

k <- tt(data.frame(x = c(0.000123456789, 12.4356789)))
format_tt(k, digits = 2, num_fmt = "significant_cell")

dat <- data.frame(
  a = c("Burger", "Halloumi", "Tofu", "Beans"),
  b = c(1.43202, 201.399, 0.146188, 0.0031),
  c = c(98938272783457, 7288839482, 29111727, 93945)
)
tt(dat) |>
  format_tt(j = "a", sprintf = "Food: %s") |>
  format_tt(j = 2, digits = 1, num_fmt = "decimal", num_zero = TRUE) |>
  format_tt(j = "c", digits = 2, num_suffix = TRUE)

y <- tt(data.frame(x = c(123456789.678, 12435.6789)))
format_tt(y, digits = 3, num_mark_big = " ")

x <- tt(data.frame(Text = c("_italicized text_", "__bold text__")))
format_tt(x, markdown = TRUE)

tab <- data.frame(a = c(NA, 1, 2), b = c(3, NA, 5))
tt(tab) |> format_tt(replace = "-")

dat <- data.frame(
  "LaTeX" = c("Dollars $", "Percent %", "Underscore _"),
  "HTML" = c("<br>", "<sup>4</sup>", "<emph>blah</emph>")
)
tt(dat) |> format_tt(escape = TRUE)

```

group_tt

Spanning labels to identify groups of rows or columns

Description

Spanning labels to identify groups of rows or columns

Usage

```

group_tt(
  x,
  i = getOption("tinytable_group_i", default = NULL),
  j = getOption("tinytable_group_j", default = NULL),
  indent = getOption("tinytable_group_indent", default = 1),
  ...
)

```

Arguments

x	A data frame or data table to be rendered as a table.
i	A vector of labels with length equal to the number of rows in x, or a named list of row indices to group. The names of the list will be used as labels. The indices represent the position where labels should be inserted in the original table. For example, • <code>i=list("Hello"=5)</code>: insert the "Hello" label after the 4th row in the original table. • <code>i=list("Hello"=2, "World"=2)</code>: insert the two labels consecutively after the 1st row in the original table. • <code>i=list("Foo Bar"=0)</code>: insert the label in the first row after the header.
j	String or named list • Named list of column indices to group, ex: <code>j=list("A"=1:2, "B"=3:6)</code>. The names of the list will be used as labels. See below for more examples. Note: empty labels must be a space: " ". • A single string when column names include the group name as a prefix, ex: <code>group1_column1</code>, <code>group1_column2</code>, etc.
indent	integer number of pt to use when indenting the non-labelled rows.
...	Other arguments are ignored.

Details

Warning: The `style_tt()` can normally be used to style the group headers, as expected, but that feature is not available for Markdown and Word tables.

Value

An object of class `tt` representing the table.

Word and Markdown limitations

Markdown and Word tables only support these styles: italic, bold, strikethrough. The width argument is also unavailable. Moreover, the `style_tt()` function cannot be used to style headers inserted by the `group_tt()` function; instead, you should style the headers directly in the header definition using markdown syntax: `group_tt(i = list("*italic header*" = 2))`. These limitations are due to the fact that there is no markdown syntax for the other options, and that we create Word documents by converting a markdown table to .docx via the Pandoc software.

Examples

```
# vector of row labels
dat <- data.frame(
  label = c("a", "a", "a", "b", "b", "c", "a", "a"),
  x1 = rnorm(8),
  x2 = rnorm(8)
)
tt(dat[, 2:3]) |> group_tt(i = dat$label)
```

```

# named lists of labels
tt(mtcars[1:10, 1:5]) |>
  group_tt(
    i = list(
      "Hello" = 3,
      "World" = 8
    ),
    j = list(
      "Foo" = 2:3,
      "Bar" = 4:5
    )
  )

dat <- mtcars[1:9, 1:8]
tt(dat) |>
  group_tt(i = list(
    "I like (fake) hamburgers" = 3,
    "She prefers halloumi" = 4,
    "They love tofu" = 7
  ))

tt(dat) |>
  group_tt(
    j = list(
      "Hamburgers" = 1:3,
      "Halloumi" = 4:5,
      "Tofu" = 7
    )
  )

x <- mtcars[1:5, 1:6]
tt(x) |>
  group_tt(j = list("Hello" = 1:2, "World" = 3:4, "Hello" = 5:6)) |>
  group_tt(j = list("Foo" = 1:3, "Bar" = 4:6))

# column names with delimiters
dat <- data.frame(
  A_id = 1,
  A_a1 = 2,
  A_a2 = "3",
  B_b1 = 4,
  B_b2 = 5,
  B_C = 6
)
tt(dat) |> group_tt(j = "_")

```

Description

The `plot_tt()` function allows for the insertion of images and inline plots into tinytable objects. This function can handle both local and web-based images.

Usage

```
plot_tt(
  x,
  i = NULL,
  j = NULL,
  fun = NULL,
  data = NULL,
  color = "black",
  xlim = NULL,
  height = 1,
  asp = 1/3,
  images = NULL,
  assets = "tinytable_assets",
  ...
)
```

Arguments

<code>x</code>	A tinytable object.
<code>i</code>	Integer vector, the row indices where images are to be inserted. If <code>NULL</code> , images will be inserted in all rows.
<code>j</code>	Integer vector, the column indices where images are to be inserted. If <code>NULL</code> , images will be inserted in all columns.
<code>fun</code>	String or function to generate inline plots. • String: "histogram", "density", "bar", "line" • Functions that return <code>ggplot2</code> objects. • Functions that return another function which generates a base R plot, ex: <code>function(x) {function() hist(x)}</code> • See the tutorial on the <code>tinytable</code> website for more information.
<code>data</code>	a list of data frames or vectors to be used by the plotting functions in <code>fun</code> .
<code>color</code>	string Name of color to use for inline plots (passed to the <code>col</code> argument base graphics plots in R).
<code>xlim</code>	Numeric vector of length 2.
<code>height</code>	Numeric, the height of the images in the table in em units.
<code>asp</code>	Numeric, aspect ratio of the plots (height / width).
<code>images</code>	Character vector, the paths to the images to be inserted. Paths are relative to the main table file or Quarto (Rmarkdown) document.
<code>assets</code>	Path to the directory where generated assets are stored. This path is relative to the location where a table is saved.
<code>...</code>	Extra arguments are passed to the function in <code>fun</code> . Important: Custom plotting functions must always have <code>...</code> as an argument.

Details

The `plot_tt()` can insert images and inline plots into tables.

Value

A modified tinytable object with images or plots inserted.

<code>print.tinytable</code>	<i>Print, display, or convert a tinytable object</i>
------------------------------	--

Description

This function is called automatically by R whenever a tinytable object is anprinted to the console or in an HTML viewer pane.

Usage

```
## S3 method for class 'tinytable'
print(x, output = get_option("tinytable_print_output", default = NULL), ...)
```

Arguments

<code>x</code>	A data frame or data table to be rendered as a table.
<code>output</code>	format in which a Tiny Table is printed: NULL or one of "latex", "markdown", "html", "typst", "dataframe". If NULL, the output is chosen based on these rules: • When called from a script in non-interactive mode, the default is "markdown" (<code>interactive() == FALSE</code>). • When called interactively in RStudio, the default is to display an HTML table in the viewer pane. • When called interactively in another development environment, the default is "markdown". • The default print output can be changed for an entire R session by calling: <code>options(tinytable_print_output = "html")</code> • The default print output can be changed for a single tinytable object by modifying the output S4 slot.
<code>...</code>	Other arguments are ignored.

Value

launch a browser window or `cat()` the table to console.

rbind2, tinytable, tinytable-method

Combine tinytable objects by rows (vertically)

Description

Combine tinytable objects by rows (vertically)

Usage

```
## S4 method for signature 'tinytable, tinytable'
rbind2(x, y, use_names = TRUE, headers = TRUE, ...)
```

Arguments

x	tinytable object
y	tinytable object
use_names	'TRUE' binds by matching column name, 'FALSE' by position
headers	Logical. TRUE inserts the colnames of y as an extra row between the two tables.
...	Additional arguments are ignored.

Details

format_tt() calls applied to x or y are evaluated before binding, to allow distinct formatting for each panel.

Calls to other tinytable functions such as style_tt() or group_tt() are ignored when applied to x or y. These functions should be applied to the final table instead.

Information in these S4 slots is carried over from x to the combined table:

- x@output
- x@caption
- x@width

Information in these S4 slots is concatenated and carried over to the combined table:

- c(x@notes, y@notes)

This function relies on the rbindlist() function from the data.table package.

Examples

```
library(tinytable)
x <- tt(mtcars[1:3, 1:2], caption = "Combine two tiny tables.")
y <- tt(mtcars[4:5, 8:10])

# rbind() does not support additional arguments
# rbind2() supports additional arguments

# basic combination
rbind(x, y)

rbind(x, y) |> format_tt(replace = "")

# omit y header
rbind2(x, y, headers = FALSE)

# bind by position rather than column names
rbind2(x, y, use_names = FALSE)
```

save_tt

Save a Tiny Table to File

Description

This function saves an object of class `tinytable` to a specified file and format, with an option to overwrite existing files.

Usage

```
save_tt(
  x,
  output,
  overwrite = get_option("tinytable_save_overwrite", default = FALSE)
)
```

Arguments

x	The <code>tinytable</code> object to be saved.
output	String or file path. - If output is "markdown", "latex", "html", "html_portable", or "typst", the table is returned in a string as an R object. - If output is a valid file path, the table is saved to file. The supported extensions are: .docx, .html, .png, .pdf, .tex, .typ, and .md (with aliases .txt, .Rmd and .qmd). - If output is "html_portable" or the global option <code>tinytable_html_portable</code> is TRUE, the images are included in the HTML as base64 encoded string instead of link to a local file.
overwrite	A logical value indicating whether to overwrite an existing file.

Value

A string with the table when output is a format, and the file path when output is a valid path.

Dependencies

- .pdf output requires a full LaTeX installation on the local computer.
- .png output requires the webshot2 package.
- .html self-contained files require the base64enc package.

LaTeX preamble

tinytable uses the tabulararray package from your LaTeX distribution to draw tables. tabulararray, in turn, uses the special tblr, talltblr, and longtblr environments.

When rendering a document from Quarto or Rmarkdown directly to PDF, tinytable will populate the LaTeX preamble automatically with all the required packages. For standalone LaTeX documents, these commands should be inserted in the preamble manually:

Note: Your document will fail to compile to PDF in Quarto if you enable caching and you use tinytable due to missing LaTeX headers. To avoid this problem, set the option `#| cache: false` for the chunk(s) where you use tinytable.

```
\usepackage{tabulararray}
\usepackage{float}
\usepackage{graphicx}
\usepackage{rotating}
\usepackage[normalem]{ulem}
\UseTblrLibrary{booktabs}
\UseTblrLibrary{siunitx}
\newcommand{\tinytableTabulararrayUnderline}[1]{\underline{#1}}
\newcommand{\tinytableTabulararrayStrikeout}[1]{\sout{#1}}
\NewTableCommand{\tinytableDefineColor}[3]{\definecolor{#1}{#2}{#3}}
```

Global options

Options can be set with `options()` and change the default behavior of tinytable. For example:

```
options(tinytable_tt_digits = 4)
tt(head(iris))
```

You can set options in a script or via `.Rprofile`. Note: be cautious with `.Rprofile` settings as they may affect reproducibility.

Default values for function arguments:

`tt()`:

- `tinytable_tt_digits`
- `tinytable_tt_caption`
- `tinytable_tt_notes`

- tinytable_tt_width
- tinytable_tt_theme
- tinytable_tt_rownames

format_tt():

- tinytable_format_digits
- tinytable_format_num_fmt
- tinytable_format_num_zero
- tinytable_format_num_suffix
- tinytable_format_num_mark_big
- tinytable_format_num_mark_dec
- tinytable_format_date
- tinytable_format_bool
- tinytable_format_other
- tinytable_format_replace
- tinytable_format_escape
- tinytable_format_markdown
- tinytable_format_quarto
- tinytable_format_fn
- tinytable_format_sprintf

save_tt():

- tinytable_save_overwrite

theme_tt():

Placement:

- tinytable_theme_placement_float
- tinytable_theme_placement_horizontal

Resize:

- tinytable_theme_resize_width
- tinytable_theme_resize_direction

Multipage:

- tinytable_theme_multipage_rowhead
- tinytable_theme_multipage_rowfoot

Tabular:

- tinytable_theme_tabular_style

print.tinytable():

- tinytable_print_output

Output-specific options:

HTML:

- tinytable_html_mathjax: Insert MathJax scripts (warning: may conflict if MathJax is loaded elsewhere)
- tinytable_html_portable: Insert base64 encoded images directly in HTML for plot_tt()

PDF:

- `tinytable_pdf_clean`: Delete temporary and log files
- `tinytable_pdf_engine`: Choose between "xelatex", "pdflatex", "lualatex"

Quarto:

The `format_tt(quarto=TRUE)` argument enables Quarto data processing with some limitations:

1. The `\QuartoMarkdownBase64{}` LaTeX macro may not process references and markdown as expected
2. Quarto processing may conflict with `tinytable` styling/formatting

Options:

- `tinytable_quarto_disable_processing`: Disable Quarto cell processing
- `tinytable_print_rstudio_notebook`: Display tables "inline" or in "viewer" for RStudio notebooks
- `tinytable_quarto_figure`: Control Typst figure environment in Quarto

Example of Quarto-specific code in cells:

```
x <- data.frame(Math = "x^2^", Citation = "@Lovelace1842")
fn <- function(z) sprintf("<span data-qmd='%s'></span>", z)
tt(x) |> format_tt(i = 1, fn = fn)
```

For more details on Quarto table processing: <https://quarto.org/docs/authoring/tables.html#disabling-quarto-table-processing>

Examples

```
library(tinytable)
x <- mtcars[1:4, 1:5]

fn <- file.path(tempdir(), "test.html")
tt(x) |> save_tt(fn, overwrite = TRUE)

library(tinytable)
filename <- file.path(tempdir(), "table.tex")
tt(mtcars[1:4, 1:4]) |> save_tt(filename)
```

strip_tt

Strip elements from a Tiny Table

Description

Strip elements from a Tiny Table

Usage

```
strip_tt(
  x,
  style = FALSE,
  format = FALSE,
```

```

    theme = FALSE,
    notes = FALSE,
    caption = FALSE,
    group = FALSE,
    bold = FALSE,
    italic = FALSE,
    monospace = FALSE,
    underline = FALSE,
    strikeout = FALSE,
    color = FALSE,
    background = FALSE,
    fontsize = FALSE,
    align = FALSE,
    alignv = FALSE,
    colspan = FALSE,
    rowspan = FALSE,
    indent = FALSE,
    line = FALSE,
    bootstrap_class = FALSE,
    bootstrap_css = FALSE,
    bootstrap_css_rule = FALSE,
    tabularray_inner = FALSE,
    tabularray_outer = FALSE,
    width = FALSE
)

```

Arguments

x	A table object created by tt().
style	TRUE reverts style_tt().
format	TRUE reverts format_tt().
theme	TRUE reverts theme_tt().
notes	TRUE reverts the effect of the notes argument from tt().
caption	TRUE reverts the effect of the caption argument from tt().
group	TRUE reverts group_tt().
bold	TRUE reverts the effect of the bold argument from style_tt().
italic	TRUE reverts the effect of the italic argument from style_tt().
monospace	TRUE reverts the effect of the monospace argument from style_tt().
underline	TRUE reverts the effect of the underline argument from style_tt().
strikeout	TRUE reverts the effect of the strikeout argument from style_tt().
color	TRUE reverts the effect of the color argument from style_tt().
background	TRUE reverts the effect of the background argument from style_tt().
fontsize	TRUE reverts the effect of the fontsize argument from style_tt().
align	TRUE reverts the effect of the align argument from style_tt().

alignv	TRUE reverts the effect of the alignv argument from style_tt().
colspan	TRUE reverts the effect of the colspan argument from style_tt().
rowspan	TRUE reverts the effect of the rowspan argument from style_tt().
indent	TRUE reverts the effect of the indent argument from style_tt().
line	TRUE reverts the effect of the line argument from style_tt().
bootstrap_class	TRUE reverts the effect of the bootstrap_class argument from style_tt().
bootstrap_css	TRUE reverts the effect of the bootstrap_css argument from style_tt().
bootstrap_css_rule	TRUE reverts the effect of the bootstrap_css_rule argument from style_tt().
tabularray_inner	TRUE reverts the effect of the tabularray_inner argument from style_tt().
tabularray_outer	TRUE reverts the effect of the tabularray_outer argument from style_tt().
width	TRUE reverts the effect of the width argument from tt().

Value

An object of class `tt` representing the table with stripped styling.

style_tt	<i>Style a Tiny Table</i>
----------	---------------------------

Description

Style a Tiny Table

Usage

```
style_tt(
  x,
  i = NULL,
  j = NULL,
  bold = FALSE,
  italic = FALSE,
  monospace = FALSE,
  underline = FALSE,
  strikeout = FALSE,
  color = NULL,
  background = NULL,
  fontsize = NULL,
  align = NULL,
  alignv = NULL,
  colspan = NULL,
```

```

    rowspan = NULL,
    indent = NULL,
    line = NULL,
    line_color = "black",
    line_width = 0.1,
    finalize = NULL,
    tabularray_inner = NULL,
    tabularray_outer = NULL,
    bootstrap_class = NULL,
    bootstrap_css = NULL,
    bootstrap_css_rule = NULL,
    output = NULL,
    ...
)

```

Arguments

<code>x</code>	A table object created by <code>tt()</code> .
<code>i</code>	Numeric vector, logical matrix, or string.. • Numeric vector: Row indices where the styling should be applied. Can be a single value or a vector. • Logical matrix: A matrix with the same number of rows and columns as <code>x</code>. <code>i=0</code> is the header, and negative values are higher level headers. Row indices refer to rows <i>after</i> the insertion of row labels by <code>group_tt()</code>, when applicable. • String: "caption", "group<i>i</i>", "notes".
<code>j</code>	Column indices where the styling should be applied. Can be: • Integer vectors indicating column positions. • Character vector indicating column names. • A single string specifying a Perl-style regular expression used to match column names.
<code>bold</code>	Logical; if TRUE, text is styled in bold.
<code>italic</code>	Logical; if TRUE, text is styled in italic.
<code>monospace</code>	Logical; if TRUE, text is styled in monospace font.
<code>underline</code>	Logical; if TRUE, text is underlined.
<code>strikeout</code>	Logical; if TRUE, text has a strike through line.
<code>color</code>	Text color. There are several ways to specify colors, depending on the output format. • HTML: – Hex code composed of # and 6 characters, ex: #CC79A7. – Keywords: black, silver, gray, white, maroon, red, purple, fuchsia, green, lime, olive, yellow, navy, blue, teal, aqua • LaTeX: – Hex code composed of # and 6 characters, ex: "#CC79A7". See the section below for instructions to add in LaTeX preambles.

	– Keywords: black, blue, brown, cyan, darkgray, gray, green, lightgray, lime, magenta, olive, orange, pink, purple, red, teal, violet, white, yellow. – Color blending using xcolor, ex: white!80!blue, green!20!red. – Color names with luminance levels from the ninecolors package (ex: "azure4", "magenta8", "teal2", "gray1", "olive3").
background	Background color. Specified as a color name or hexadecimal code. Can be NULL for default color.
fontsize	Font size in em units. Can be NULL for default size.
align	A single character or a string with a number of characters equal to the number of columns in j. Valid characters include 'c' (center), 'l' (left), 'r' (right), 'd' (decimal). Decimal alignment is only available in LaTeX via the siunitx package. The width of columns is determined by the maximum number of digits to the left and to the right in all cells specified by i and j.
alignv	A single character specifying vertical alignment. Valid characters include 't' (top), 'm' (middle), 'b' (bottom).
colspan	Number of columns a cell should span. i and j must be of length 1.
rowspan	Number of rows a cell should span. i and j must be of length 1.
indent	Text indentation in em units. Positive values only.
line	String determines if solid lines (rules or borders) should be drawn around the cell, row, or column. • "t": top • "b": bottom • "l": left • "r": right • Can be combined such as: "lbt" to draw borders at the left, bottom, and top.
line_color	Color of the line. See the color argument for details.
line_width	Width of the line in em units (default: 0.1).
finalize	A function applied to the table object at the very end of table-building, for post-processing. For example, the function could use regular expressions to add LaTeX commands to the text version of the table hosted in x@table_string, or it could programmatically change the caption in x@caption.
tabularray_inner	A string that specifies the "inner" settings of a tabularray LaTeX table.
tabularray_outer	A string that specifies the "outer" settings of a tabularray LaTeX table.
bootstrap_class	String. Bootstrap table class such as "table", "table table-dark" or "table table-dark table-hover". See the bootstrap documentation.
bootstrap_css	Character vector. CSS style declarations to be applied to every cell defined by i and j (ex: "font-weight: bold").
bootstrap_css_rule	String. Complete CSS rules (with curly braces, semicolon, etc.) that apply to the table class specified by the bootstrap_class argument.

output	Apply style only to the output format specified by this argument. NULL means that we apply to all formats.
...	extra arguments are ignored

Details

This function applies styling to a table created by `tt()`. It allows customization of text style (bold, italic, monospace), text and background colors, font size, cell width, text alignment, column span, and indentation. The function also supports passing native instructions to LaTeX (tabulararray) and HTML (bootstrap) formats.

Value

An object of class `tt` representing the table.

Word and Markdown limitations

Markdown and Word tables only support these styles: italic, bold, strikethrough. The width argument is also unavailable. Moreover, the `style_tt()` function cannot be used to style headers inserted by the `group_tt()` function; instead, you should style the headers directly in the header definition using markdown syntax: `group_tt(i = list("*italic header*" = 2))`. These limitations are due to the fact that there is no markdown syntax for the other options, and that we create Word documents by converting a markdown table to .docx via the Pandoc software.

Examples

```
if (knitr::is_html_output()) options(tinytable_print_output = "html")

library(tinytable)

tt(mtcars[1:5, 1:6])

# Alignment
tt(mtcars[1:5, 1:6]) |>
  style_tt(j = 1:5, align = "lcccr")

# Colors and styles
tt(mtcars[1:5, 1:6]) |>
  style_tt(i = 2:3, background = "black", color = "orange", bold = TRUE)

# column selection with `j`
tt(mtcars[1:5, 1:6]) |>
  style_tt(j = 5:6, background = "pink")

tt(mtcars[1:5, 1:6]) |>
  style_tt(j = "drat|wt", background = "pink")

tt(mtcars[1:5, 1:6]) |>
  style_tt(j = c("drat", "wt"), background = "pink")
```

```

tt(mtcars[1:5, 1:6], theme = "void") |>
  style_tt(
    i = 2, j = 2,
    colspan = 3,
    rowspan = 2,
    align = "c",
    alignv = "m",
    color = "white",
    background = "black",
    bold = TRUE)

tt(mtcars[1:5, 1:6], theme = "void") |>
  style_tt(
    i = 0:3,
    j = 1:3,
    line = "tblr",
    line_width = 0.4,
    line_color = "teal")

tt(mtcars[1:5, 1:6], theme = "bootstrap") |>
  style_tt(
    i = c(2, 5),
    j = 3,
    strikeout = TRUE,
    fontsize = 0.7)

tt(mtcars[1:5, 1:6]) |>
  style_tt(bootstrap_class = "table table-dark table-hover")

inner <- "
column{1-4}={halign=c},
hlines = {fg=white},
vlines = {fg=white},
cell{1,6}{odd} = {bg=teal7},
cell{1,6}{even} = {bg=green7},
cell{2,4}{1,4} = {bg=red7},
cell{3,5}{1,4} = {bg=purple7},
cell{2}{2} = {r=4,c=2}{bg=azure7},
"

tt(mtcars[1:5, 1:4], theme = "void") |>
  style_tt(tabularray_inner = inner)

```

theme_tt

Themes for tinytable

Description

A theme is a function which applies a collection of transformations to a `tinytable` object. Whereas the other `tinytable` functions such as `format_tt()` and `style_tt()` aim to be output-agnostic,

themes can be output-specific, only applying to LaTeX, HTML, or Typst, as needed.

Each theme can have specific arguments, which are passed to the `theme_tt()` function. See the "Arguments" section below.

Usage

```
theme_tt(x, theme, ...)
```

Arguments

<code>x</code>	A <code>tinytable</code> object
<code>theme</code>	String. Name of the theme to apply. One of: • "bootstrap": Similar appearance to the default Bootstrap theme in HTML • "grid": Vertical and horizontal rules around each cell. • "multipage": Long tables continue on the next page (LaTeX only) • "placement": Position of the table environment (LaTeX) • "revealjs": Tables optimized for Reveal.js presentations with light/dark theme support • "rotate": Rotate a LaTeX or Typst table. • "resize": Scale a LaTeX <code>tinytable</code> to fit the width argument. • "spacing": Draw more compact or airy tables. • "striped": Grey stripes on alternating rows • "tabular": Remove table environment (LaTeX) or Javascript/CSS (HTML) • "void": No rules
<code>...</code>	Additional arguments passed the themeing function. See the "Arguments" section below for a list of supported arguments for each theme.

Value

A modified `tinytable` object

Arguments

<code>revealjs</code>	• <code>css</code>: String. "light" (default) or "dark" for light or dark theme colors. – Set globally with <code>options("tinytable_theme_revealjs_css" = "dark")</code> • <code>fontsize</code>: Numeric. Font size multiplier for table content. – Set globally with <code>options("tinytable_theme_revealjs_fontsize" = 0.8)</code> • <code>fontsize_caption</code>: Numeric. Font size multiplier for table captions. – Set globally with <code>options("tinytable_theme_revealjs_fontsize_caption" = 1)</code>
<code>multipage</code>	• <code>rowhead</code>: Non-negative integer. The number of header rows to repeat on each page. – Set globally with <code>options("tinytable_theme_multipage_rowhead" = 1L)</code>

- rowfoot: Non-negative integer. The number of footer rows to repeat on each page.
 - Set globally with options("tinytable_theme_multipage_rowfoot" = 1L)

tabular

- style:
 - "tabular": Drop all LaTeX dependencies and floating environments, except `\begin{tabular}`
 - "tabularray": Drop all LaTeX dependencies and floating environments, except `\begin{tblr}`
 - Set globally with options("tinytable_theme_tabular_style" = "tblr")

placement

- horizontal (Typst only): "l", "c", or "r" to align the table horizontally in the page.
 - Set globally with options("tinytable_theme_placement_horizontal" = "l")
- latex_float: String to insert in square brackets after the LaTeX table environment, ex: "H", "htbp". The default value is controlled by a global option:
 - Set globally with options("tinytable_theme_placement_latex_float" = "H")

resize

- width: A numeric value between 0.01 and 1, representing the proportion of the line width to use
 - Set globally with options("tinytable_theme_resize_width" = 0.9)
- direction: "down", "up", "both" A string indicating if the table should be scaled in one direction. For example, "down" will only resize the table if it exceeds `\linewidth`
 - Set globally with options("tinytable_theme_resize_direction" = "down")

rotate

- angle: Angle of the rotation. For example, 'angle=90' applies a half counter-clockwise turn.
- Caveats:
 - LaTeX and Typst only.
 - Typst: In Quarto documents, rotation does not work because Quarto takes over the figure environment.
 - LaTeX: In Quarto documents, captions must be specified using the caption argument in `tt()` rather than via Quarto chunk options.

spacing

- rowsep: Row spacing
- colsep: Column spacing

Examples

```
library(tinytable)

x <- mtcars[1:4, 1:4]

# equivalent calls
tt(x, theme = "striped")

tt(x) |> theme_tt("striped")

# resize w/ argument
x <- cbind(mtcars[1:10, ], mtcars[1:10, ])
tt(x) |>
  theme_tt("resize", width = .9) |>
  print("latex")
```

tt	<i>Draw a Tiny Table</i>
----	--------------------------

Description

The `tt` function renders a table in different formats with various styling options: HTML, Markdown, LaTeX, Word, PDF, PNG, or Typst. The table can be customized with additional functions:

- `style_tt()`: style fonts, colors, alignment, etc.
- `format_tt()`: format numbers, dates, strings, etc.
- `group_tt()`: row or column group labels.
- `theme_tt()`: apply a collection of transformations to a `tinytable`.
- `save_tt()`: save the table to a file or return the table as a string.
- `print()`: print to a specific format, ex: `print(x, "latex")`

`tinytable` attempts to determine the appropriate way to print the table based on interactive use, RStudio availability, and output format in RMarkdown or Quarto documents. Users can call `print(x, output="markdown")` to print the table in a specific format. Alternatively, they can set a global option: `options("tinytable_print_output"="markdown")`

Usage

```
tt(
  x,
  digits = get_option("tinytable_tt_digits", default = NULL),
  caption = get_option("tinytable_tt_caption", default = NULL),
  notes = get_option("tinytable_tt_notes", default = NULL),
  width = get_option("tinytable_tt_width", default = NULL),
  theme = get_option("tinytable_tt_theme", default = "default"),
  colnames = get_option("tinytable_tt_colnames", default = TRUE),
```

```

rownames = get_option("tinytable_tt_rownames", default = FALSE),
escape = get_option("tinytable_tt_escape", default = FALSE),
...
)

```

Arguments

x	A data frame or data table to be rendered as a table.
digits	Number of significant digits to keep for numeric variables. When <code>digits</code> is an integer, <code>tt()</code> calls <code>format_tt(x, digits = digits)</code> before proceeding to draw the table. Note that this will apply all default argument values of <code>format_tt()</code> , such as replacing NA by "". Users who need more control can use the <code>format_tt()</code> function instead.
caption	A string that will be used as the caption of the table. This argument should <i>not</i> be used in Quarto or Rmarkdown documents. In that context, please use the appropriate chunk options.
notes	Notes to append to the bottom of the table. This argument accepts several different inputs: • Single string insert a single note: "blah blah" • Multiple strings insert multiple notes sequentially: <code>list("Hello world", "Foo bar")</code> • A named list inserts a list with the name as superscript: <code>list("a" = list("Hello World"))</code> • A named list with positions inserts markers as superscripts inside table cells: <code>list("a" = list(i = 0:1, j = 2, text = "Hello World"))</code>
width	Table or column width. • Single numeric value smaller than or equal to 1 determines the full table width, in proportion of line width. • Numeric vector of length equal to the number of columns in <code>x</code> determines the width of each column, in proportion of line width. If the sum of width exceeds 1, each element is divided by <code>sum(width)</code>. This makes the table full-width with relative column sizes.
theme	Function or string. • String: bootstrap, grid, multipage, placement, revealjs, resize, rotate, spacing, striped, tabular, void • Function: Applied to the <code>tinytable</code> object.
colnames	Logical. If FALSE, column names are omitted.
rownames	Logical. If TRUE, rownames are included as the first column
escape	Logical. If TRUE, escape special characters in the table. Equivalent to <code>format_tt(tt(x), escape = TRUE)</code> .
...	Additional arguments are ignored

Value

An object of class `tt` representing the table.

The table object has S4 slots which hold information about the structure of the table. For example, the `table@group_index_i` slot includes the row indices for grouping labels added by `group_tt()`.

Warning: Relying on or modifying the contents of these slots is strongly discouraged. Their names and contents could change at any time, and the `tinytable` developers do not consider changes to the internal structure of the output object to be a "breaking change" for versioning or changelog purposes.

Dependencies

- .pdf output requires a full LaTeX installation on the local computer.
- .png output requires the `webshot2` package.
- .html self-contained files require the `base64enc` package.

LaTeX preamble

`tinytable` uses the `tabulararray` package from your LaTeX distribution to draw tables. `tabulararray`, in turn, uses the special `tblr`, `talltblr`, and `longtblr` environments.

When rendering a document from Quarto or Rmarkdown directly to PDF, `tinytable` will populate the LaTeX preamble automatically with all the required packages. For standalone LaTeX documents, these commands should be inserted in the preamble manually:

Note: Your document will fail to compile to PDF in Quarto if you enable caching and you use `tinytable` due to missing LaTeX headers. To avoid this problem, set the option `cache: false` for the chunk(s) where you use `tinytable`.

```
\usepackage{tabulararray}
\usepackage{float}
\usepackage{graphicx}
\usepackage{rotating}
\usepackage[normalem]{ulem}
\UseTblrLibrary{booktabs}
\UseTblrLibrary{siunitx}
\newcommand{\tinytableTabulararrayUnderline}[1]{\underline{#1}}
\newcommand{\tinytableTabulararrayStrikeout}[1]{\sout{#1}}
\NewTableCommand{\tinytableDefineColor}[3]{\definecolor{#1}{#2}{#3}}
```

Word and Markdown limitations

Markdown and Word tables only support these styles: italic, bold, `strikeout`. The width argument is also unavailable. Moreover, the `style_tt()` function cannot be used to style headers inserted by the `group_tt()` function; instead, you should style the headers directly in the header definition using markdown syntax: `group_tt(i = list("*italic header*" = 2))`. These limitations are due to the fact that there is no markdown syntax for the other options, and that we create Word documents by converting a markdown table to .docx via the Pandoc software.

Global options

Options can be set with `options()` and change the default behavior of `tinytable`. For example:

```
options(tinytable_tt_digits = 4)
tt(head(iris))
```

You can set options in a script or via `.Rprofile`. Note: be cautious with `.Rprofile` settings as they may affect reproducibility.

Default values for function arguments:

tt():

- `tinytable_tt_digits`
- `tinytable_tt_caption`
- `tinytable_tt_notes`
- `tinytable_tt_width`
- `tinytable_tt_theme`
- `tinytable_tt_rownames`

format_tt():

- `tinytable_format_digits`
- `tinytable_format_num_fmt`
- `tinytable_format_num_zero`
- `tinytable_format_num_suffix`
- `tinytable_format_num_mark_big`
- `tinytable_format_num_mark_dec`
- `tinytable_format_date`
- `tinytable_format_bool`
- `tinytable_format_other`
- `tinytable_format_replace`
- `tinytable_format_escape`
- `tinytable_format_markdown`
- `tinytable_format_quarto`
- `tinytable_format_fn`
- `tinytable_format_sprintf`

save_tt():

- `tinytable_save_overwrite`

theme_tt():

Placement:

- `tinytable_theme_placement_float`
- `tinytable_theme_placement_horizontal`

Resize:

- `tinytable_theme_resize_width`
- `tinytable_theme_resize_direction`

Multipage:

- `tinytable_theme_multipage_rowhead`
- `tinytable_theme_multipage_rowfoot`

Tabular:

- `tinytable_theme_tabular_style`

`print.tinytable()`:

- `tinytable_print_output`

Output-specific options:

HTML:

- `tinytable_html_mathjax`: Insert MathJax scripts (warning: may conflict if MathJax is loaded elsewhere)
- `tinytable_html_portable`: Insert base64 encoded images directly in HTML for `plot_tt()`

PDF:

- `tinytable_pdf_clean`: Delete temporary and log files
- `tinytable_pdf_engine`: Choose between "xelatex", "pdflatex", "lualatex"

Quarto:

The `format_tt(quarto=TRUE)` argument enables Quarto data processing with some limitations:

1. The `\QuartoMarkdownBase64{}` LaTeX macro may not process references and markdown as expected
2. Quarto processing may conflict with `tinytable` styling/formatting

Options:

- `tinytable_quarto_disable_processing`: Disable Quarto cell processing
- `tinytable_print_rstudio_notebook`: Display tables "inline" or in "viewer" for RStudio notebooks
- `tinytable_quarto_figure`: Control Typst figure environment in Quarto

Example of Quarto-specific code in cells:

```
x <- data.frame(Math = "x^2^", Citation = "@Lovelace1842")
fn <- function(z) sprintf("<span data-qmd='%s'></span>", z)
tt(x) |> format_tt(i = 1, fn = fn)
```

For more details on Quarto table processing: <https://quarto.org/docs/authoring/tables.html#disabling-quarto-table-processing>

Examples

```
library(tinytable)
x <- mtcars[1:4, 1:5]

tt(x)

tt(x,
  theme = "striped",
  width = 0.5,
  caption = "Data about cars.")
```

```
)  
  
tt(x, notes = "Hello World!")  
  
fn <- list(i = 0:1, j = 2, text = "Hello World!")  
tab <- tt(x, notes = list("*" = fn))  
print(tab, "latex")  
  
k <- data.frame(x = c(0.000123456789, 12.4356789))  
tt(k, digits = 2)
```

Index

- * **package**
 - tinytable-package, [2](#)
- format_tt, [3](#)
- group_tt, [7](#)
- plot_tt, [9](#)
- print.tinytable, [11](#)
- rbind2
 - (rbind2, tinytable, tinytable-method), [12](#)
- rbind2, tinytable, tinytable-method, [12](#)
- save_tt, [13](#)
- strip_tt, [16](#)
- style_tt, [18](#)
- theme_tt, [22](#)
- tinytable (tinytable-package), [2](#)
- tinytable-package, [2](#)
- tt, [25](#)