Package 'tinytiger'

July 22, 2025

Title Lightweight Interface to TIGER/Line Shapefiles

Version 0.0.10

Description Download geographic shapes from the United States Census Bureau TIGER/Line Shapefiles <https://www.census.gov/geographies/mapping-files/time-series/geo/tiger-line-file.html>.
Functions support downloading and reading in geographic boundary data.
All downloads can be set up with a cache to avoid multiple downloads.
Data is available back to 2000 for most geographies.

License MIT + file LICENSE

Depends R (>= 2.10)

Imports cli, glue, curl, sf

Suggests knitr, rappdirs, rmarkdown, testthat (>= 3.0.0)

Encoding UTF-8

RoxygenNote 7.3.2

LazyData true

URL https://github.com/alarm-redist/tinytiger,
https://alarm-redist.org/tinytiger/

BugReports https://github.com/alarm-redist/tinytiger/issues

Config/testthat/edition 3

VignetteBuilder knitr

NeedsCompilation no

Author Christopher T. Kenny [aut, cre] (ORCID:
<https://orcid.org/0000-0002-9386-6860>),
Cory McCartan [aut]

Maintainer Christopher T. Kenny <christopherkenny@fas.harvard.edu>

Repository CRAN

Date/Publication 2025-04-30 02:30:01 UTC

Contents

county_fips_2020 . . . 3
tt_address_ranges . . . 3
tt_ai_an_nh_areas . . . 4
tt_anrc . . . 4
tt_area_landmarks . . . 5
tt_area_water . . . 5
tt_blocks . . . 6
tt_block_groups . . . 6
tt_cache_size . . . 7
tt_cbsa . . . 8
tt_coastline . . . 8
tt_congressional_districts . . . 9
tt_consolidated_cities . . . 9
tt_counties . . . 10
tt_county_subdivisions . . . 11
tt_csa . . . 11
tt_elementary_school_districts . . . 12
tt_estates . . . 12
tt_linear_water . . . 13
tt_metropolitan_divisions . . . 14
tt_military . . . 14
tt_new_england_cities . . . 15
tt_new_england_city_divisions . . . 15
tt_new_england_combined_areas . . . 16
tt_places . . . 16
tt_point_landmarks . . . 17
tt_polygon_edges . . . 17
tt_polygon_faces . . . 18
tt_primary_roads . . . 19
tt_primary_secondary_roads . . . 19
tt_puma . . . 20
tt_rails . . . 20
tt_roads . . . 21
tt_secondary_school_districts . . . 21
tt_states . . . 22
tt_state_leg_lower . . . 23
tt_state_leg_upper . . . 23
tt_subbarrios . . . 24
tt_tracts . . . 24
tt_tribal_block_groups . . . 25
tt_tribal_subdivisions . . . 25
tt_tribal_tracts . . . 26
tt_uac . . . 27
tt_unified_school_districts . . . 27
tt_voting_districts . . . 28
tt_zcta . . . 28

Index **30**

`county_fips_2020` *Counties FIPS 2020*

Description

Contains three columns:

- state: state FIPS
- county: county FIPS
- name: county name

Usage

```
data("county_fips_2020")
```

Value

tibble

`tt_address_ranges` *Download TIGER shapes for Address Ranges*

Description

Download TIGER shapes for Address Ranges

Usage

```
tt_address_ranges(state, county, year = 2024)
```

Arguments

`state`	FIPS, postal codes, or full names of states.
`county`	FIPS codes or full names of counties. Optional.
`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_address_ranges("DE", county = "001")) # downloads slow on CRAN
```

tt_ai_an_nh_areas *Download TIGER shapes for American Indian / Alaska Native / Native Hawaiian Areas*

Description

Download TIGER shapes for American Indian / Alaska Native / Native Hawaiian Areas

Usage

```
tt_ai_an_nh_areas(year = 2024)
```

Arguments

year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_ai_an_nh_areas())
```

tt_anrc *Download TIGER shapes for Alaska Native Regional Corporation (Alaska)*

Description

Download TIGER shapes for Alaska Native Regional Corporation (Alaska)

Usage

```
tt_anrc(year = 2024)
```

Arguments

year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_anrc()) # downloads slow on CRAN
```

tt_area_landmarks *Download TIGER shapes for Area Landmarks*

Description

Download TIGER shapes for Area Landmarks

Usage

```
tt_area_landmarks(state, year = 2024)
```

Arguments

state	FIPS, postal codes, or full names of states.
year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_area_landmarks("DE")) # downloads slow on CRAN
```

tt_area_water *Download TIGER Shapes for Area Water*

Description

Download TIGER Shapes for Area Water

Usage

```
tt_area_water(state, county, year = 2024)
```

Arguments

state	FIPS, postal codes, or full names of states.
county	FIPS codes or full names of counties. Optional.
year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_area_water("DE")) # downloads slow on CRAN
```

`tt_blocks` *Download TIGER shapes for blocks*

Description

Download TIGER shapes for blocks

Usage

```
tt_blocks(state, county, year = 2024)
```

Arguments

`state`	FIPS, postal codes, or full names of states.
`county`	FIPS codes or full names of counties. Optional.
`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_blocks(state = "DE", county = "001"))
```

`tt_block_groups` *Download TIGER shapes for block groups*

Description

Download TIGER shapes for block groups

Usage

```
tt_block_groups(state, county, year = 2024)
```

Arguments

`state`	FIPS, postal codes, or full names of states.
`county`	FIPS codes or full names of counties. Optional.
`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_block_groups(state = "DE", county = "001")) # downloads slow on CRAN
```

`tt_cache_size` *Work with the the* `tinytiger` *cache*

Description

Functions to inspect and clear the cache. If the cache is not enabled, uses a temporary directory.

Usage

```
tt_cache_size()

tt_cache_clear(force = FALSE)

tt_cache_path()
```

Arguments

`force`	FALSE by default. Asks the user to confirm if interactive. Does not clear cache if force is FALSE and not interactive.

Value

For `tt_cache_size()`, tthe size in bytes, invisbly

For `tt_cache_clear()`, the path to the cache, invisbly.

For `tt_cache_path()`, the path to the cache

Examples

```
tt_cache_size()

tt_cache_clear()

tt_cache_path()
```

tt_cbsa *Download TIGER shapes for Core Based Statistical Areas*

Description

Download TIGER shapes for Core Based Statistical Areas

Usage

```
tt_cbsa(year = 2021)
```

Arguments

year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
 # takes > 5 seconds
# Wrapped in try due to false positive 304 errors
try(tt_cbsa()) # downloads slow on CRAN
```

tt_coastline *Download TIGER shapes for Coastlines*

Description

Download TIGER shapes for Coastlines

Usage

```
tt_coastline(year = 2024)
```

Arguments

year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
 # takes > 5 seconds
# Wrapped in try due to false positive 304 errors
try(tt_coastline()) # downloads slow on CRAN
```

`tt_congressional_districts`

Download TIGER shapes for congressional districts

Description

Download TIGER shapes for congressional districts

Usage

```
tt_congressional_districts(state, year = 2024)
```

Arguments

`state`	FIPS, postal codes, or full names of states.
`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
 # takes > 5 seconds
# Wrapped in try due to false positive 304 errors
try(tt_congressional_districts()) # downloads slow on CRAN
```

`tt_consolidated_cities`

Download TIGER shapes for Public Use Microdata Areas

Description

Download TIGER shapes for Public Use Microdata Areas

Usage

```
tt_consolidated_cities(state, year = 2024)
```

Arguments

state	FIPS, postal codes, or full names of states.
year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_consolidated_cities("CT")) # downloads slow on CRAN
```

---

tt_counties *Download TIGER shapes for counties*

Description

Download TIGER shapes for counties

Usage

```
tt_counties(state, year = 2024)
```

Arguments

state	FIPS, postal codes, or full names of states.
year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
 # takes > 5 seconds
# Wrapped in try due to false positive 304 errors
try(tt_counties(state = "DE")) # downloads slow on CRAN
```

tt_county_subdivisions *Download TIGER shapes for County Subdivisions*

Description

Download TIGER shapes for County Subdivisions

Usage

```
tt_county_subdivisions(state, year = 2024)
```

Arguments

state	FIPS, postal codes, or full names of states.
year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_county_subdivisions("DE")) # downloads slow on CRAN
```

tt_csa *Download TIGER shapes for Combined Statistical Area*

Description

Download TIGER shapes for Combined Statistical Area

Usage

```
tt_csa(year = 2021)
```

Arguments

year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_csa())
```

`tt_elementary_school_districts` *Download TIGER shapes for Elementary School Districts*

Description

Download TIGER shapes for Elementary School Districts

Usage

```
tt_elementary_school_districts(state, year = 2024)
```

Arguments

`state`	FIPS, postal codes, or full names of states.
`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_elementary_school_districts("AZ")) # downloads slow on CRAN
```

`tt_estates` *Download TIGER shapes for Estates (US Virgin Islands)*

Description

Download TIGER shapes for Estates (US Virgin Islands)

Usage

```
tt_estates(year = 2024)
```

Arguments

`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_estates()) # downloads slow on CRAN
```

`tt_linear_water` *Download TIGER Shapes for Linear Water*

Description

Download TIGER Shapes for Linear Water

Usage

```
tt_linear_water(state, county, year = 2024)
```

Arguments

`state`	FIPS, postal codes, or full names of states.
`county`	FIPS codes or full names of counties. Optional.
`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_linear_water("DE")) # downloads slow on CRAN
```

tt_metropolitan_divisions *Download TIGER shapes for Metropolitan Divisions*

Description

Download TIGER shapes for Metropolitan Divisions

Usage

```
tt_metropolitan_divisions(year = 2021)
```

Arguments

year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_metropolitan_divisions()) # downloads slow on CRAN
```

tt_military *Download TIGER shapes for Military Installations*

Description

Download TIGER shapes for Military Installations

Usage

```
tt_military(year = 2024)
```

Arguments

year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_military()) # downloads slow on CRAN
```

tt_new_england_cities *Download TIGER shapes for New England City and Town Area*

Description

Download TIGER shapes for New England City and Town Area

Usage

```
tt_new_england_cities(year = 2024)
```

Arguments

year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_new_england_cities()) # downloads slow on CRAN
```

tt_new_england_city_divisions *Download TIGER shapes for New England City and Town Area Divisions*

Description

Download TIGER shapes for New England City and Town Area Divisions

Usage

```
tt_new_england_city_divisions(year = 2021)
```

Arguments

year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_new_england_city_divisions()) # downloads slow on CRAN
```

tt_new_england_combined_areas *Download TIGER shapes for New England Combined City and Town Areas*

Description

Download TIGER shapes for New England Combined City and Town Areas

Usage

```
tt_new_england_combined_areas(year = 2021)
```

Arguments

year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_new_england_combined_areas()) # downloads slow on CRAN
```

tt_places *Download TIGER shapes for Places*

Description

Download TIGER shapes for Places

Usage

```
tt_places(state, year = 2024)
```

Arguments

state	FIPS, postal codes, or full names of states.
year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_places("DE")) # downloads slow on CRAN
```

`tt_point_landmarks` *Download TIGER shapes for Point Landmarks*

Description

Download TIGER shapes for Point Landmarks

Usage

```
tt_point_landmarks(state, year = 2024)
```

Arguments

`state`	FIPS, postal codes, or full names of states.
`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_point_landmarks("DE")) # downloads slow on CRAN
```

`tt_polygon_edges` *Download TIGER shapes for Polygon Edges*

Description

Download TIGER shapes for Polygon Edges

Usage

```
tt_polygon_edges(state, county, year = 2024)
```

Arguments

`state`	FIPS, postal codes, or full names of states.
`county`	FIPS codes or full names of counties. Optional.
`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_polygon_edges("DE", county = "001")) # downloads slow on CRAN
```

`tt_polygon_faces` *Download TIGER shapes for Polygon Faces*

Description

Download TIGER shapes for Polygon Faces

Usage

```
tt_polygon_faces(state, county, year = 2024)
```

Arguments

`state`	FIPS, postal codes, or full names of states.
`county`	FIPS codes or full names of counties. Optional.
`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_polygon_faces("DE", county = "001")) # downloads slow on CRAN
```

tt_primary_roads *Download TIGER shapes for Primary Roads*

Description

Download TIGER shapes for Primary Roads

Usage

```
tt_primary_roads(year = 2024)
```

Arguments

year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
 # takes > 5 seconds
# Wrapped in try due to false positive 304 errors
try(tt_primary_roads()) # downloads slow on CRAN
```

tt_primary_secondary_roads *Download TIGER shapes for Primary and Secondary Roads*

Description

Download TIGER shapes for Primary and Secondary Roads

Usage

```
tt_primary_secondary_roads(state, year = 2024)
```

Arguments

state	FIPS, postal codes, or full names of states.
year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_primary_secondary_roads("DE")) # downloads slow on CRAN
```

`tt_puma` *Download TIGER shapes for Public Use Microdata Areas*

Description

Download TIGER shapes for Public Use Microdata Areas

Usage

```
tt_puma(state, year = 2024)
```

Arguments

`state`	FIPS, postal codes, or full names of states.
`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_puma("DE")) # downloads slow on CRAN
```

`tt_rails` *Download TIGER shapes for Rails*

Description

Download TIGER shapes for Rails

Usage

```
tt_rails(year = 2024)
```

Arguments

`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
 # takes > 5 seconds
# Wrapped in try due to false positive 304 errors
try(tt_rails()) # downloads slow on CRAN
```

`tt_roads` *Download TIGER shapes for Roads*

Description

Download TIGER shapes for Roads

Usage

```
tt_roads(state, county, year = 2024)
```

Arguments

`state`	FIPS, postal codes, or full names of states.
`county`	FIPS codes or full names of counties. Optional.
`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_roads("DE")) # downloads slow on CRAN
```

`tt_secondary_school_districts`
Download TIGER shapes for Secondary School Districts

Description

Download TIGER shapes for Secondary School Districts

Usage

```
tt_secondary_school_districts(state, year = 2024)
```

Arguments

state	FIPS, postal codes, or full names of states.
year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_secondary_school_districts("AZ")) # downloads slow on CRAN
```

---

tt_states *Download TIGER shapes for states*

Description

Download TIGER shapes for states

Usage

```
tt_states(year = 2024)
```

Arguments

year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_states())
```

tt_state_leg_lower *Download TIGER shapes for lower state legislative districts*

Description

Download TIGER shapes for lower state legislative districts

Usage

```
tt_state_leg_lower(state, year = 2024)
```

Arguments

state	FIPS, postal codes, or full names of states.
year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_state_leg_lower("DE")) # downloads slow on CRAN
```

tt_state_leg_upper *Download TIGER shapes for upper state legislative districts*

Description

Download TIGER shapes for upper state legislative districts

Usage

```
tt_state_leg_upper(state, year = 2024)
```

Arguments

state	FIPS, postal codes, or full names of states.
year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_state_leg_lower("DE")) # downloads slow on CRAN
```

`tt_subbarrios` *Download TIGER shapes for Subbarrios (Puerto Rico)*

Description

Download TIGER shapes for Subbarrios (Puerto Rico)

Usage

```
tt_subbarrios(year = 2024)
```

Arguments

`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_subbarrios()) # downloads slow on CRAN
```

`tt_tracts` *Download TIGER shapes for tracts*

Description

Download TIGER shapes for tracts

Usage

```
tt_tracts(state, county, year = 2024)
```

Arguments

`state`	FIPS, postal codes, or full names of states.
`county`	FIPS codes or full names of counties. Optional.
`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_tracts(state = "DE", county = "001")) # downloads slow on CRAN
```

`tt_tribal_block_groups` *Download TIGER shapes for Tribal Block Groups*

Description

Download TIGER shapes for Tribal Block Groups

Usage

```
tt_tribal_block_groups(year = 2024)
```

Arguments

`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_tribal_block_groups())
```

`tt_tribal_subdivisions` *Download TIGER shapes for American Indian Tribal Subdivision National*

Description

Download TIGER shapes for American Indian Tribal Subdivision National

Usage

```
tt_tribal_subdivisions(year = 2024)
```

Arguments

year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_tribal_subdivisions())
```

---

tt_tribal_tracts *Download TIGER shapes for Tribal Tracts*

Description

Download TIGER shapes for Tribal Tracts

Usage

```
tt_tribal_tracts(year = 2024)
```

Arguments

year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_tribal_tracts())
```

tt_uac *Download TIGER shapes for Urban Area*

Description

Download TIGER shapes for Urban Area

Usage

```
tt_uac(year = 2024)
```

Arguments

year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
 # takes > 5 seconds
# Wrapped in try due to false positive 304 errors
try(tt_uac()) # downloads slow on CRAN
```

tt_unified_school_districts *Download TIGER shapes for Unified School Districts*

Description

Download TIGER shapes for Unified School Districts

Usage

```
tt_unified_school_districts(state, year = 2024)
```

Arguments

state	FIPS, postal codes, or full names of states.
year	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_unified_school_districts("DE")) # downloads slow on CRAN
```

`tt_voting_districts` *Download TIGER shapes for Voting Districts*

Description

Download TIGER shapes for Voting Districts

Usage

```
tt_voting_districts(state, county, year = 2024)
```

Arguments

`state`	FIPS, postal codes, or full names of states.
`county`	FIPS codes or full names of counties. Optional.
`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
# Wrapped in try due to false positive 304 errors
try(tt_voting_districts("DE", county = "001")) # downloads slow on CRAN
```

`tt_zcta` *Download TIGER shapes for Zip Code Tabulation Areas*

Description

Download TIGER shapes for Zip Code Tabulation Areas

Usage

```
tt_zcta(year = 2024)
```

Arguments

`year`	Integer year. Required. 2000 and 2010-2022 are currently supported.

Value

sf data.frame

Examples

```
 # takes > 5 seconds
# Wrapped in try due to false positive 304 errors
try(tt_zcta()) # downloads slow on CRAN
```

Index

∗ **cities**
  tt_consolidated_cities, 9
  tt_county_subdivisions, 11
  tt_places, 16
  tt_puma, 20
∗ **city**
  tt_new_england_cities, 15
  tt_new_england_city_divisions, 15
  tt_new_england_combined_areas, 16
∗ **data**
  county_fips_2020, 3
∗ **districts**
  tt_congressional_districts, 9
  tt_state_leg_lower, 23
  tt_state_leg_upper, 23
  tt_voting_districts, 28
∗ **landmarks**
  tt_area_landmarks, 5
  tt_point_landmarks, 17
∗ **other**
  tt_address_ranges, 3
  tt_cache_size, 7
  tt_cbsa, 8
  tt_csa, 11
  tt_estates, 12
  tt_metropolitan_divisions, 14
  tt_military, 14
  tt_polygon_edges, 17
  tt_polygon_faces, 18
  tt_subbarrios, 24
  tt_uac, 27
  tt_zcta, 28
∗ **roads**
  tt_primary_roads, 19
  tt_primary_secondary_roads, 19
  tt_rails, 20
  tt_roads, 21
∗ **schools**
  tt_elementary_school_districts, 12
  tt_secondary_school_districts, 21
  tt_unified_school_districts, 27
∗ **spine**
  tt_block_groups, 6
  tt_blocks, 6
  tt_counties, 10
  tt_states, 22
  tt_tracts, 24
∗ **tribal**
  tt_ai_an_nh_areas, 4
  tt_anrc, 4
  tt_tribal_block_groups, 25
  tt_tribal_subdivisions, 25
  tt_tribal_tracts, 26
∗ **water**
  tt_area_water, 5
  tt_coastline, 8
  tt_linear_water, 13

county_fips_2020, 3

tt_address_ranges, 3
tt_ai_an_nh_areas, 4
tt_anrc, 4
tt_area_landmarks, 5
tt_area_water, 5
tt_block_groups, 6
tt_blocks, 6
tt_cache_clear *(*tt_cache_size*)*, 7
tt_cache_path *(*tt_cache_size*)*, 7
tt_cache_size, 7
tt_cbsa, 8
tt_coastline, 8
tt_congressional_districts, 9
tt_consolidated_cities, 9
tt_counties, 10
tt_county_subdivisions, 11
tt_csa, 11
tt_elementary_school_districts, 12
tt_estates, 12

tt_linear_water, 13
tt_metropolitan_divisions, 14
tt_military, 14
tt_new_england_cities, 15
tt_new_england_city_divisions, 15
tt_new_england_combined_areas, 16
tt_places, 16
tt_point_landmarks, 17
tt_polygon_edges, 17
tt_polygon_faces, 18
tt_primary_roads, 19
tt_primary_secondary_roads, 19
tt_puma, 20
tt_rails, 20
tt_roads, 21
tt_secondary_school_districts, 21
tt_state_leg_lower, 23
tt_state_leg_upper, 23
tt_states, 22
tt_subbarrios, 24
tt_tracts, 24
tt_tribal_block_groups, 25
tt_tribal_subdivisions, 25
tt_tribal_tracts, 26
tt_uac, 27
tt_unified_school_districts, 27
tt_voting_districts, 28
tt_zcta, 28