

Package ‘tubern’

July 22, 2025

Title R Client for the YouTube Analytics and Reporting API

Version 0.2.1

Maintainer Gaurav Sood <gsood07@gmail.com>

Description Get statistics and reports from YouTube. To learn more about the YouTube Analytics and Reporting API, see <<https://developers.google.com/youtube/reporting/>>.

URL <https://github.com/gojiplus/tubern>

BugReports <https://github.com/gojiplus/tubern/issues>

Depends R (>= 4.1.0)

License MIT + file LICENSE

Encoding UTF-8

Imports httr, jsonlite

VignetteBuilder knitr

Suggests knitr (>= 1.11), testthat, rmarkdown, xml2, lintr

RoxygenNote 7.3.2

NeedsCompilation no

Author Gaurav Sood [aut, cre]

Repository CRAN

Date/Publication 2025-03-24 18:50:02 UTC

Contents

add_groups	2
add_group_item	3
delete_group	3
delete_group_item	4
get_report	5
list_groups	6
list_group_items	7
tubern	8

tubern_DELETE	8
tubern_GET	9
tubern_POST	9
tubern_PUT	10
update_group	10
yt_check_token	11
yt_oauth	11
Index	13

add_groups	<i>Add Groups</i>
------------	-------------------

Description

Add Groups

Usage

add_groups(resource_details, ...)

Arguments

- resource_details
Named nested list. Required. Must provide: etag, snippet title and contentDetails itemType
- ...
Additional arguments passed to [tubern_POST](#).

Value

named list

References

<https://developers.google.com/youtube/analytics/v1/reference/groups/insert>

Examples

```
## Not run:  
add_groups(list(etag="vponEBg8hrR1yBUX0Hz66Uc5WMk/vyGp6PvFo4RvsFtPoIWecReyIC8",  
ContentDetails = list(itemType="youtube#channel"), snippet = list(title ="hello")))  
  
## End(Not run)
```

add_group_item	<i>Add Group Item</i>
----------------	-----------------------

Description

Add Group Item

Usage

```
add_group_item(resource_details, ...)
```

Arguments

resource_details	
	Named nested list. Required. Must provide: groupId, resource.id
...	Additional arguments passed to tubern_POST .

Value

named list

References

<https://developers.google.com/youtube/analytics/v1/reference/groupItems/insert>

Examples

```
## Not run:  
add_group_item(list(groupId = "", resouce.id ="hello"))  
  
## End(Not run)
```

delete_group	<i>Delete Group</i>
--------------	---------------------

Description

Delete Group

Usage

```
delete_group(id, ...)
```

Arguments

- id String. Required. “The id parameter specifies the YouTube group ID of the group that is being deleted.”
- ... Additional arguments passed to [tubern_PUT](#).

Value

named list

References

<https://developers.google.com/youtube/analytics/v1/reference/groups/delete>

Examples

```
## Not run:  
delete_group(id="ABZZzGSIAAA")  
  
## End(Not run)
```

delete_group_item	<i>Delete Group</i>
-------------------	---------------------

Description

Delete Group

Usage

```
delete_group_item(id, ...)
```

Arguments

- id String. Required. “The id parameter specifies the YouTube group item ID for the group that is being deleted.”
- ... Additional arguments passed to [tubern_PUT](#).

Value

named list

References

<https://developers.google.com/youtube/analytics/v1/reference/groupItems/delete>

Examples

```
## Not run:
delete_group_item(id="ABZZzGSIAAA")

## End(Not run)
```

get_report

*Get Reports***Description**

Lists reporting jobs that have been scheduled for a channel or content owner.

Usage

```
get_report(
  ids,
  metrics,
  start_date = NULL,
  end_date = NULL,
  currency = NULL,
  dimensions,
  filters,
  historical_channel_data = NULL,
  max_results = NULL,
  sort = NULL,
  start_index = NULL,
  user_ip = NULL,
  ...
)
```

Arguments

ids	Named vector with two potential names: channel or contentOwner If channel, potential values are: mine or channel_id If contentOwner, potential values are: owner_id of the content
metrics	String. Comma-separated list of YouTube Analytics metrics, such as views or likes, dislikes.
start_date	String. Must be in YYYY-MM-DD format.
end_date	String. Must be in YYYY-MM-DD format.
currency	Optional. String. Default is USD. Specifies what earnings metrics like earnings, adEarnings, grossRevenue, playbackBasedCpm, impressionBasedCpm will be reported in.
dimensions	String. Optional. Comma-separated list of YouTube Analytics dimensions, such as video or ageGroup, gender.

filters	Named Vector. Optional. For instance, “video==pd1FJh59zxQ,Zhawgd0REhA;country==IT restricts the result set to include data for the given videos in Italy”
historical_channel_data	Boolean. Defaults is False. “Whether the API response should include channels’ watch time and view data from the time period prior to when the channels were linked to the content owner.”
max_results	Integer. Optional. The maximum number of rows to include in the response.
sort	String. Optional A comma-separated list of dimensions or metrics that determine the sort order for YouTube
start_index	Integer. Optional. “The 1-based index of the first entity to retrieve.”
user_ip	“IP address of the end user for whom the API call is being made.”
...	Additional arguments passed to tubern_GET .

Value

named list

References

<https://developers.google.com/youtube/analytics/v1/reference/reports/query>

Examples

```
## Not run:
get_report(ids = "channel==MINE", metrics = "views",
start_date = "2010-04-01", end_date ="2017-01-01")

## End(Not run)
```

list_groups	List Groups
-------------	-------------

Description

List Groups

Usage

```
list_groups(filter, page_token, ...)
```

Arguments

filter	Named Vector. Required. Only One of the two: id or mine. id “The Named parameter specifies a comma-separated list of the YouTube group ID(s) for the resource(s) that are being retrieved.” mine String. Can be 'True' or 'False.' “Set this parameter’s value to true to retrieve all groups owned by the authenticated user.”
page_token	String. Optional. “Identifies a specific page in the result set that should be returned.”
...	Additional arguments passed to tubern_GET .

Value

named list

References

<https://developers.google.com/youtube/analytics/v1/reference/groups/list>

Examples

```
## Not run:  
list_groups(filter = c(mine = 'True'))  
  
## End(Not run)
```

list_group_items	<i>List Group Items</i>
------------------	-------------------------

Description

List Group Items

Usage

```
list_group_items(group_id, ...)
```

Arguments

group_id	String. Required. ID of the group
...	Additional arguments passed to tubern_GET .

Value

named list

References

<https://developers.google.com/youtube/analytics/v1/reference/groupItems/list>

Examples

```
## Not run:
list_group_items(group_id = "vponEBg8hrR1yBUX0Hz66Uc5WMk/vyGp6PvFo4RvsFtPoIWeCReyIC8")

## End(Not run)
```

tubern	tubern provides access to the YouTube Analytics and Reporting API
--------	--

Description

Get statistics and reports from YouTube. To learn more about the YouTube Analytics and Reporting API, see <https://developers.google.com/youtube/reporting/>.

Author(s)

Maintainer: Gaurav Sood <gsood07@gmail.com>

See Also

- Useful links:
- <https://github.com/gojipius/tubern>
 - Report bugs at <https://github.com/gojipius/tubern/issues>

tubern_DELETE	<i>DELETE</i>
---------------	---------------

Description

DELETE

Usage

```
tubern_DELETE(path, query = NULL, body = "", ...)
```

Arguments

- | | |
|-------|---|
| path | path to specific API request URL |
| query | query list |
| body | passing image through body |
| ... | Additional arguments passed to DELETE . |

Value

list

tubern_GET	<i>Base POST AND GET functions. Not exported.</i>
------------	---

Description

GET

Usage

```
tubern_GET(path, query = NULL, ...)
```

Arguments

path	path to specific API request URL
query	query list
...	Additional arguments passed to GET .

Value

list

tubern_POST	<i>POST</i>
-------------	-------------

Description

POST

Usage

```
tubern_POST(path, query = NULL, body = "", ...)
```

Arguments

path	path to specific API request URL
query	query list
body	passing image through body
...	Additional arguments passed to POST .

Value

list

tubern_PUT	<i>PUT</i>
------------	------------

Description

PUT

Usage

tubern_PUT(path, query = NULL, body = "", ...)

Arguments

path	path to specific API request URL
query	query list
body	passing image through body
...	Additional arguments passed to PUT .

Value

list

update_group	<i>Update Groups</i>
--------------	----------------------

Description

Update Groups

Usage

update_group(resource_details, ...)

Arguments

resource_details	
	Named nested list. Required. Must provide: id, snippet title
...	Additional arguments passed to tubern_PUT .

Value

named list

References

<https://developers.google.com/youtube/analytics/v1/reference/groups/update>

Examples

```
## Not run:
update_group(list(id="ABZZzGSIAAA", snippet = list(title="hello")))

## End(Not run)
```

yt_check_token	<i>Check if authentication token is in options</i>
----------------	--

Description

Check if authentication token is in options

Usage

```
yt_check_token()
```

yt_oauth	<i>Set up Authorization</i>
----------	-----------------------------

Description

The function looks for .httr-oauth in the working directory. If it doesn't find it, it expects an application ID and a secret. If you want to remove the existing .httr-oauth, set `remove_old_oauth` to TRUE. By default, it is set to FALSE. The function launches a browser to allow you to authorize the application

Usage

```
yt_oauth(
  app_id = NULL,
  app_secret = NULL,
  scope = "analytics",
  token = ".httr-oauth",
  ...
)
```

Arguments

app_id	client id; required; no default
app_secret	client secret; required; no default
scope	Character. analytics or monetary-analytics. Required. Default is monetary-analytics. The scopes are largely exchangeable but monetary-analytics yields extra authorizations that come in handy.

token	path to file containing the token. If a path is given, the function will first try to read from it. Default is <code>.httr-oauth</code> in the local directory. So if there is such a file, the function will first try to read from it.
...	Additional arguments passed to <code>oauth2.0_token</code>

Value

sets the `google_token` option and also saves `.httr_auth` in the working directory (find out the working directory via `getwd()`)

References

<https://developers.google.com/youtube/analytics/v1/reference/>

<https://developers.google.com/youtube/analytics/v1/reference/> for different scopes

Examples

```
## Not run:
yt_oauth("998136489867-5t3tq1g7hbovoj46dreqd6k5kd35ctjn.apps.googleusercontent.com",
         "Mb0St6cQhhFkwETXKur-L9rN")

## End(Not run)
```

Index

`add_group_item`, [3](#)
`add_groups`, [2](#)

`DELETE`, [8](#)
`delete_group`, [3](#)
`delete_group_item`, [4](#)

`GET`, [9](#)
`get_report`, [5](#)

`list_group_items`, [7](#)
`list_groups`, [6](#)

`oauth2.0_token`, [12](#)

`POST`, [9](#)
`PUT`, [10](#)

`tubern`, [8](#)
`tubern-package (tubern)`, [8](#)
`tubern_DELETE`, [8](#)
`tubern_GET`, [6](#), [7](#), [9](#)
`tubern_POST`, [2](#), [3](#), [9](#)
`tubern_PUT`, [4](#), [10](#), [10](#)

`update_group`, [10](#)

`yt_check_token`, [11](#)
`yt_oauth`, [11](#)