

Package ‘voronoiTreemap’

July 22, 2025

Type Package

Title Voronoi Treemaps with Added Interactivity by Shiny

Version 0.2.0

Date 2019-01-08

Description The d3.js framework with the plugins d3-voronoi-map, d3-voronoi-treemap and d3-weighted-voronoi are used to generate Voronoi treemaps in R and in a shiny application. The computation of the Voronoi treemaps are based on Nocaj and Brandes (2012) <[doi:10.1111/j.1467-8659.2012.03078.x](https://doi.org/10.1111/j.1467-8659.2012.03078.x)>.

URL <https://github.com/uRosConf/voronoiTreemap>

License GPL-3

Imports data.tree, rlang, htmlwidgets, shiny, shinyjs, DT

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

Suggests rmarkdown, scales, testthat

NeedsCompilation no

Author Alexander Kowarik [aut, cre] (ORCID: <<https://orcid.org/0000-0001-8598-4130>>),
Bernhard Meindl [aut],
Malaver Vojvodic [aut],
Mike Bostock [aut, cph] (d3.js library, <http://d3js.org>),
Franck Lebeau [aut, cph] (d3-voronoi-treemap library, <https://github.com/Kcnarf/d3-voronoi-treemap>)

Maintainer Alexander Kowarik <alexander.kowarik@statistik.gv.at>

Repository CRAN

Date/Publication 2019-01-11 17:00:03 UTC

Contents

canada	2
ExampleGDP	3
vt_add_nodes	3
vt_app	4
vt_create_node	5
vt_d3	5
vt_d3-shiny	7
vt_export_json	7
vt_input_from_df	8
vt_testdata	9
Index	10

canada	<i>canada</i>
--------	---------------

Description

An example data.frame using Canadian Consumer Price Index (CPI) to demonstrate the voronoiTree package

Usage

data(canada)

Format

- A data frame with 247 rows and 5 variables:
- h1** Name of first-level (region)
 - h2** Leaf names of second-level (elementary_aggregate)
 - h3** Leaf names of third-level values (intermediate_aggregate)
 - color** colors in which the plot-regions will be filled
 - weight** CPI in percent of the overall total
 - codes** NAs

Examples

data("canada")
head(canada)

ExampleGDP	<i>ExampleGDP</i>
------------	-------------------

Description

An example data.frame using GDP data to demonstrate the voronoiTree package

Usage

```
data(ExampleGDP)
```

Format

- A data frame with 42 rows and 6 variables:
- h1** Name of first-level (redundant)
 - h2** Leaf names of second-level (continents)
 - h3** Leaf names of third-level values (countries)
 - color** colors in which the plot-regions will be filled
 - weight** GDP values in percent of the overall total
 - codes** short labels used for overlays in plotting

Examples

```
data("ExampleGDP")
head(ExampleGDP)
```

vt_add_nodes	<i>vt_add_nodes</i>
--------------	---------------------

Description

add (sub)nodes to a node generated by [vt_create_node](#) or returned from [vt_add_nodes](#)

Usage

```
vt_add_nodes(node, refnode, node_names, colors = NULL, weights = NULL,
             codes = NULL)
```

Arguments

- | | |
|------------|---|
| node | a node object |
| refnode | name of the reference node |
| node_names | new node names |
| colors | optionally a vector of colors matching the length of node_names |
| weights | optionally a vector of weights matching the length of node_names |
| codes | optionally a vector of short labels matching the length of node_names |

Value

a Node object

Examples

```
n <- vt_create_node("Total")
n <- vt_add_nodes(n, refnode="Total", node_names=c("Asia", "Europe"), colors=c("red", "blue"))
n <- vt_add_nodes(n, refnode="Asia", node_names=c("China", "Thailand"),
  weights=c(0.5, 0.8), codes=c("CN", "TH"))
n <- vt_add_nodes(n, refnode="Europe", node_names=c("Netherlands", "Austria"),
  weights=c(0.9, 1.1), codes=c("NL", "AT"))
print(n, "weight", "code", "color")
```

vt_app

vt_app

Description

starts the graphical user interface developed with *shiny*.

Usage

```
vt_app(maxRequestSize = 50, ...)
```

Arguments

`maxRequestSize` (numeric) number defining the maximum allowed filesize (in megabytes) for uploaded files, defaults to 50MB

`...` arguments (e.g host) that are passed through [vt_app](#) when starting the shiny application

Value

starts the interactive graphical user interface which may be used to perform the anonymisation process.

Examples

```
## Not run:
vt_app()

## End(Not run)
```

vt_create_node	<i>vt_create_node</i>
----------------	-----------------------

Description

vt_create_node

Usage

vt_create_node(total_lab = "Total")

Arguments

total_lab name of the total level

Value

a Node

Examples

vt_create_node("Total")

vt_d3	<i>Voronoi Treemap in an htmlwidget</i>
-------	---

Description

Function to generate an htmlwidget with a voronoi treemap

Usage

```
vt_d3(data, elementId = NULL, width = NULL, height = NULL,
      seed = NULL, title = NULL, legend = FALSE, legend_title = NULL,
      footer = NULL, label = TRUE, color_circle = "#aaaaaa",
      color_border = "#ffffff", color_label = "#000000",
      size_border = "1px", size_border_hover = "3px",
      size_circle = "2px")
```

Arguments

data	a correct json data object
elementId	optional a custom elementId to be returned
width	width of the widget
height	height of the widget
seed	if defined, the plot is fixed
title	NULL or a string for the title
legend	TRUE/FALSE if a legend should be printed
legend_title	NULL or a string for the title of the legend
footer	NULL or a string for the footer text
label	TRUE/FALSE if the labels should be printed
color_circle	color for the outer circle
color_border	color for the inner lines
color_label	color for the label in the plot
size_border	thickness of the borders in css style, e.g. '1px'
size_border_hover	thickness of the borders when hovering in css style, e.g. '3px'
size_circle	thickness of the circle in css style, e.g. '2px'

Note

The JavaScript library d3-voronoi treemap can be found here <https://github.com/Kcнарf/d3-voronoi-treemap> and the example is based on the remake of HowMuch.net's article 'The Global Economy by GDP' by _Kcнарf <https://bl.ocks.org/Kcнарf/fa95aa7b076f537c00aed614c29bb568>.

References

Arlind Nocaj and Ulrik Brandes. (2012). Computing Voronoi Treempas: Faster, Simpler and Resolution-independent. Computer Graphics Forum. Vol.31. 855-864.

Examples

```
vt_d3(vt_export_json(vt_testdata()))
data(ExampleGDP)
gdp_json <- vt_export_json(vt_input_from_df(ExampleGDP))
vt_d3(gdp_json)
data(canada)
canada$codes <- canada$h3
canada <- canada[canada$h1=="Canada",]
canadaH <- vt_input_from_df(canada,scaleToPerc = FALSE)
vt_d3(vt_export_json(canadaH))
#without label
vt_d3(vt_export_json(canadaH), label=FALSE)
#Example with coloring from scales package
library(scales)
```

```
canada$color <- seq_gradient_pal()(exp(canada$weight)/500)
canadaH <- vt_input_from_df(canada, scaleToPerc = FALSE)
vt_d3(vt_export_json(canadaH))
```

vt_d3-shiny

*Shiny bindings for d3vt***Description**

Output and render functions for using d3vt within Shiny applications and interactive Rmd documents.

Usage

```
vt_d3_output(outputId, width = "100%", height = "400px")
```

```
render_vt_d3(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

outputId	output variable to read from
width, height	Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended.
expr	An expression that generates a d3vt
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.

vt_export_json

*vt_export_json***Description**

exports a node to suitable json required by voronoi javascript function

Usage

```
vt_export_json(node, file = NULL)
```

Arguments

node	a Node object generated by vt_create_node or returned from vt_add_nodes
file	path where the json should be written to, if NULL, the json is returned as a character

Value

NULL or a character vector

See Also

vt_create_node vt_add_nodes

Examples

```
n <- vt_testdata()
vt_export_json(n)
vt_export_json(n, file=tempfile())
```

vt_input_from_df	<i>vt_input_from_df</i>
------------------	-------------------------

Description

create a tree-structure from a data.frame

Usage

```
vt_input_from_df(inp, scaleToPerc = FALSE)
```

Arguments

inp	a data.frame with specific format
scaleToPerc	(logical) scale to percent

Value

a Node that can be written to json using [vt_export_json](#)

Examples

```
## non yet
```

vt_testdata	<i>vt_testdata</i>
-------------	--------------------

Description

vt_testdata

Usage

vt_testdata()

Value

returns a json-string as in the example from <https://bl.ocks.org/Kcnarf/fa95aa7b076f537c00aed614c29bb568>

Examples

vt_testdata()

Index

* **datasets**

canada, [2](#)

ExampleGDP, [3](#)

canada, [2](#)

ExampleGDP, [3](#)

render_vt_d3 (vt_d3-shiny), [7](#)

vt_add_nodes, [3](#), [3](#), [7](#)

vt_app, [4](#), [4](#)

vt_create_node, [3](#), [5](#), [7](#)

vt_d3, [5](#)

vt_d3-shiny, [7](#)

vt_d3_output (vt_d3-shiny), [7](#)

vt_export_json, [7](#), [8](#)

vt_input_from_df, [8](#)

vt_testdata, [9](#)