

Package ‘wildpoker’

July 22, 2025

Title Best Hand Analysis for Poker Variants Including Wildcards

Version 1.1

Date 2016-01-25

Author Bradley Shanrock-Solberg

Maintainer Bradley Shanrock-Solberg <greblosb@gmail.com>

Description

Provides insight into how the best hand for a poker game changes based on the game dealt, players who stay in until the showdown and wildcards added to the base game. At this time the package does not support player tactics, so draw poker variants are not included.

License GPL-3

Depends R (>= 3.2), grDevices, graphics, utils

NeedsCompilation no

Repository CRAN

Date/Publication 2016-01-30 00:32:45

Contents

wildpoker-package	2
wpgame	3
wpgraphs	5
wpnotsupported	7
wprules	8
wpstats	9
wpsupportedgames	12

Index	14
--------------	-----------

wildpoker-package

Best Hand Analysis for Poker Variants Including Wildcards

Description

Provides insight into how the best hand for a poker game changes based on the game dealt, players who stay in until the showdown and wildcards added to the base game. At this time the package does not support player tactics, so draw poker variants are not included. This package provides insight into how the best hand for a poker game changes based on the following variables:

- Game Variant (which may include rules to split pot, wildcards that emerge in play, various dealing options)
- Player Number (a good hand changes significantly as more players are added to the game)
- Wildcards Added (additional wildcards incorporated beyond the basic game variant)

All hands are dealt completely and all players are assumed to stay in. Therefore the package makes no assumptions about betting strategy and largely because of this fact, poker variants involving drawing, discarding, passing or bidding on cards are not included at this time.

Details

The DESCRIPTION file:

```
Package:      wildpoker
Title:       Best Hand Analysis for Poker Variants Including Wildcards
Version:     1.1
Date:       2016-01-25
Author:      Bradley Shanrock-Solberg
Maintainer:  Bradley Shanrock-Solberg <greblosb@gmail.com>
Description: Provides insight into how the best hand for a poker game changes based on the game dealt, players who stay in
License:     GPL-3
Depends:     R (>= 3.2), grDevices, graphics, utils
```

Index of help topics:

wildpoker-package	Best Hand Analysis for Poker Variants Including Wildcards
wpgame	Play a Wild Poker Variant Game
wpgraphs	Wild Poker Graphs for Best Hand Analysis
wpnotsupported	Poker Games not supported by the wildpoker package
wprules	Display Wild Poker Variant Game Rules
wpstats	Deal Many Hands of a Wild Poker Variant Game
wpsupportedgames	Poker Games Supported by the wildpoker package

This package is organized into three specific functions and two data elements

- [wpgame](#) - Play a poker variant, see who won, game-level stats
- [wprules](#) - Display rules of a poker variant
- [wpstats](#) - Deal many games of a poker variant, capture statistics
- [wpgraphs](#) - Plot data from wpstats output into useful graphs
- [wpsupportedgames](#) - lists all supported games & basic description of each
- [wpnotsupported](#) - lists unsupported games & reason they are not yet included

For most purposes calling wpgraphs is sufficient - results have been precalculated for each supported game with from zero to 8 additional wildcards and from 2 to 8 players (or less, if a 52 card deck can not deal 8 hands), using 1000 hands dealt and a random number seed of 52.

Author(s)

Bradley Shanrock-Solberg Maintainer: Bradley Shanrock-Solberg <greblosb@gmail.com>

References

Shanrock-Solberg, B (2015) [Monte Carlo Methods for Decision Support \(or Winning More at Dealer's Choice Poker\)](#)

wpgame

Play a Wild Poker Variant Game

Description

This function will play a single game of a wildpoker variant, and return a visual display of the hands dealt to each player and/or community cards, a showdown matrix with the best hands chosen by each player, their score and pot percent won, as well as some game-level statistics.

Usage

```
wpgame(ngame, players, wcards = NULL)
```

Arguments

- | | |
|---------|--|
| ngame | This is any supported game, such as "Seven Card Stud" or "Baseball". See wpsupportedgames . |
| players | An integer value, must be at least 2 and is limited by the number of cards that can be physically dealt. (eg, Seven Card Stud has a max of 7 players) |
| wcards | A vector of string values which are either supported wildcard aliases or individual cards. These cards are in addition to any wildcards that are a natural part of the poker game variant chosen with "ngame". The table below shows the supported aliases and their individual card vector equivalents: <ul style="list-style-type: none"> • "Suicide King" or "KH" • "One Eyed Jacks" or c("JH", "JS") |

- "Deuces" or c("2H", "2C", "2D", "2S")
- "Heinz 57" or c("5H", "5C", "5D", "5S", "7H", "7C", "7D", "7S")
- "Pregnant Threes" or c("3H", "3C", "3D", "3S", "6H", "6C", "6D", "6S", "9H", "9C", "9D", "9S")
- "Dr Pepper" or c("2H", "2C", "2D", "2S", "4H", "4C", "4D", "4S", "10H", "10C", "10D", "10S")

Details

This program shuffles a deck, deals the cards and uses the cards allowed to each player to evaluate the best poker hand for both the main hand and (if the variant includes a split hand) the alternate hand, then presents the results in a list form, suitable to just display to a user, or pass along to another program

Value

A "pgame" list with the following structure:

\$ntable	A list of cards showing the deal visually, divided into \$Extra, \$Community and \$Players. Extra cards are not used in hands, but affect gameplay. Community cards are shared by all players. Player cards are used only by individual players, and may include hole cards (prefixed with a #). Wildcards are suffixed by a "w".
\$showdown	A data frame with one row per player (rowname), \$maintype and \$splitttype represent the type of hand used by the player, eg 3-Kind or 7-High. \$mainhand and \$splithand show the cards used in the hand, using the same format as \$ntable. \$mainscore and \$splitscore are calculated using the value of the cards in the hand, including "kickers", which allows two-pair Aces and 8s with Queen kicker to beat two-pair Aces and 8s with Jack kicker. The \$potpct column shows how much of the pot the individual player won. The sum of all \$potpct will be 1 if anybody won, but it is possible in some games for nobody to win, and nobody wins, all \$potpct will equal zero.
\$summary	A character vector with basic information \$game and \$wild capture the ngame and wcard parameters, \$mwtype and \$swtype capture the winning hands in the game
\$detail	A numeric vector with other statistics, \$mwscore and \$ssscore capture the winning scores, \$mssscore and \$ssscore capture the number of players whose hand score matched the winning hand, \$mstype and \$sstype capture the number of players whose hand type matched the winning hand, \$wdeck is the number of wildcards in the deck before the deal, \$wcdeal is the number of wildcards in play after the deal, pnum captures the players parameter, and \$mppct, \$sppct and \$bppct are used by wpstats to evaluate the effect of ties on pot percentage for each player who won either main pot, split pot or both.

Note

This function is intended to give a sense of how an individual game plays, as well as a way to test that the underlying model is correctly dealing the cards and assigning the best hands to the showdown for each player.

Author(s)

Maintainer: Bradley Shanrock-Solberg <greblosb@gmail.com>

References

[poker.com](#) has an excellent reference on game variants which was the primary source for games rules not encountered in my own play.

See Also

[wpstats](#)

Examples

```
set.seed(52)
wpgame("Iron Cross Last Wild", 6, "Deuces")
wpgame("Seven Stud Hi-Lo", 4, c("6C", "Suicide King"))
wpgame("Low Chicago", 4)
```

wpgraphs

Wild Poker Graphs for Best Hand Analysis

Description

This function presents an array of graphs which indicate how hand types compare for a given wild poker variant.

Usage

```
wpgraphs(gstat, ngame=NULL, players=NULL, wcnnum=NULL,
         stats=FALSE, gtype="Default", split="Vertical")
```

Arguments

- | | |
|---------|---|
| gstat | a gstat (graph stats) object generated by the wpstats function. If this parameter exists, ngame, players and wcnnum are not used. |
| ngame | This is any supported game, such as "Seven Card Stud" or "Baseball". See wpsupportedgames . |
| players | An integer value, must be at least 2 and is limited by the number of cards that can be physically dealt. (eg, Seven Card Stud has a max of 7 players) |
| wcnnum | A standardized set of wildcard combinations, valid values are 0:7. unlike the wcard parameter in wpgame and wpstats, each numeric value matches one and only one set of wildcards: <ul style="list-style-type: none"> • 0 = no wildcards |

	• 1 = "Suicide King" aka "KH" • 2 = "One Eyed Jacks" aka c("JH", "JS") • 3 = c("Suicide King", "One Eyed Jacks") • 4 = "Deuces" aka c("2H", "2C", "2D", "2S") • 5 = c("Deuces", "Suicide King") • 6 = c("Deuces", "One Eyed Jacks") • 7 = c("Deuces", "Suicide King", "One Eyed Jacks")
stats	if TRUE, return the gstat list instead of generating graphs
gtype	Controls which graphs are generated: • "Default" = 4x4 graph array as described below • "Confidence" = Confidence graph for Main and, if any, Split hand • "Hands" = Hands Won graph for Main and, if any, Split hand
split	For gtype = "Confidence" or "Hands", controls how split hand graphs behave: • "Vertical" = Split Hand graph displays beneath Main Hand graph • "Horizontal" = Split Hand graph displays to right of Main Hand graph

Details

This function either accepts input from wpstats or more typically matches game variant details (ngame, players, wnum) to pre-calculated gstat lists. All supported game combinations with 0-7 wildcards and 2-8 players (or less if 8 players aren't possible) have been precalculated.

Precisely what is graphed depends on whether the game has split hands or not, and the graphic device needs a sufficiently large window to show a 4x4 array of graphs with reasonable detail.

Value

if stats = TRUE, prints the gstat list - either gstat parameter, or the precalculated gstat object queried by the ngame, player and wnum combination.

if stats = FALSE, generates a 4x4 graph array.

Example1	Precalculated variant with emergent wildcards and main hand only: wpgraphs(ngame = "Follow the Queen", players = 6, wnum = 1)
Example2	Just the Confidence graphs for Example 1: wpgraphs(ngame = "Follow the Queen", players = 6, wnum = 1, gtype = "Confidence")
Example3	Custom variant with split hand and nonstandard win conditions: wpgraphs(wpstats("High Chicago", 4, "Dr Pepper", numdeal = 10, seed = 100))
Example4	Just the Hands Won graph for example 3: wpgraphs(wpstats("High Chicago", 4, "Dr Pepper", numdeal = 10, seed = 100), gtype = "Hands")

Note

This function is the primary point of the wildpoker package, intended to allow a user to rapidly evaluate the way hands change in value as wildcards, players or game variants change.

Author(s)

Maintainer: Bradley Shanrock-Solberg <greblosb@gmail.com>

References

[poker.com](#) has an excellent reference on game variants which was the primary source for games rules not encountered in my own play.

See Also

[wpstats](#)

Examples

```
# These examples show the gstat output option. For the graphs of these examples,
# see \bold{value} section, above.
#
# example of normal wpgraphs use.
wpgraphs(ngame = "Follow the Queen", players = 6, wcnun = 1, stats = TRUE)

# example of using wpstats to generate a nonstandard combination
# note that if a gstat object is provided (by wpstats), the ngame, players, wcnun aren't used
wpgraphs(wpstats("High Chicago", 4, "Dr Pepper", numdeal = 10, seed = 100), stats = TRUE)
```

wpnotsupported

Poker Games not supported by the wildpoker package

Description

This data set shows games not supported and brief indications of the enhancements required to add them. Anything involving modeling human behavior (drawing, discarding, bidding, passing) will be much more difficult to add in future than purely rules based variants (like extra hands dealt, win conditions, etc)

Usage

wpnotsupported

Format

A data frame with rownames describing the game and 2 variables:

rowname = name of the game (ngame parameter, eg, "Pineapple")

[,1]	Issue	chr	Brief description of the issue type
[,2]	Notes	chr	Brief rules notes touching on game differences

Issue codes, in rough order of difficulty to add to existing logic

1. **strip** = Need to discard cards from deck before dealing
2. **wild logic** = additional wildcard logic required
3. **graphs** = change scale of grouping logic for graphs
4. **win** = Nonstandard Win conditions
5. **fold logic** = Fold player hands under some conditions
6. **card steal** = steal the best visible card from another player
7. **card bid** = choose visible vs no card or blind card logic
8. **discards** = introduce discard-only logic
9. **Draw Round** = introduce discard and draw logic
10. **card pass** = choose card to pass rather than discard

Source

This data set assembled manually based on poker rules

References

[poker.com](#) has an excellent reference on game variants which was the primary source for games rules not encountered in my own play.

See Also

[wprules](#), [wpsupportedgames](#)

wprules

Display Wild Poker Variant Game Rules

Description

This function will Print the rules of a single Wild Poker game variant

Usage

```
wprules(ngame)
```

Arguments

ngame	This is any supported game, such as "Seven Card Stud" or "Baseball". See wpsupportedgames .
-------	---

Details

This program displays values from the [wpsupportedgames](#) data frame with formatting

Value

Prints the following output. Note that max players is capped at 8, even if a deck can support more.

```

GAME :      ngame parameter (game type and max players in parentheses)
DEAL :      cards dealt expressed as hole card, up card or community card - eg Seven Card
             Stud is "2 hole 4 up 1 hole"
BETS :      who leads, ante vs blind bid, betting rounds by card number - eg Seven Card
             Stud is "ante & high up leads - cards 3 4 5 6 7"
WILD :      any wildcards intrinsic to the game - eg Baseball is "3s and 9s" indicating that
             all 3 and 9 cards are wild
MAIN :      Victory conditions for main hand - eg "High - Pair or better to win"
SPLIT:      Victory conditions for split hand - eg "None" for no split hand, can be quite odd
             like "Sum of Spots in 7 card hand"
NOTES:      NOTES: any other information about the game or common variants - eg in Base-
             ball you sometimes have to pay for 3s, 4s and 9s

```

Author(s)

Maintainer: Bradley Shanrock-Solberg <greblosb@gmail.com>

References

poker.com has an excellent reference on game variants which was the primary source for games rules not encountered in my own play.

See Also

[wpsupportedgames](#)

Examples

```

set.seed(52)
wprules("Iron Cross Last Wild")
wprules("Seven Stud Hi-Lo")
wprules("Low Chicago")

```

wpstats

Deal Many Hands of a Wild Poker Variant Game

Description

This function deals a large number of hands of poker and captures the game statistics as observations in a "raw" data frame, then summarizes the results into a "gstat" list, suitable for graphing with the wpgraphs function.

Usage

```
wpstats(ngame, players, wcards = NULL, numdeal = 1000, seed = 52, raw = FALSE)
```

Arguments

ngame	This is any supported game, such as "Seven Card Stud" or "Baseball". See wpsupportedgames .
players	An integer value, must be at least 2 and is limited by the number of cards that can be physically dealt. (eg, Seven Card Stud has a max of 7 players)
wcards	A vector of string values which are either supported wildcard aliases or individual cards. These cards are in addition to any wildcards that are a natural part of the poker game variant chosen with "ngame". The table below shows the supported aliases and their individual card vector equivalents: "Suicide King" or "KH" "One Eyed Jacks" or c("JH", "JS") "Deuces" or c("2H", "2C", "2D", "2S") "Heinz 57" or c("5H", "5C", "5D", "5S", "7H", "7C", "7D", "7S") "Pregnant Threes" or c("3H", "3C", "3D", "3S", "6H", "6C", "6D", "6S", "9H", "9C", "9D", "9S") "Dr Pepper" or c("2H", "2C", "2D", "2S", "4H", "4C", "4D", "4S", "10H", "10C", "10D", "10S")
numdeal	Number of hands to deal, must be positive integer
seed	random number seed set at beginning, must be positive integer
raw	If TRUE the full "raw" data frame is returned instead of the gstat list

Details

This program calls the wpgame function numdeal times, generating a raw data frame. This data frame is then consolidated into a gstat list, whose format depends on ngame.

Value

if raw is TRUE, returns a rawstat data frame, # of rows = numdeal

[,1]	game	chr	pname parameter
[,2]	pnum	numeric	players parameter
[,3]	wild	chr	wcard parameter
[,4]	mwtype	chr	Winning hand type of Main hand
[,5]	swtype	chr	Winning hand type of Split hand
[,6]	mwscore	numeric	score of winning main hand
[,7]	msscore	numeric	Num players score = winning Main score
[,8]	mstype	numeric	Num players type = winning Main type
[,9]	swscore	numeric	score of winning Split hand
[,10]	ssscore	numeric	Num players score = winning Split score
[,11]	sstype	numeric	Num players type = winning Split type
[,12]	mppct	numeric	percent won if Main hand is won

[,13]	sppct	numeric	percent won if Split hand is won
[,14]	bpct	numeric	percent won if Both hands are won
[,15]	wcdeck	numeric	wildcards in deck before the deal
[,16]	wcdeal	numeric	wildcards in deck after the deal

if raw is FALSE, returns a gstat list

\$game	a vector of the pname, players and wcards parameters
\$stats	a vector of the numdeal & seed parameters, and the number of wildcards added to the deck by the wcards parameter
\$pmain	a table used for graphing win percentage chance of Main hand type by number of players
\$cmain	a table used for graphing count of winning Main hand types by number of players
\$wmain	a table used for graphing count of winning Main hand types by wildcard count
\$psplit	a table used for graphing win percentage chance of Split hand type by number of players
\$csplit	a table used for graphing count of winning Split hand types by number of players
\$wsplit	a table used for graphing count of winning Split hand types by wildcard count
\$potpct	a table used for graphing count of percentage of pot won if a hand wins

Note

This function is intended to allow exposing the raw data behind the pre-calculated results normally used by wpgraphs or to allow running for different random number seeds, number of hands dealt, nonstandard additional wildcards or (when games allow) more than eight players.

It takes about .005 seconds to evaluate each hand - 6 players takes 3 times as long as 2 players, a split hand variant takes twice as long as a variant that has only a main hand. Dealing 1000 rounds of most variants takes a minute or two, but Omaha and Courcheval build hands out of subsets of the player hands, requiring up to 70 separate hand evaluations for each player. This means that 1000 hands of those variants can take a couple of hours to generate.

For this reason, gstat values for all supported game variants have already been calculated for 2-8 players and 0-7 additional wildcards - if interested in any of these standard combinations, there is no need to call the wpstats function, wpgraphs has the required gstat list already.

Author(s)

Maintainer: Bradley Shanrock-Solberg <greblosb@gmail.com>

References

poker.com has an excellent reference on game variants which was the primary source for games rules not encountered in my own play.

See Also

[wpgame](#), [wpgraphs](#)

Examples

```
# example of the wpstats run to generate raw statistics
rawstat <- wpstats("Iron Cross Last Wild", 6, "Deuces", numdeal = 10, raw = TRUE)
head(rawstat)

# example of wpstats run to generate a gstat object, used by wpgraphs
wpstats("Seven Stud Hi-Lo", 4, numdeal = 10, seed = 100)
```

wpsupportedgames	<i>Poker Games Supported by the wildpoker package</i>
------------------	---

Description

This data set shows all supported games (in the rownames) and a brief description of each game.
For a better formatted description of an individual game, use [wprules](#)

Usage

```
wpsupportedgames
```

Format

A data frame with rownames describing the game and 10 variables:

rowname = name of the game(ngame parameter eg, "Seven Stud Hi-Lo")

[,1]	Type	chr	"Community" games have community cards, "Stud" games do not
[,2]	Main.Hand	chr	Victory Conditions for Main Hand (see below)
[,3]	Split.Hand	chr	Victory Conditions for Split Hand
[,4]	Wildcards	chr	Wildcards generated by the game variant
[,5]	Deal1	chr	cards dealt in first round (5h1c = 5 hole, 1 community)
[,6]	Deal2	chr	cards dealt in second round (1u = 1 upcard, 3c = 3 community)
[,7]	Deal3	chr	cards dealt in third round (NA = no such round in this game)
[,8]	Deal4	chr	cards dealt in third round (NA = no such round in this game)
[,9]	Deal5	chr	cards dealt in third round (NA = no such round in this game)
[,10]	Misc	chr	notes about the game. A game listed in parentheses is statistically the same.

Win codes:

- HI = High hand wins, no restrictions
- HI - Pair = High hand wins if it is at least a pair

- HI - Flop1 = There are two sets of community cards. Build with 1st
- HI - Flop2 = There are two sets of community cards. Build with 2nd
- LO - A-5 = Low hand wins, Ace is low, straights/flushes ignored
- LO - A-5 8- = As A-5, but need 8-High or lower to win (usually Hi-Lo)
- LO - A-6 = Ace is low, straights/flushes count. Homegame variant.
- LO - 2-7 = Ace is high, straights/flushes count
- LO - 2-7 9- = As 2-7, but need 8-High or lower to win (usually Hi-Lo)

Poker Hand Value: High Card < Pair < 2-Pair < 3-Kind < Straight < Flush < FullHouse < 4-Kind < StrFlush < 5-Kind

Ace can normally be either high or low, and wildcards substitute for any suit or value unless otherwise specified by the poker variant

Wildcards added by the game are in addition to those added using the wcard parameter in the wpgame or wpstats functions.

Minor variants can be created by adding wildcards. As an example my group used to play "**Dangerous Queens**" which was Follow the Queen with Suicide King and One Eyed Jacks wild (the idea being that the wilcards already followed the queens earlier and were wild, but damaged by the experience)

Dangerous Queens would be specified in **wpgame** or **wpstats** as:

```
ngame = "Follow the Queen", wcards = c("Suicide King", "One Eyed Jacks") or alternately wcards = c("KH", "JH", "JS")
```

If using **wpgraphs** directly, **Dangerous Queens** would use the number of added wildcards instead of specifying the wildcards:

```
ngame = "Follow the Queen", wcards =3
```

Source

This data set assembled manually from poker rules

References

[poker.com](#) has an excellent reference on game variants which was the primary source for games rules not encountered in my own play.

See Also

[wprules](#), [wpnotsupported](#)

Index

* **datasets**

- wpnotsupported, [7](#)
- wpsupportedgames, [12](#)

- wildpoker (wildpoker-package), [2](#)
- wildpoker-package, [2](#)
- wpgame, [3](#), [3](#), [12](#)
- wpgraphs, [3](#), [5](#), [12](#)
- wpnotsupported, [3](#), [7](#), [13](#)
- wprules, [3](#), [8](#), [8](#), [12](#), [13](#)
- wpstats, [3](#), [5](#), [7](#), [9](#)
- wpsupportedgames, [3](#), [5](#), [8–10](#), [12](#)